

Specifications

Model	F2690E		F2690	F3710
	2WD		4WD	
Engine				
Model	Kubota D1105		Kubota D1105	Kubota V1505T-IDI+DPF
Type	Liquid-cooled diesel (3 cylinder)			Liquid-cooled diesel (4 cylinder)
Engine gross horsepower*	HP (kW)	24.8 (18.5)	24.8 (18.5)	36.9 (27.5)
Total displacement	cu.in. (cm³)	68.5 (1,123)	68.5 (1,123)	91.4 (1,498)
Air cleaner	Type	Dual element		
	Air restriction indicator	N/A		Standard
Alternator		12 V, 40A		12 V, 60A
Fuel tank capacity				
	U.S. gals. (ℓ)	16.1 (61.0)		
Transmission				
Type	HST (F2/R2)			
Max. travel speed	Forward / Reverse	mph (km/h)	12 (19.3)/6.2 (10)	12.4 (20)/6.8 (11)
4WD mode select		N/A	Auto-assist 4WD with dual acting overrunning clutch/locked 4WD	
Differential lock			Standard	
Cruise control			Optional	
Tire				
Front		23x10.5-12	24x12-12	
Rear		16x6.5-8	18x9.5-8	
Brake				
		Wet discs		
Steering				
Type	Hydrostatic power			
Tilt steering		Standard		
Turn assist brake		Optional		
Dimension				
Tread (F/R)	in. (mm)	38.4 (975) / 34.4 (875)		41.9 (1,063) / 40.2 (1,020)
Wheel base	in. (mm)	51.2 (1,300)		53.1 (1,350)
Overall length	in. (mm)	96.5 (2,450)		99.6 (2,530)
Overall width	in. (mm)	48.8 (1,240)		53.9 (1,370)
Overall height	in. (mm)	77.8 (1,975)		78.1 (1,985)
Weight (without fuel)	lbs. (kg)	1,559 (707)		1,872 (849)
Ground clearance	in. (mm)	6.9 (175)		7.3 (185)
Mower mounting				
Type	Independent live, Shaft drive			
PTO revolution		2,545		2,580
Clutch		Wet multi discs, hydraulic		
Lift system		Hydraulic 2-point hitch		
Tilt angle	Degrees	90		
Tilt assist		Standard		
Weight transfer		Standard		
Others				
ROPS	Standard (ISO21299 and OSHA)			
Fuel gauge		LCD Display (Orange backlight)		LCD Display (White backlight)
Tachometer		LCD Display (Orange backlight)		LCD Display (White backlight)
Toolbox		Standard		
Seat		Reclining suspension seat		
Cup holder		Standard		

Mower Specifications

Model	RCK60P-F39	RCK72P-F39	RCK60R-F36	RCK72R-F36
Discharge	Side discharge		Rear discharge	
Cutting width	in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)
Cutting height	in. (mm)	1 (25) - 5 (129)		
Cutting height adjustment	in. (mm)	Each 0.25 (6.4)		
Depth	in. (mm)	6.0 (152)		5.5 (140)
Deck pan		Welded		
Thickness	in. (mm)	Top: 0.101 (4.2), Side 0,108(4.5)		0.108 (4.5)
Number of blades		3		
Front baffle kit		Standard		N/A
Mulch kit		Optional		

*SAE J1995

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com

©2022 Kubota Corporation



**Kubota
Genuine Parts**
for maximum
performance,
durability and
safety

