

# DM5000

# Specifications

DM5032 - DM5040



Kubota Models	DM5028	DM5032	DM5040
<b>Dimensions and Weight</b>			
Cutting Width (ft)	9'2"	10'6"	13'1"
Weight, approx. (lbs)	2734	2756	2778
Transport Width (ft)	8'6"	9'10"	12'5"
<b>Attachment to Tractor</b>			
Hitch (CAT)	2	2	2
Pin hitch	•	•	•
PTO (RPM)	540/1000	540/1000	540/1000
Minimum PTO horsepower required (hp)	45	65	85
<b>Operation</b>			
Number of disc and knives	8 / 24	8 / 24	10 / 30
Remotes	2	2	2
Cutterbar operating angle	-17 / +17	-17 / +17	-17 / +17
Stubble height (in)	1.79"-3.94"	1.79"-3.94"	1.79"-3.94"
<b>Other Features</b>			
BreakAway	-	-	-
Non-Stop BreakAway	-	-	-
Overrun clutch	•	•	•
Friction clutch	•	•	tt
<b>Optional Equipment</b>			
Swath Board (RH/LH)	-	-	-
Swath Rollers (RH/LH)	o / o	o / o	o / o
High skids (inches) +0.8 / +1.6 / +3.2	• / o / o	• / o / o	• / o / o
Lighting kit	•	•	•
• = standard o = optional - = not available			

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.