

SPECIFICATIONS

MODEL	L2502		L3302		L3902		L4802		L4802-Narrow		L4802		
	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST		Gear-Drive Transmission		HST
	2WD	4WD	4WD						2WD	4WD	4WD		
ENGINE													
Type	Direct injection, vertical, water-cooled 4-cycle diesel												
Engine Gross Power* <i>HP (kW)</i>	24.8 (18.5)		33.0 (24.6)		37.5 (28.0)		48.4 (36.1)						
Engine Net Power** <i>HP (kW)</i>	24.0 (17.9)		31.8 (23.7)		36.3 (27.1)		46.0 (34.3)						
PTO Power <i>HP (kW)</i>	20.5 (15.3)	19.0 (14.2)	28.0 (20.9)	26.1 (19.5)	32.1 (23.9)	30.3 (22.6)	40.5 (30.2)		39.0 (29.1)				
No. of Cylinders	3						4						
Bore & Stroke <i>in. (mm)</i>	3.4 x 3.6 (87 x 92.4)			3.4 x 4.0 (87 x 102.4)									
Total Displacement <i>cu. in. (cm³)</i>	100.5 (1647)			111.4 (1826)				148.5 (2434)					
Rated Speed <i>rpm</i>	2200			2700				2600					
Battery	12V, RC: 110 min, CCA: 580 A	12V, RC: 120 min, CCA: 600 A	12V, RC: 110 min, CCA: 580 A	12V, RC: 120 min, CCA: 600 A	12V, RC: 110 min, CCA: 580 A	12V, RC: 120 min, CCA: 600 A							
Alternator	12V, 40A			12V, 45A									
Fuel Tank Capacity <i>US gal. (ℓ)</i>	11.1 (42)						13.5 (51)						
PTO													
Rear PTO Type	Transmission driven with overrunning clutch	Live-independent hydraulic PTO with PTO brake, wet	Transmission driven with overrunning clutch	Live independent PTO with hydraulic clutch	Live-continuous running	Live independent PTO with hydraulic clutch							
PTO/Engine Speed	540/1910	540/2020	540/2430	540/2470	540/2425	540/2470	540/2475		540/2640				
HYDRAULIC													
Lift Control Type	Position control												
Pump Capacity (main) <i>gpm (ℓ/min)</i>	5.2 (19.5)		6.3 (23.9)				7.8 (29.4)						
(PS) <i>gpm (ℓ/min)</i>	3.1 (11.8)		3.8 (14.5)				4.7 (17.9)						
3-Point Hitch	SAE Category I												
Lift Capacity at Lift Points <i>lbs. (kg)</i>	1874 (850)		1998 (906)				2870 (1300)						
24 in. behind Lift Points <i>lbs. (kg)</i>	1389 (630)		1435 (651)				2320 (1053)						
System Pressure <i>kgf/cm² psi</i>	220 (15.2)		165 (16.2)				180 (17.7)						



* SAE J1995 ** SAE J1349

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

MODEL	L2502		L3302		L3902		L4802		L4802-Narrow		L4802							
	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST	Gear-Drive Transmission		HST		Gear-Drive Transmission		HST					
	2WD	4WD	4WD						2WD	4WD								
TRAVELING SYSTEM																		
Transmission	Constant mesh with synchronized shuttle 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed		Gear shift with synchronized shuttle, 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed		Gear shift with synchronized shuttle, 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed		Constant mesh with synchronized shuttle 8 forward and 8 reverse		Hydrostatic transmission, 3 range speed			
Steering	Integral type power steering										Hydrostatic power steering							
Brake	Mechanical, wet disc type																	
Clutch	Dry type single stage		-		Dry type single stage		-		Dry type dual stage		-		Dry type single stage		-			
TIRE SIZE																		
AG Standard <i>Front/Rear</i>	5.0 - 15 / 11.2 - 24	7.2 - 16 / 11.2 - 24	7.2 - 16 / 11.2 - 24	7.2 - 16 / 11.2 - 24				7.5L - 15 / 14.9 - 24	8.3 - 16 / 14.9 - 24	7.2 - 16 / 11.2 - 24	8.3 - 16 / 14.9 - 24							
TURF Option <i>Front/Rear</i>	23 x 8.50-12 / 13.6-16	25 x 8.50-14 / 13.6-16	25 x 8.50-14 / 13.6-16				27 x 8.50-15 / 44 x 18-20	27 x 10.5-15 / 44 x 18-20	N/A		27 x 10.5-15 / 44 x 18-20							
Indust. Option <i>Front/Rear</i>	N/A	27 x 8.50-15 / 15-19.5	27 x 8.50 - 15 / 15 - 19.5 R4				N/A	10.0- 16.5 / 17.5L - 24	N/A		10.0- 16.5 / 17.5L - 24							
AG/Indust. Hybrid Option <i>Front/Rear</i>	N/A	29 x 9.50 / 43 x 16 - 20 / 27 x 8.50-15 / 15 - 19.5	29 x 9.50-15 / 43 x 16-20 / 27 x 8.50-15 / 15-19.5				N/A											
Traveling Speed with Standard AG Tires <i>mph (km/h)</i>	Forward 0.9 (1.4) - 10.7 (17.3) / Reverse 0.9 (1.4) - 10.7 (17.2)		Forward 0.0 (0.0) - 11.5 (18.5) / Reverse 0.0 (0.0) - 10.3 (16.6)		Forward 1.1 (1.7) - 13.2 (21.2) / Reverse 1.1 (1.7) - 13.2 (21.2)		Forward 0.0 (0.0) - 14.1 (22.7) / Reverse 0.0 (0.0) - 12.7 (20.5)		Forward 1.1 (1.7) - 13.2 (21.2) / Reverse 1.1 (1.7) - 13.2 (21.2)		Forward 0.0 (0.0) - 14.1 (22.7) / Reverse 0.0 (0.0) - 12.7 (20.5)		Forward 1.4 (2.2) - 14.9 (24.0) / Reverse 1.3 (2.1) - 14.3 (23.0)		Forward 1.2 (1.9) - 12.9 (20.8) / Reverse 1.2 (1.9) - 12.4 (20.0)		Forward 0.0 (0.0) - 15.8 (25.4) / Reverse 0.0 (0.0) - 14.2 (22.9)	
DIMENSIONS																		
Overall Length (w/o 3P) <i>in. (mm)</i>	110.6 (2810)	108.5 (2755)										122.8 (3120)	120.3 (3055)	117.7 (2990)	120.3 (3055)			
Overall Width (min. tread) <i>in. (mm)</i>	55.1 (1400)												62.2 (1580)	53.7 (1365)	62.2 (1580)			
Overall Height (w/Foldable ROPS) <i>in. (mm)</i>	91.7 (2330)										94.9 (2410) / 61.2 (1555)***		91.7 (2330)					
Wheelbase <i>in. (mm)</i>	63.8 (1620)	63.4 (1610)						72.6 (1845)										
Min. Ground Clearance <i>in. (mm)</i>	13.6 (345)	13.4 (340)						15.2 (385)		11.6 (295)		15.2 (385)						
Tread Front Tire <i>in. (mm)</i>	41.3 (1050)	43.1 (1095)						50.4 (1280) / 54.3 (1380) / 58.3 (1480) / 62.2 (1580)	45.5 (1155)		41.5 (1055)		45.5 (1155)					
Tread Rear Tire <i>in. (mm)</i>	43.9 (1115) / 47.1 (1195) / 50.8 (1290)						46.5 (1180) / 47.2 (1200) / 51.2 (1300) / 57.1 (1450) / 60.8 (1545)		41.3 (1050)		46.5 (1180) / 47.2 (1200) / 51.2 (1300) / 57.1 (1450) / 60.8 (1545)							
Min. Turning Radius (w/brake, 4WD disengaged) <i>feet (m)</i>	7.9 (2.4)	8.2 (2.5)										8.9 (2.7)	8.5 (2.6)	8.9 (2.7)	8.5 (2.6)			
Weight (with ROPS) <i>lbs. (kg)</i>	2601 (1180)	2811 (1275)	2833 (1285)	2734 (1240)	2778 (1260)	2767 (1255)	2778 (1260)	3296 (1495)	3428 (1555)	3362 (1525)	3549 (1610)							