

Specifications

Model	MX5400				MX6000
	Gear-Drive Transmission		HST		HST
	2WD	4WD	4WD	4WD	
Engine		V2403CR-T			
Type (Make: KUBOTA)		CRS, direct injection, liquid cooled diesel			
Engine gross SAE J1995 power	HP (kW)	55.5 (41.4)		57.0 (42.5)	63.4 (47.3)
Engine net SAE J1349 power	HP (kW)	53.0 (39.5)		53.8 (40.1)	59.5 (44.4)
PTO power	HP (kW)	46.5 (34.7)			51.7 (38.6)
No. of cylinders/Aspiration		4 / Turbocharged			
Total displacement	cu. in. (cm ³)	148.6 (2434)			
Rated speed	rpm	2700			
Fuel tank capacity	US gal. (ℓ)	11.9 (45)			
Air cleaner		Dry-dual element			
Alternator (ROPS / CAB)	Amp	45 / 60			
Transmission					
No. of speeds		8F/8R		3-range speed	
Main gear shift (4 speeds) (ROPS / CAB)		Partially synchronized (3rd & 4th)		-	
Shuttle		Synchronized		Hydrostatic Pedal Operation	
Main clutch		Dry single plate		No clutch	
Brake		Mechanical wet disc			
Differential lock		Rear standard (mechanical)			
PTO					
PTO type		Live independent, hydraulic PTO with PTO brake, wet clutch			
Speed		@540 rpm			
Hydraulic					
Pump capacity (main)	gpm (ℓ/min)	9.5 (35.8)			
Power steering	gpm (ℓ/min)	4.9 (18.6)			
3-point hitch		Category I & II			
Control system		Position (std), Draft (opt)			
	lbs. (kg)	2310 (1050)			
No. of remote valves		Maximum 3 (opt)			
Tires					
Standard ⁽¹⁾	Front/Rear	7.5L-15/14.9-26		9.5-16/14.9-26	
Traveling speeds (w/std. Ag. tires)					
No. of speeds (at rated engine speed)		Forward		Reverse	
First	Fifth	1.1 (1.7)	5.1 (8.2)	1.0 (1.6)	4.7 (7.5)
Second	Sixth	1.5 (2.4)	7.2 (11.6)	1.4 (2.2)	6.6 (10.7)
Third	Seventh	2.4 (3.9)	11.7 (18.9)	2.2 (3.6)	10.7 (17.3)
Fourth	Eighth	3.6 (5.8)	17.3 (27.9)	3.3 (5.3)	15.9 (25.6)
				Forward	Reverse
				L: 0 to	L: 0 to
				4.2 (6.7)	3.7 (6.0)
				M: 0 to	M: 0 to
				8.1 (13.0)	7.3 (11.8)
				H: 0 to	H: 0 to
				17.7 (28.5)	16.0 (25.8)
Other features					
4WD drive system (4WD model)		-		Bevel gear type	
Steering		Hydrostatic Power Steering			
Hood type / Pedal type		Full open hood / Hanging pedals			
Deck type		Flat			
Dimensions					
Overall length (w/o 3P)	in. (mm)	127.8 (3245)		125.8 (3195)	
Overall height (w/Foldable ROPS / CAB)	in. (mm)	95.7 (2430) / 92.7 (2355)			
Overall width (Minimum)	in. (mm)	69.7 (1770)			
Wheelbase	in. (mm)	74.6 (1895)			
Min. ground clearance	in. (mm)	15.2 (385)			
Tread width	Front	in. (mm)	50.4-62.2 (1280-1580)		52.2 (1325)
	Rear	in. (mm)	54.1-58.7 (1375-1490)		
Turning radius (w/ brake)	ft. (m)	8.5 (2.6)		8.9 (2.7)	
Weight	(with ROPS)	lbs. (kg)	3474 (1576)		3734 (1694)
	(with CAB)	lbs. (kg)	-		4268 (1936)

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com

©2019 Kubota Corporation

