

SPECIFICATIONS

Model name		RTV-X			
Grade		Basic	Standard	Premium	
Color		Orange	Orange, Camo	Orange, Camo, Desert Sand	
Engine	Make and model		KUBOTA D1105-E4-UV		
	Type		3-cylinders, 4-cycle, diesel, OHV		
	Displacement	cu.in (cc)	68.5 (1,123)		
	Horsepower	HP (kW) / rpm	24.8 (18.5) @3000		
	Cooling system		Liquid		
	Battery		670 CCA		
Transmission		Variable hydro transmission (VHT-X)			
Gear selection		Hi-Lo range forward, neutral, reverse			
Max. traveling speed		mph (km/h) 0-25 (0-40)			
4WD system	Front differential		Limited-slip differential		
	Rear differential		Foot operated differential lock		
Steering		Hydrostatic power steering			
Brakes	Front / Rear		Wet-disk brakes		
	Parking brake		Rear wheel, hand operated		
Suspension		Independent, Dual A-arms with adjustable spring preload / Independent with coil over shock			
Ground clearance	Front / Rear suspension travel	in. (mm)	8 (205) / 8 (205)		
	Front	in. (mm)	10.5 (266)		
	Rear	in. (mm)	10.4 (263)		
Headlights		LED (Low)	LED (High/Low)		
Occupant Protective System (OPS)	Tubular overhead structure	in. (mm)	2.0 (50.8) steel tube		
	Seat belts		2-point		
	Certification		SAE J2194 and OSHA 1928 ROPS		
Dimensions	Length	in. (mm)	120.3 (3055)	122.4 (3,110)	122.9 (3121)
	Width	in. (mm)	63.2 (1,605)		
	Height, overall	in. (mm)	79.5 (2,020)		
	Front tread centers	in. (mm)	48.8 (1,240)		
	Rear tread centers	in. (mm)	48.8 (1,240)		
	Wheelbase	in. (mm)	80.5 (2,045)		
	Turning radius	ft. (m)	13.1 (4.0)		
Weight	lbs. (kg)	2,050 (930)	2,072 (940)	2,099 (952)	
Towing capacity	lbs. (kg)	1,300 (590)			
Payload capacity	lbs. (kg)	1,521 (690)	1,499 (680)	1,472 (668)	
Cargo bed	Material		Steel		
	Width × Length × Depth	in. (mm)	57.7 (1,465) × 40.5 (1,030) × 11.2 (285)		
	Volume	cu. f. (m ³)	15.2 (0.43)		
	Bed height (unloaded)	in. (mm)	34.9 (887)		
	Capacity	lbs. (kg)	1,102 (500)		
	Hydraulic bed lift		Option	Standard	Standard
	Spray-on bed liner		Not available	(Orange) Available, (Camo) Standard	Standard
3-way open		Not available	Not available	Standard	
Fuel tank capacity	U.S. gal (L)	7.9 (30)			
Sound rating at operator's ear at max rpm		db. (A) 84			
Tires	ATV (All Terrain)		25 × 10-12, 6-ply		
	HDMP (Heavy Duty Multi-Purpose)		25 × 10-12, 6-ply		
Alloy wheel		Option	Option	(Orange, Camo) Available (Desert Sand) Standard	
Standard front guard		Basic	Standard	Premium	