

BV Series

Specifications

BV4580 Premium - BV4580 PremNet



Kubota Models	BV4580Prem	BV4580Net
Weight and Dimensions		
Length (in)	176"	176"
Width (in)	116"	116"
Height (in)	112"	112"
Weight (lbs)	7275	7175
Bale chamber		
Diameter Min (in)	24"	24"
Diameter Max (in)	71"	71"
Bale Width(in)	62"	62"
Bale Formation	8 Belts + 3 Rollers	
Type of Belts	Mato Plate	Mato Plate
Bale Ramp	.	.
Pick-up		
Working Width (in)	86"	86"
Number of Bars	5	
Number of Tines	160	
Tine Spacing (in)	2.36"	2.36"
Windguard	Roller	Roller
Pneumatic Gauge Wheel	.	.
Flare to Flare Pickup	86	
Lift	Hydraulic	
Lift Protection	Radial Clutch	
Intake System		
Rotor feeder	.	.
Protection, cam clutch	.	.
Driveline		
Chain	100	100
1 1/4" Main drive chain	.	.
Wide angle PTO Shaft	.	.
Shear Bolt Protection	.	.
Cam Clutch Protection	.	.
Binding		
Binding	Net/Twine	Net
Monitor	Focus	
Twine	double arm	NA
Operations		
ISOBUS	o	o
Focus Terminal	.	.
IsoMatch Tellus	o	o
Hydraulic Outlets	1SA + 1DA	1SA + 1DA
Wheels and Axles		
14L-16.1SL	.	.
16.5-16.1SL	o	o
Others		
PTO (rpm)	540	540
PTO Protection	Slipclutch	Slipclutch
Minimum Horsepower	70	70
• = standard o = optional - = not available		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.