

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model	L3560				
	DT (4WD)	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)	
Engine	Direct injection, vertical, water-cooled 4 cycle diesel				
Type					
Engine gross power	HP (kW)	37.0 (27.6)			
Engine net power	HP (kW)	35.0 (26.1)			
PTO power	HP (kW)	29.5 (22.0)	28.0 (20.9)		
No. of cylinders / Aspiration	3 / Natural with EGR				
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)			
Total displacement	cu. in. (cc)	111.4 (1826)			
Rated speed	rpm	2700	2600		
Battery	12V, RC: 133 min, CCA: 582A				
Alternator	12V, 40A			12V, 60A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)			
PTO					
Rear PTO					
Revolution	1 speed: 540 rpm				
Type	Independent				
Mid PTO	Option				
Revolution	1 speed: 2000 rpm				
Hydraulic					
Lift control type: Position	Standard				
Draft	Option				
Implement pump	GPM (ℓ/min.)	8.3 (31.5)	8.1 (30.4)		
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)	4.7 (17.9)		
Total hydraulic flow	GPM (ℓ/min.)	13.2 (50.1)	12.8 (48.3)		
3-point hitch	Category I				
Lift capacity at 24 in. behind lift point	lbs. (kg)	2646 (1200)			
Traveling System					
Transmission	FST 8F / 8R	GST 12F/8R	HST Plus (3 Ranges)		
Steering	Hydrostatic power steering				
Brake	Wet disc type				
Clutch	Dry type single stage			—	
Standard tire size^{*2}	Front	7.0-16			
Rear	12.4-24				
Travel speeds					
No. of speeds (at rated engine speed)					
		GST ^{*3}		HST Plus	
		12 Forward	8 Reverse	Forward	Reverse
First	Ninth	1.0 (1.6)	5.7 (9.2)	0.9 (1.5)	H-DS L: 2.1 (3.4)
Second	Tenth	1.4 (2.3)	6.9 (11.1)	1.4 (2.2)	M: 4.3 (6.9)
Third	Eleventh	1.9 (3.1)	11.2 (18.0)	2.2 (3.5)	H: 9.9 (15.9)
Fourth	Twelfth	2.3 (3.7)	16.5 (26.6)	3.2 (5.2)	H: 8.9 (14.3)
Fifth		2.8 (4.5)		4.7 (7.5)	H-DS H: 3.5 (5.6)
Sixth		3.4 (5.4)		6.6 (10.6)	L: 3.2 (5.1)
Seventh		4.0 (6.5)		10.7 (17.2)	M: 7.1 (11.5)
Eighth		4.8 (7.8)		15.8 (25.4)	M: 6.4 (10.3)
					H: 16.5 (26.5)
					H: 14.9 (23.9)
Dimensions					
Overall length (w/o 3P)	in. (mm)	115.0 (2920)			
Overall width (min. tread)	in. (mm)	59.8 (1520)			
Overall height (w/Foldable ROPS)	in. (mm)	97.2 (2470)	90.6 (2300)		
Wheelbase	in. (mm)	71.1 (1805)			
Min. ground clearance	in. (mm)	13.5 (342)			
Tread	Front	(Front tire)			
		in. (mm)			
		45.5 (1155)			
	Rear	(Rear tire)			
		in. (mm)			
		47.2 (1200)			
		51.2 (1300)			
		54.5 (1385)			
		58.3 (1480)			
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)			
Weight (with ROPS)	lbs. (kg)	3483 (1580)	3494 (1585)	3505 (1590)	3880 (1760)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*¹With Master Clutch. *²Kubota offers several tire options. *³Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model		L4060			
		DT (4WD)	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine		Direct injection, vertical, water-cooled 4 cycle diesel			
Type		Direct injection, vertical, water-cooled 4 cycle diesel			
Engine gross power	HP (kW)	42.0 (31.3)			
Engine net power	HP (kW)	40.0 (29.8)			
PTO power	HP (kW)	34.0 (25.4)		32.5 (24.2)	
No. of cylinders / Aspiration		4 / Natural with EGR			
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)			
Total displacement	cu. in. (cc)	148.5 (2434)			
Rated speed	rpm	2700		2600	
Battery		12V, RC: 133 min, 582A			
Alternator		12V, 40A		12V, 60A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)			
PTO					
Rear PTO					
Revolution		1 speed: 540 rpm			
Type		Independent			
Mid PTO		Option			
Revolution		1 speed: 2000 rpm			
Hydraulic					
Lift control type: Position		Standard			
Draft		Option			
Implement pump	GPM (ℓ/min.)	9.8 (37.0)		9.4 (35.6)	
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)		4.7 (17.9)	
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)		14.1 (53.5)	
3-point hitch		Category I			
Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)			
Traveling System					
Transmission		FST 8F/8R	GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering			
Brake		Wet disc type			
Clutch		Dry type single stage		-	
Standard tire size*2					
Front		8.3 - 16			
Rear		14.9 - 24			
Travel speeds					
No. of speeds (at rated engine speed)		GST*3		HST Plus	
		12 Forward / 8 Reverse			
		Forward Reverse		Forward Reverse	
First	Ninth	0.9 (1.5)	5.5 (8.9)	0.9 (1.4)	H-DS L L: 2.1 (3.4)
Second	Tenth	1.3 (2.1)	6.6 (10.7)	1.2 (2.0)	M: 4.4 (7.0)
Third	Eleventh	1.8 (2.9)	10.8 (17.4)	2.1 (3.3)	H: 10.1 (16.2)
Fourth	Twelfth	2.2 (3.5)	16.0 (25.7)	3.0 (4.9)	
Fifth		2.6 (4.2)		4.5 (7.2)	H-DS H L: 3.5 (5.7)
Sixth		3.2 (5.1)		6.3 (10.2)	M: 7.3 (11.7)
Seventh		3.9 (6.3)		10.3 (16.6)	H: 16.8 (27.0)
Eighth		4.7 (7.6)		15.2 (24.5)	L: 1.9 (3.1)
				M: 3.9 (6.3)	
				H: 9.0 (14.5)	
				L: 3.2 (5.2)	
				M: 6.5 (10.5)	
				H: 15.1 (24.3)	
Dimensions					
Overall length (w/o 3P)	in. (mm)	121.5 (3085)			
Overall width (min. tread)	in. (mm)	66.5 (1690)			
Overall height (w/Foldable ROPS)	in. (mm)	97.6 (2480)		91.1 (2315)	
Wheelbase	in. (mm)	74.6 (1895)			
Min. ground clearance	in. (mm)	14.4 (360)			
Tread	Front	(Front tire)			
		in. (mm)			
		45.5 (1155)			
	Rear	(Rear tire)			
		in. (mm)			
		50.6 (1285)			
		56.5 (1435)			
		60.2 (1530)			
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)			
Weight (with ROPS)	lbs. (kg)	3737 (1695)	3748 (1700)	3759 (1705)	4134 (1875)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3, 5, 7 and 9 of the GST are not included in the FST's 8 forward speeds.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model	L4760		
	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine	Direct injection, vertical, water-cooled 4 cycle diesel		
Type			
Engine gross power	HP (kW)	49.0 (36.6)	
Engine net power	HP (kW)	47.0 (35.1)	
PTO power	HP (kW)	41.0 (30.6)	39.5 (29.5)
No. of cylinders / Aspiration	4 / Natural with EGR		
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)	
Total displacement	cu. in. (cc)	148.5 (2434)	
Rated speed	rpm	2700	2600
Battery	12V, RC: 133 min, 582A		
Alternator	12V, 40A		12V, 60A
Fuel tank capacity	US gal. (ℓ)	13.5 (51)	
PTO			
Rear PTO			
Revolution	1 speed: 540 rpm		
Type	Independent		
Mid PTO	Option		
Revolution	1 speed: 2000 rpm		
Hydraulic			
Lift control type: Position	Standard		
Draft	Option		
Implement pump	GPM (ℓ/min.)	9.8 (37.0)	9.4 (35.6)
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)	4.7 (17.9)
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)	14.1 (53.5)
3-point hitch	Category I		
Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)	
Traveling System			
Transmission	GST 12F/8R	HST Plus (3 Ranges)	
Steering	Hydrostatic power steering		
Brake	Wet disc type		
Clutch	Dry type single stage	-	
Standard tire size^{*2}	Front	8.3-16	
	Rear	14.9-24	
Travel speeds			
No. of speeds (at rated engine speed)			
		GST ^{*3}	HST Plus
		12 Forward / 8 Reverse	Forward Reverse
First	Ninth	Forward	Reverse
Second	Tenth	0.9 (1.5)	5.5 (8.9)
Third	Eleventh	0.9 (1.4)	1.2 (2.0)
Fourth	Twelfth	1.3 (2.1)	6.6 (10.7)
Fifth		1.8 (2.9)	10.8 (17.4)
Sixth		2.2 (3.5)	16.0 (25.7)
Seventh		2.6 (4.2)	4.5 (7.2)
Eighth		3.2 (5.1)	6.3 (10.2)
		3.9 (6.3)	10.3 (16.6)
		4.7 (7.6)	15.2 (24.5)
			H-DS L L: 2.1 (3.4) L: 1.9 (3.1)
			M: 4.4 (7.0) M: 3.9 (6.3)
			H: 10.1 (16.2) H: 9.0 (14.5)
			H-DS H L: 3.5 (5.7) L: 3.2 (5.2)
			M: 7.3 (11.7) M: 6.5 (10.5)
			H: 16.8 (27.0) M: 15.1 (24.3)
Dimensions			
Overall length (w/o 3P)	in. (mm)	121.5 (3085)	
Overall width (min. tread)	in. (mm)	66.5 (1690)	
Overall height (w/Foldable ROPS)	in. (mm)	97.6 (2480)	91.1 (2315)
Wheelbase	in. (mm)	74.6 (1895)	
Min. ground clearance	in. (mm)	14.2 (360)	
Tread	Front (Front tire)	51.2 (1300)	
	in. (mm)		
	Rear (Rear tire)	50.6 (1285)	
	in. (mm)	56.5 (1435)	
		60.2 (1530)	
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)	
Weight (with ROPS)	lbs. (kg)	3836 (1740)	3847 (1745) 4222 (1915)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

^{*1}With Master Clutch. ^{*2}Kubota offers several tire options. ^{*3}Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model		L5060	
		GST (4WD)	
Engine			
Type		Direct injection, vertical, water-cooled 4 cycle diesel	
Engine gross power	HP (kW)	52.0 (38.8)	
Engine net power	HP (kW)	50.0 (37.3)	
PTO power	HP (kW)	44.0 (32.8)	
No. of cylinders / Aspiration		4 / Turbo with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)	
Total displacement	cu. in. (cc)	148.5 (2434)	
Rated speed	rpm	2700	
Battery		12V, RC: 133 min, 582A	
Alternator		12V, 45A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)	
PTO			
Rear PTO			
Revolution		1 speed: 540 rpm	
Type		Independent	
Mid PTO		Option	
Revolution		1 speed: 2000 rpm	
Hydraulic			
Lift control type: Position		Standard	
Draft		Option	
Implement pump	GPM (ℓ/min.)	9.8 (37.0)	
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)	
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)	
3-point hitch		Category I & II	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2976 (1350)	
Traveling System			
Transmission		GST 12F/8R	
Steering		Hydrostatic power steering	
Brake		Wet disc type	
Clutch		Dry type single stage	
Standard tire size^{a2}			
Front		9.5-16	
Rear		14.9-26	
Travel speeds			
No. of speeds (at rated engine speed)		GST ^{a3}	
		12 Forward / 8 Reverse	
First	Ninth	Forward	Reverse
Second	Tenth	0.9 (1.5) 5.7 (9.2)	0.9 (1.5)
Third	Eleventh	1.4 (2.2) 6.8 (11.0)	1.3 (2.1)
Fourth	Twelfth	1.9 (3.0) 11.1 (17.9)	2.1 (3.4)
Fifth		2.2 (3.6) 16.5 (26.5)	3.1 (5.0)
Sixth		2.7 (4.4)	4.7 (7.5)
Seventh		3.3 (5.3)	6.5 (10.5)
Eighth		4.0 (6.5)	10.6 (17.1)
		4.8 (7.8)	15.7 (25.3)
Dimensions			
Overall length (w/o 3P)	in. (mm)	126.4 (3210)	
Overall width (min. tread)	in. (mm)	67.3 (1710)	
Overall height (w/Foldable ROPS)	in. (mm)	98.0 (2490)	
Wheelbase	in. (mm)	75.4 (1915)	
Min. ground clearance	in. (mm)	15.4 (392)	
Tread	Front	(Front tire)	
		in. (mm)	52.8 (1340)
	Rear	(Rear tire)	
		in. (mm)	52.2 (1325) 56.3 (1430)
Min. turning radius (w/brake, 4WD disengaged)		feet (m)	
		9.2 (2.8)	
Weight (with ROPS)		lbs. (kg)	
		3979 (1805)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

^{a1}With Master Clutch. ^{a2}Kubota offers several tire options. ^{a3}Speeds 3, 5, 7 and 9 of the GST are not included in the FST's 8 forward speeds.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model	L5460	
	HST (4WD)	HSTC (4WD, CAB)
Engine	Direct injection, vertical, water-cooled 4 cycle diesel	
Type		
Engine gross power	HP (kW)	56.0 (41.8)
Engine net power	HP (kW)	54.0 (40.3)
PTO power	HP (kW)	46.5 (34.7)
No. of cylinders / Aspiration	4 / Turbo with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)
Total displacement	cu. in. (cc)	148.5 (2434)
Rated speed	rpm	2600
Battery	12V, RC: 133 min, 582A	
Alternator	12V, 45A	12V, 60A
Fuel tank capacity	US gal. (ℓ)	13.5 (51)
PTO		
Rear PTO		
Revolution	1 speed: 540 rpm	
Type	Independent	
Mid PTO	Option	
Revolution	1 speed: 2000 rpm	
Hydraulic		
Lift control type: Position	Standard	
Draft	Option	
Implement pump	GPM (ℓ/min.)	9.4 (35.6)
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)
Total hydraulic flow	GPM (ℓ/min.)	14.1 (53.5)
3-point hitch	Category I & II	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2976 (1350)
Traveling System		
Transmission	HST Plus (3 Ranges)	
Steering	Hydrostatic power steering	
Brake	Wet disc type	
Clutch	-	
Standard tire size*2	Front	9.5-16
	Rear	14.9-26
Travel speeds	HST Plus	
No. of speeds (at rated engine speed)		
	Forward	Reverse
First	H-DS L: 2.1 (3.4)	L: 1.9 (3.1)
Second	M: 4.3 (7.0)	M: 3.9 (6.3)
Third	H: 10.1 (16.2)	H: 9.1 (14.6)
Fourth		
Fifth	H-DS H L: 3.6 (5.8)	L: 3.2 (5.2)
Sixth	M: 7.3 (11.8)	M: 6.6 (10.6)
Seventh	H: 16.8 (27.1)	H: 15.2 (24.4)
Eighth		
Dimensions		
Overall length (w/o 3P)	in. (mm)	126.4 (3210)
Overall width (min. tread)	in. (mm)	67.3 (1710)
Overall height (w/Foldable ROPS)	in. (mm)	98.0 (2490)
Wheelbase	in. (mm)	75.4 (1915)
Min. ground clearance	in. (mm)	15.4 (392)
Tread	Front	(Front tire) in. (mm)
		52.8 (1340)
	Rear	(Rear tire) in. (mm)
		52.2 (1325) 56.3 (1430)
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	9.2 (2.8)
Weight (wlth ROPS)	lbs. (kg)	3990 (1810)
		4365 (1980)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*With Master Clutch. **Kubota offers several tire options.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Model	L6060	
	HST (4WD)	HSTC (4WD, CAB)
Engine	Direct injection, vertical, water-cooled 4 cycle diesel	
Type	Direct injection, vertical, water-cooled 4 cycle diesel	
Engine gross power	HP (kW)	62.0 (46.3)
Engine net power	HP (kW)	60.0 (44.8)
PTO power	HP (kW)	53.0 (39.5)
No. of cylinders / Aspiration	4 / Turbo with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)
Total displacement	cu. in. (cc)	148.5 (2434)
Rated speed	rpm	2600
Battery	12V, RC: 133 min, 582A	
Alternator	12V, 45A	12V, 60A
Fuel tank capacity	US gal. (ℓ)	13.5 (51)
PTO		
Rear PTO		
Revolution	1 speed: 540 rpm	
Type	Independent	
Mid PTO	Option	
Revolution	1 speed: 2000 rpm	
Hydraulic		
Lift control type: Position	Standard	
Draft	Option	
Implement pump	GPM (ℓ/min.)	9.4 (35.6)
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)
Total hydraulic flow	GPM (ℓ/min.)	14.1 (53.5)
3-point hitch	Category I & II	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2976 (1350)
Travelling System		
Transmission	HST Plus (3 Ranges)	
Steering	Hydrostatic power steering	
Brake	Wet disc type	
Clutch	-	
Standard tire size^{*2}	Front	9.5-16
	Rear	14.9-26
Travel speeds	HST Plus	
No. of speeds (at rated engine speed)	HST Plus	
	Forward	Reverse
First	H-DS L L: 2.1 (3.4) M: 4.3 (7.0) H: 10.1 (16.2)	L: 1.9 (3.1)
Second		M: 3.9 (6.3)
Third		H: 9.1 (14.6)
Fourth	H-DS H L: 3.6 (5.8) M: 7.3 (11.8) H: 16.8 (27.1)	L: 3.2 (5.2)
Fifth		M: 6.6 (10.6)
Sixth		H: 15.2 (24.4)
Seventh		
Eighth		
Dimensions		
Overall length (w/o 3P)	in. (mm)	126.4 (3210)
Overall width (min. tread)	in. (mm)	67.3 (1710)
Overall height (w/Foldable ROPS)	in. (mm)	98.0 (2490)
Wheelbase	in. (mm)	75.4 (1915)
Min. ground clearance	in. (mm)	15.4 (392)
Tread	Front (Front tire) in. (mm)	52.8 (1340)
	Rear (Rear tire) in. (mm)	52.2 (1325) 56.3 (1430)
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	9.2 (2.8)
Weight (with ROPS)	lbs. (kg)	3990 (1810)
		4365 (1980)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*With Master Clutch. ²Kubota offers several tire options.

L60 Series

Specifications

L3560 - L4060 - L4760 - L5060 - L5460 - L6060



Loader Specifications

Model		LA555	LA805	LA1055
Maximum Lift Height (Pivot pin)	in. (mm)	92.9 (2359)	105.0 (2668)	112.7 (2862)
Clearance with Attachment Dump	in. (mm)	72.4 (1838)	80.4 (2042)	87.4 (2219)
Reach @ Maximum Height	in. (mm)	28.4 (721)	23.7 (601)	26.5 (673)
Maximum Dump Angle	deg.	40	42	46
Reach with Attachment on Ground	in. (mm)	65.3 (1659)	72.3 (1836)	77.8 (1976)
Maximum Rollback Angle	deg.	33	41	42
Digging Depth (When Bucket is level)	in. (mm)	8.4 (213)	4.7 (120)	6.9 (174)
Overall Height in Carry Position	in. (mm)	49.3 (1251)	54.6 (1386)	57.2 (1454)
Square Bucket Width / Struck Capacity	in. (mm)/cu.ft (m ³)	66 (1675) / 8.1 (0.23)	72 (1830) / 10.9 (0.31)	72 (1830) / 10.9 (0.31)
Lift Capacity (Pivot pin)	lbs. (kg)	1190 (540)	1720 (780)	2361 (1071)
Lift Capacity (500mm forward)	lbs. (kg)	899 (408)	1292 (586)	1784 (809)
Breakout Force (500mm forward)	lbs. (N)	1955 (8697)	2554 (11362)	3171 (14107)
Raising Time to Full Height without Load	sec.	2.7	3.2	4.1
Lowering Time without Load (powerdown)	sec.	2.2	2.0	3.9
Attachment Rollback Time	sec.	1.6	1.9	2.5
Attachment Dumping Time	sec.	1.3	1.3	2.6
Rated Flow	l/m (GPM)	31.5 (8.3)	37.0 (9.8)	37.0 (9.8)
Relief Valve PSI	psi (kg/cm ²)	2560 (180)	2630 (185)	2630 (185)
Specs taken from		L3560	L4060	L6060

Backhoe Specifications

Model		BH77	BH92
Digging Depth	in. (mm)	91.0 (2311)	109.8 (2789)
Swing Arc	deg.	180	180
Loading Height	in. (mm)	64.4 (1636)	84.3 (2141)
Reach from Centerline of Swing Pivot	in. (mm)	120.5 (3060)	150.4 (3819)
Reach from Centerline of Rear Axle	in. (mm)	160.6 (4079)	192.3 (4885)
Transport Height	in. (mm)	80.4 (2042)	100.1 (2542)
Bucket Rotation	deg.	182	180
Transport Overhang	in. (mm)	43.9 (1114)	54.0 (1371)
Undercut from Centerline	in. (mm)	25.8 (656)	20.1 (511)
Hydraulic Stabilizer Spread, Down	in. (mm)	67.6 (1717)	92.0 (2336)
Hydraulic Stabilizer Spread, Up	in. (mm)	51.8 (1315)	69.2 (1758)
Digging Force Using Bucket Cylinder	lbs. (kg)	3339 (1514)	4548 (2063)
Digging Force Using Dipperstick Cylinder	lbs. (kg)	2097 (951)	2698 (1224)
Bucket Sizes		10", 12", 16", 24"	12", 16", 24", 30", 36"
Specs Taken from		L3560	L6060