

# Specifications

			KUBOTA					
Model			Z411KW-48	Z421KW-54	Z421KWT-60	Z412KW-48	Z422KW-54	Z422KWT-60
<b>Engine</b>	Model		GH7302V	GH7301V		GH7302V	GH7301V	
	Type		Air cooled 2 cylinders gasoline engine					
	Engine Gross power	HP	22.0	24.0		22.0	24.0	
	Total displacement	cu.in. (cc)	44.3 (726)					
	Starting system		Key switch					
<b>Dimensions</b>	Overall length	in. (mm)	80.9 (2055)					
	Overall width	w/ mower	61.1 (1552)	67.3 (1710)	73.6 (1870)	61.1 (1552)	67.3 (1710)	73.6 (1870)
		w/o mower	48.7 (1236)		54.2 (1376)	48.7 (1236)		54.2 (1376)
	Overall height	w/ ROPS (upright)	69.8 (1772)					
		w/o ROPS (folded)	49.8 (1265)					
<b>Wheelbase</b>		in. (mm)	49.4 (1255)					
<b>Tread/Tire</b>	Tread	Front	37.2 (944)					
		Rear	39.4 (1000)		42.1 (1070)	39.4 (1000)		42.1 (1070)
	Tire size	Front tire	13 x 5.0 - 6, Smooth pneumatic			13 x 6.5 - 6, Smooth pneumatic		
		Rear tire	24 x 9.5 -14, Low profile tire		24 x 12.0 -14, Low profile tire	24 x 9.5 -14, Low profile tire		24 x 12.0 -14, Low profile tire
<b>Weight (w/ mower)</b>		lbs. (kg)	874 (396)	884 (401)	930 (422)	904 (410)	918 (416)	954 (433)
<b>Transmission</b>	Hydro-Gear® Commercial ZT3600®							
<b>Transmission system</b>	2-HST w/Gear reduction							
<b>Speed control</b>	2-hand lever							
<b>Traveling speed range</b>	Forward	mph (km/h)	0 - 10.0 (0 - 16.0)					
	Reverse	mph (km/h)	0 - 5.0 (0 - 8.0)					
<b>Braking system</b>	Cog style parking lock / Foot pedal							
<b>PTO</b>	Type		Belt drive					
	Clutch type		Electric clutch					
	PTO brake		Dry disc					
<b>Mower deck</b>	Model		RCK48P-400Z	RCK54P-400Z	RCK60P-400Z	RCK48P-400Z	RCK54P-400Z	RCK60P-400Z
	Mower deck type		Side discharge					
	Mower lift system		Mechanical / Foot pedal					
	Deck depth	in. (mm)	5.0 (127)					
	Belt type		Belt drive					
	Deck steel thickness	in. (mm)	0.135 (3.4)					
	Anti scalp roller		Rigid					
	Cutting width of mower	in. (mm)	48 (1219)	54 (1372)	60 (1524)	48 (1219)	54 (1372)	60 (1524)
	Number of blades		3					
	Cutting height	in. (mm)	1.5 - 5.0 (38 - 127)					
	Mounting system of mower		Parallel linkage					
	Blade tip speed	FPM	18800	18700	18300	18800	18700	18300
<b>Seat</b>			Deluxe seat			Deluxe seat w/3 inch stroke suspension		
<b>Engine stop system</b>	Key stop							
<b>Fuel tank capacity</b>		Gal. (ℓ)	6.8 (25.7)					
<b>Battery</b>	U1 (12V, RC : 45min, CCA : 300, CA : 410)							
<b>Generator capacity</b>		Amp	15A					
<b>Hour meter</b>	Standard							
<b>Fuel gauge</b>	Sight window							

\*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.\*

\*\*Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

## Attachment & Option Kit



### • Grass Catcher

The optional 7 bushels (250 liters) grass catcher can be attached and detached without ever requiring the use of any tools.



- Mulching Kit
- LED Work Lights
- Seat Suspension Kit
- OCDC
- Maintenance Lift Kit

# Kubota

**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [kubotaUSA.com](http://kubotaUSA.com)

©2020 Kubota Corporation

