

# SPECIFICATIONS

MODEL	MX4900			MX5400			MX6000
	GEAR-DRIVE TRANSMISSION		HST	GEAR-DRIVE TRANSMISSION		HST	HST
	4WD		4WD	2WD	4WD	4WD	4WD
ENGINE	V2403CR-T			V2403CR-T			
Type (Make: KUBOTA)	Liquid-cooled, 4-cylinder diesel						
Engine gross SAE J1995 power	HP (kW)	50.3 (37.5)	51.8 (38.6)	55.5 (41.4)		57.0 (42.5)	63.4 (47.3)
Engine net SAE J1349 power	HP (kW)	47.7 (35.6)	48.5 (36.2)	53.0 (39.5)		53.8 (40.1)	59.5 (44.4)
PTO power	HP (kW)	41.3 (30.8)		46.5 (34.7)			51.8 (38.6)
No. of cylinders/Aspiration	4 / Turbocharged						
Total displacement	cu. in. (cm³)	148.6 (2434)					
Rated speed	RPM	2700					
Fuel tank capacity (ROPS / CAB)	US gal. (l)	13.5 (51) / 11.9 (45)					
Air cleaner	Dry-dual element						
Alternator (ROPS / CAB)	Amp	45 / 60					
TRANSMISSION							
No. of speeds	8F/8R		3-range speed	8F/8R		3-range speed	
Main gear shift (4 speeds) (ROPS / CAB)	Partially synchronized (3rd & 4th)		—	Partially synchronized (3rd & 4th)		—	
Shuttle	Synchronized		Hydrostatic Pedal Operation	Synchronized		Hydrostatic Pedal Operation	
Main clutch	Dry single plate		No clutch	Dry single plate		No clutch	
Brake	Mechanical wet disc						
Differential lock	Rear standard (mechanical)						
PTO							
PTO type	Live independent, hydraulic PTO with PTO brake, wet clutch						
Speed	@540 rpm						
HYDRAULIC							
Pump capacity (main)	gpm (l/min.)	9.5 (35.8)					
Power steering	gpm (l/min.)	4.9 (18.6)					
3-point hitch	Category I & II						
Control system	Position (std), Draft (opt)						
Lift capacity at 24 in. behind lift point	lbs. (kg)	2310 (1050)					
No. of remote valves	Maximum 3 (opt)						

MODEL			MX4900				MX5400				MX6000	
			GEAR-DRIVE TRANSMISSION		HST		GEAR-DRIVE TRANSMISSION		HST		HST	
			4WD		4WD		2WD	4WD	4WD		4WD	
TIRES												
Standard		Front/ Rear	9.5–16/14.9–26				7.5L-15/14.9–26	9.5–16/14.9–26				
TRAVELING SPEEDS (W/STD. AG. TIRES)												
No. of speeds (at rated engine speed)			Forward	Reverse	Forward	Reverse	Forward	Reverse	Forward	Reverse	Forward	Reverse
First	Fifth	mph (km/h)	1.1 (1.7) 5.1 (8.2)	1.0 (1.6) 4.7 (7.5)	L: 0 to 4.2 (6.7) M: 0 to 8.1 (13.0) H: 0 to 17.7 (28.5)	L: 0 to 3.7 (6.0) M: 0 to 7.3 (11.8) H: 0 to 16.0 (25.8)	1.1 (1.7) 5.1 ( 8.2)	1.0 (1.6) 4.7 ( 7.5)	L: 0 to 4.2 (6.7) M: 0 to 8.1 (13.0) H: 0 to 17.7 (28.5)	L: 0 to 3.7 (6.0) M: 0 to 7.3 (11.8) H: 0 to 16.0 (25.8)	L: 0 to 4.2 (6.7) M: 0 to 8.1 (13.0) H: 0 to 17.7 (28.5)	L: 0 to 3.7 (6.0) M: 0 to 7.3 (11.8) H: 0 to 16.0 (25.8)
Second	Sixth	1.5 (2.4) 7.2 (11.6)	1.4 (2.2) 6.6 (10.7)	1.5 (2.4) 7.2 (11.6)			1.4 (2.2) 6.6 (10.7)					
Third	Seventh	2.4 (3.9) 11.7 (18.9)	2.2 (3.6) 10.7 (17.3)	2.4 (3.9) 11.7 (18.9)			2.2 (3.6) 10.7 (17.3)					
Fourth	Eighth	3.6 (5.8) 17.3 (27.9)	3.3 (5.3) 15.9 (25.6)	3.6 (5.8) 17.3 (27.9)			3.3 (5.3) 15.9 (25.6)					
OTHER FEATURES												
4WD drive system (4WD model)			Bevel gear type					Bevel gear type				
Steering			Hydrostatic Power Steering									
Hood type / Pedal type			Full open hood / Hanging pedals									
Deck type			Flat									
DIMENSIONS												
Overall length (w/o 3P)		in. (mm)	125.9 (3195)				127.8 (3245)	125.9 (3195)				
Overall height (w/Foldable ROPS / CAB)		in. (mm)	95.7 (2430) / 92.7 (2355)									
Overall width (Minimum)		in. (mm)	69.7 (1770)									
Wheelbase		in. (mm)	74.6 (1895)									
Min. ground clearance		in. (mm)	15.2 (385)									
Tread width		Front in. (mm)	52.2 (1325)				50.4–62.2 (1280–1580)	52.2 (1325)				
		Rear in. (mm)	54.2–58.7 (1375–1490)									
Turning radius (w/ brake)		ft. (m)	8.9 (2.7)				8.5 (2.6)	8.9 (2.7)				
WEIGHT												
With ROPS		lbs. (kg)	3716 (1686)		3734 (1694)		3474 (1576)	3716 (1686)	3734 (1694)			
With CAB		lbs. (kg)	4251 (1928)		4268 (1936)			4251 (1928)	4268 (1936)			

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

