

Specifications

Model	L3560				L4060				
	HST-LE (4WD, ROPS)		HSTC-LE (4WD, CAB)		HST-LE (4WD, ROPS)		HSTC-LE (4WD, CAB)		
Engine	Direct injection, vertical, water-cooled 4-cycle diesel								
Type									
Engine gross power*1	HP (kW)	37.0 (27.6)				42.0 (31.3)			
Engine net power*2	HP (kW)	35.0 (26.1)				40.0 (29.8)			
PTO power	HP (kW)	28.0 (20.9)				32.5 (24.2)			
No. of cylinders / Aspiration	3 / Natural with EGR				4 / Natural with EGR				
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)							
Total displacement	cu. in. (cc)	111.4 (1826)				148.5 (2434)			
Rated speed	rpm	2600							
Battery	12V, RC: 133 min, CCA: 582A								
Alternator		12V, 40A		12V, 60A		12V, 40A		12V, 60A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)							
PTO									
Rear PTO									
Revolution	1 speed: 540 rpm								
Type	Independent								
Mid PTO	Option								
Revolution	1 speed: 2000 rpm								
Hydraulic									
Lift control type: Position	Standard								
Draft	Option								
Implement pump	GPM (ℓ/min.)	8.1 (30.4)				9.4 (35.6)			
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)							
Total hydraulic flow	GPM (ℓ/min.)	12.8 (48.3)				14.1 (53.5)			
3-point hitch	Category I								
Lift capacity at 24 in. behind lift point	lbs. (kg)	2646 (1200)				2760 (1250)			
Travelling System									
Transmission	HST Plus (3 Ranges)								
Steering	Hydrostatic power steering								
Brake	Wet disc type								
Standard Tire Size*3	Front	7.0-16				8.3-16			
	Rear	12.4-24				14.9-24			
Travel Speeds	HST Plus								
	mph (km/h)	Forward		Reverse		Forward		Reverse	
		H-DS L	L: 2.1 (3.4)	L: 1.9 (3.0)	H-DS H	L: 3.5 (5.6)	L: 3.2 (5.1)	H-DS L	L: 2.1 (3.4)
		M: 4.3 (6.9)	M: 3.9 (6.2)	M: 7.1 (11.5)	M: 6.4 (10.3)	M: 4.4 (7.0)	M: 3.9 (6.3)	M: 7.3 (11.7)	M: 6.5 (10.5)
		H: 9.9 (15.9)	H: 8.9 (14.3)	H: 16.5 (26.5)	H: 14.9 (23.9)	H: 10.1 (16.2)	H: 9.0 (14.5)	H: 16.8 (27.0)	H: 15.1 (24.3)
Dimensions									
Overall length (w/o 3P)	in. (mm)	115.0 (2920)				121.5 (3085)			
Overall width (min. tread)	in. (mm)	59.8 (1520)				66.5 (1690)			
Overall height (w/Foldable ROPS)	in. (mm)	97.2 (2470)		90.6 (2300)		97.6 (2480)		91.1 (2315)	
Wheelbase	in. (mm)	71.1 (1805)				74.6 (1895)			
Min. ground clearance	in. (mm)	13.5 (342)				14.2 (360)			
Tread	Front (Front tire) in. (mm)	45.5 (1155)							
	Rear (Rear tire) in. (mm)	47.2 (1200), 51.2 (1300), 54.5 (1385), 58.3 (1480)				50.6 (1285), 56.5 (1435), 60.2 (1530)			
Min. Turning Radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)							
Weight (with ROPS)	lbs. (kg)	3649 (1655)		3880 (1760)		3748 (1700)		4134 (1875)	

*1 SAE J1995 *2 SAE J1349 *3 Kubota offers several tire options.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



For Earth, For Life
Kubota



KUBOTA DIESEL TRACTOR L60 Limited Edition Series L3560/L4060

Get the Kubota Limited Edition's best in class comfort and quality at an affordable price.



©2020 Kubota Corporation



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

**Kubota
Genuine Parts**
for maximum
performance,
durability and
safety



Affordability plus industry leading features and comfort all-in-one.

AFFORDABILITY. QUALITY. COMFORT.

The L60LE Series has been positioned uniquely between our L01 and Grand L60 Series. With the L60LE Series you get premium features at an affordable cost that you will not find on other brands. You would expect to pay more for features such as the HST Plus transmission, larger chassis size, low engine noise, smooth loader operation and spacious operator platform on all models, but the L60LE Series provides you all these premium features at an affordable price. The L60LE Series gives you the best in class when it comes to affordability, quality and comfort.



L3560LE	HST ROPS	37.0 Engine HP
	HST Cab	37.0 Engine HP
L4060LE	HST ROPS	42.0 Engine HP
	HST Cab	42.0 Engine HP

L3560/L4060 LIMITED EDITION

AFFORDABILITY / INDUSTRY LEADING FEATURES



THE AFFORDABLE OPTION

Providing you deluxe features at an affordable price, the new L60LE Series meets the demands of customers by providing features that are most commonly used with the option to add select features.

MULTIPLE MODEL LINEUP

Kubota understands that not every customer's needs are the same. With that in mind, Kubota offers multiple options for customers throughout the L60LE Series lineup. Ranging from 37.0 to 42.0 gross horsepower, Kubota's L60LE Series offers four affordable horsepower models to choose from based on your application and implements requirements.

ACCESSORIES TO CUSTOMIZE YOUR NEEDS

- Air ride seat
- Canopies
- Mid-PTO
- Up to 3 remote valves
- Top and tilt kit
- Draft control
- Front and rear weights
- Agricultural, Turf or industrial tires
- Plus many more!

Tire options

Kubota's L60LE Series offers a wide variety of tire tread types and sizes. Agricultural tires are designed for heavy-duty field work requiring maximum traction. Turf tires are designed for mowing with minimal ground disruption. And Industrial tires are designed for loader work requiring a more everyday use style tread.



AFFORDABILITY / QUALITY



AFFORDABILITY / COMFORT

OPERATOR STATION

The L60LE Series boasts a wide range of deluxe features and functions to reduce fatigue and maintain productivity. With reduced noise and vibration levels, an improved deluxe seat, power steering and a cup holder, you can rest assured that your comfort comes first—so much so that you might forget you're working.

STANDARD COMFORT FEATURES

- Deluxe suspension seat
- More legroom
- Ergonomic lever layout
- Tilt steering wheel
- Electric PTO switch
- Rounded fender / Wide step
- Cup holder
- Full open hood
- Ground level fuel tank fill



KUBOTA BUILT DIESEL ENGINE

The L60LE Series is equipped with a world-renowned Kubota built diesel engine. Designed to withstand all the heavy loads and potential wear and tear, the L60LE Series reduces maintenance. Additionally, the Kubota diesel engine is designed to provide a smooth and quiet operation especially under higher engine rpm applications such as loader work.



DELUXE GRAND CAB

Enjoy comfort with the wide, spacious cab and standard deluxe suspension seat. You can also customize your operating position with the standard tilt steering and the seat position adjustment with swivel features.



STANDARD EQUIPMENT FOR CAB

- AC / Heater with internal/ external ventilation
- 60 Amp alternator
- Front wiper and washer
- Interior light
- Deluxe high-back reclining seat with swivel
- Wide fenders

OPTIONAL EQUIPMENT FOR CAB

- Rear windshield wiper
- Rear window defogger
- Rear work lights
- Radio/CD player
- Air-ride seat



Comfortable, Easy to Use Industry-leading HST transmission "HST Plus"

With extraordinary precision, HST Plus's automated control of both the HST pump and drive motor gives you optimal performance, regardless of the task, working conditions, or operator expertise. Kubota's easy-to-use HST Plus transmission provides better control and increased productivity. You will not operate an easier, more comfortable HST on the market.



HST mode selection (Stall Guard Plus & Auto H-DS)

Manual mode puts you in complete control of the tractor. Kubota's Stall Guard PLUS protects the engine and PTO from stalling in heavy-duty applications. AUTO H-DS (Auto Hydro Dual Speed) enables automatic Hi/Lo shifting, and in conjunction with Stall Guard PLUS, keeps your tractor running optimally at all times.

Auto Throttle Advance

This function synchronizes tractor speed and engine revolution. This greatly simplifies tractor operation and helps reduce fuel consumption.



Industry leading performance

Best-in-class quality, reliability and high performance with the Kubota built powertrain, metal hood and fenders, and cast-iron axles. One of the biggest 3-point hitch lift capacity, loader lift capacity and hydraulic flow in this class.

FRONT LOADERS

INDUSTRY LEADING FRONT LOADER

Designed to match the performance of the L60LE Series, LA555 and LA805 front loaders ensure precise operation and improved productivity. With the standard-equipped front loader valve and lever, the front loaders feature outstanding lift capacity and lift height for an impressive performance with each load. Plus, loader lift and bucket dump cycle speeds are amazingly fast.

STANDARD FRONT LOADER FEATURES

- 2-lever quick coupler
- Loader valve and joystick
- Grill guard
- Bucket level indicator



Shown with 2-lever hydraulic quick coupler



OPTIONAL FRONT LOADER FEATURES

- 66"-72" light material, square back and heavy duty buckets
- 60" 4-in-1 bucket
- Third function valve
- Bale spears
- Pallet forks
- Hydraulic 2-lever quick coupler*
- Hydraulic spill guard*
- Single lever hose quick coupler*

*Only available on LA805

Front Loader Specifications

Model		LA555	LA805
Maximum Lift Height (pivot pin)	in. (mm)	96.4 (2448)	104.7 (2659)
Clearance with Attachment Dump	in. (mm)	75.9 (1928)	80.0 (2033)
Reach @ Maximum Height	in. (mm)	28.4 (721)	23.3 (591)
Maximum Dump Angle	deg.	40	42
Reach with Attachment on Ground	in. (mm)	66.6 (1691)	72.4 (1840)
Maximum Rollback Angle	deg.	30	41
Digging Depth (when bucket is level)	in. (mm)	4.9 (124)	4.7 (120)
Overall Height in Carry Position	in. (mm)	52.7 (1338)	54.6 (1386)
Square Bucket Width / Struck Capacity	in. (mm)/cu.ft (m³)	66 (1675) / 8.1 (0.23)	72 (1830) / 10.9 (0.31)
Lift Capacity (pivot pin)	lbs. (kg)	1190 (540)	1715 (778)
Lift Capacity (500mm forward)	lbs. (kg)	899 (408)	1290 (585)
Breakout Force (500mm forward)	lbs. (N)	2030 (9029)	2549 (11341)
Raising Time to Full Height without Load	sec.	2.7	3.2
Lowering Time without Load (powerdown)	sec.	2.2	2.0
Attachment Rollback Time	sec.	1.6	1.9
Attachment Dumping Time	sec.	1.3	1.3
Rated Flow	l/m (GPM)	31.5 (8.3)	37.0 (9.8)
Relief Valve PSI	psi (kg/cm²)	2560 (180)	2630 (185)
Specs taken from		L3560	L4060

BACKHOES

PERFORMANCE-MATCHED KUBOTA-BUILT BACKHOES

The BH77 and BH92 backhoes are "performance-matched" with the L60LE Series to deliver more power and greater capacity. And thanks to the full-flat deck, the backhoes deliver optimal legroom for maximum operator comfort. They are equipped with a quick attach/detach mounting system.

BH77 Backhoe

The BH77 backhoe, available on the L3560HST-LE, is a great solution when you are working in small or restricted areas. It offers easy attachment and detachment and can dig to depths of 7.6 feet.

BH92 Backhoe

The BH92 backhoe, designed for the L60LE Series, boasts a curved boom for deeper digging. It offers easy attachment and detachment and can dig to depths of 9.2 feet.



Backhoe Specifications

Model		BH77	BH92
Digging Depth	in. (mm)	91.0 (2311)	109.8 (2789)
Swing Arc	deg.	180	180
Loading Height	in. (mm)	64.4 (1636)	84.3 (2141)
Transport Height	in. (mm)	80.4 (2042)	100.1 (2542)
Bucket Rotation	deg.	182	180
Digging Force using Bucket Cylinder	lbs. (kg)	3339 (1514)	4548 (2063)
Digging Force using Dipperstick Cylinder	lbs. (kg)	2097 (951)	2698 (1224)
Bucket Sizes		10", 12", 16", 24"	12", 16", 24", 30", 36"
Specs taken from		L3560	L6060

FRONT HITCH ATTACHMENTS



Snow blower

FRONT HITCH AND FRONT ATTACHMENT OPTIONS

- Utility and commercial snow blowers
- Front blade
- Rotary sweeper
- Flail mower
- Manual or fully automatic front hitch