

# BV Series

# Specifications

## BV4160 Economy



Kubota Models	BV4160 ECONO
<b>Weight and Dimensions</b>	
Length (in)	176"
Width (in)	99"
Height (in)	106"
Weight (lbs)	5842
<b>Bale chamber</b>	
Diameter Min (in)	31"
Diameter Max (in)	65"
Bale Width(in)	47"
Bale Formation	5 Belts + 3 Rollers
Endless Belts	-
Bale Ramp	•
<b>Pick-up</b>	
Working Width (in)	67"
Number of Tine Rows	4
Tine Spacing (in)	2.36"
Windguard	Crop Deflector
Pneumatic Gauge Wheel	•
<b>Intake System</b>	
Fork Feeder	•
Protection, cam clutch	•
SuperCut-14 Knives	-
Single Knife Protection	-
Knife Group Selection	-
Unblocking System	-
<b>Driveline</b>	
1 Main chain	•
1 1/4" Main drive chain	-
Wide angle PTO Shaft	•
Shear Bolt Protection	•
Cam Clutch Protection	-
<b>Binding</b>	
Twine (double) / Capacity	• / 8
Net/Capacity	o / 3
<b>Operations</b>	
ISOBUS	-
Focus Terminal	•
IsoMatch Tellus	-
Hydraulic Outlets	1SA + 1DA
<b>Wheels and Axles</b>	
11.5/80-15	•
15.0/55-17	-
19.0/45-17	o
500/45-22.5	-
<b>Others</b>	
PTO (rpm)	540
Min. power requirem. (hp)	55

• = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.