



For Earth, For Life
Kubota

W/SZ

COMMERCIAL-GRADE MOWERS

Walk-Behind & Stand-On

Whatever the job, from small to large, there's a Kubota walk-behind or stand-on mower offering professionals the durability, convenience, and performance they need.



COMMERCIAL WALK-BEHIND MOWERS

W Series

Kubota Compact Durability

Kubota's 21" commercial mowers combine cutting, mulching, and bagging performance with great durability. The serviceable wheels, with ball bearings and replaceable tires, and a cast aluminum deck meet the demands of lawn-care professionals.

These mowers are designed for maximum compactness, durability, and convenience, and include the following features:

- › Die-cast aluminum deck provides long-lasting rust-proof durability.
- › 2 N 1 convertible bag and mulch, with a 2.5 bushel bag capacity and easy mulch conversion.
- › Die-cast aluminum wheels with dual ball bearings give smooth rolling durability.
- › Replaceable steel deck edge guards protect the deck easily and affordably.
- › Mow confidently with a 2-year warranty.





W Series	WGC6 / 21" DECK
Engine Type	Kawasaki FJ180
Horsepower (gross)*	5.5
Speed (MPH)	4.1
Transmission	3-speed Gear Drive
Deck Type	High Vacuum, Rear Discharge
Deck	Heavy-duty cast aluminum
Cutting Height	.75–4"
Starter	Manual
Hand Controls	Blade Brake Clutch
Deck Drive	Blade Brake Clutch
Front & Rear Tires	9 x 2.25
Wheel Construction	Die-Cast Aluminum w/ Dual Ball Bearings
Weight (lb)	130
Length	64"
Height	38–43"
Warranty	2 Yr - Unlimited Hours



*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

COMMERCIAL WALK-BEHIND MOWERS

W Series

Kubota Precision and Power

Kubota Commercial Walk-Behind Mowers are tough enough for every kind of turf. Each mower is built to put precise cutting power in your hands. With our new ergonomic bull horn control hydro drive models, mowing with our walk-behind mowers has never been easier.

These machines are perfectly tuned to optimize power and cutting width so that mower speed and horsepower increase with each deck size option. These Kubota Walk-Behind Mowers are built to out-perform with the following cutting-edge features:

- › Never let a flat tire stop you again with puncture-proof, semi-pneumatic front tires on all models.
- › Precision-ground, double-sealed bearings and heavy-duty, maintenance-free spindles are engineered to prolong cutting performance and efficiency.
- › Integrated Hydro-Gear transmissions with speeds up to 6.5 MPH.
- › New ergonomic bull horn control models available. Ergonomic handles reduce fatigue and improve operation.
- › Take on properties from ¼ to 3 acres with a resilient 5-hour run time.
- › Mow confidently with a 2-year warranty.



WG14NC / 36" Deck | **WHF14NC / 36" Deck** | **WHF15NC / 48" Deck** | **WHF19NC / 52" Deck**



W Series	WG14 / 36" DECK	WHF14 / 36" DECK	WHF15 / 48" DECK	WHF19 / 52" DECK
Engine Type	Kawasaki FS481V		Kawasaki FS541V	Kawasaki FX600V
Horsepower (gross)*	14.5		15	19
Speed (MPH)	5.1	-	6.0	6.7
Transmission	5-Speed Peerless gear box		2-ZT-2800 Hydrostatic Transmission	
Deck Type	Fabricated Fixed		Fabricated Float with Wear band	
Deck	7 ga deck with 7 ga skirts		10 ga deck with 10 ga top and 7 ga skirts	
Cutting Height	1.5-4.5"			
Starter	Manual		Electric	
Hand Controls	Pistol Grip		Ergonomic Bull Horn	
Spindle Bearings	-		1" shaft with maintenance-free precision ground double-sealed bearings	
Deck Drive	Warner Mag Stop 125 ft-lb electric clutch		Warner Mag Stop 105 ft-lb electric clutch	
Front Tires / Rear Tires	9 x 3.50-4 (No-Flat) / 13 x 5-6 4-ply	11"x6"-5" (No Flat) / 20"x5"-10"	11"x6"-5" (No Flat) / 20"x8"-10"	11"x6"-5" (No Flat) / 20"x8"-10"
Brake	Band Type		Hydrostatic Dynamic Braking	
Weight (lb)	464	500	600	700
Length / Height	78" / 40.3"		78" / 43"	
Warranty	2 Yr - Unlimited Hours			

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

COMMERCIAL STAND-ON MOWERS

SZ Series

Kubota Comfort and Productivity

Kubota Stand-On Mowers are some of the fastest machines in their class, while delivering superior comfort and durability. The mower deck delivers superior mowing performance that professionals demand. You'll be able to get more done in even the tightest spaces.

These Stand-On Mowers are designed to offer a smooth and easy ride, all while delivering high-end operational power and maneuverability. The SZ Series stand-on mowers feature the following:

- › All models are powered by Kawasaki commercial-grade engines, including an EFI option.
- › Adjustable reference bar and dampers give the operator a personalized experience.
- › Toolless adjustable tracking keeps you driving straight.
- › Kubota Stand-On Mowers provide exceptional transport speed, allowing maximum speeds of up to 11 mph.
- › The fuel tank is housed inside the control tower, protecting the fuel tank and allowing for a lower center-of-gravity design.
- › Wide and angled operator platform offers ample foot space, as well as the option of flipping up the platform to easily walk behind.
- › Easy access to maintenance points reduces downtime.
- › Mow confidently with a 2-year warranty.



SZ19 / 36" Deck | **SZ22** / 48" Deck | **SZ26** / 52" / 61" Decks



SZ Series	SZ19 / 36" DECK	SZ22 / 48" DECK	SZ26 / 52" DECK / 61" DECK
Engine Type	Kawasaki FX600V	Kawasaki FX691V	Kawasaki FT730V-EFI
Horsepower (gross)*	19	22	26
Fuel Capacity (gal)	5.1	6.5	
Speed (MPH)	9	10.5	11
Transmission	Hydro-Gear ZT3100	Hydro-Gear ZT3600	
Deck Type		Floating Fabricated Steel with Wear band	
Deck	7 ga deck with 7 ga skirts	Adjustable front baffle (-2 models) 10 ga deck with 10 ga top and 7 ga skirts	
Cutting Height		1.5–4.5"	
Starter		Electric	
Spindle Bearings	1" shaft with maintenance-free precision ground double-sealed bearings		
Deck Drive	Warner Mag Stop 125 ft-lb electric clutch	Warner Mag Stop 200 ft-lb electric clutch	
Front Tires / Rear Tires	11"x6"-5"(-2 models) 11 x 4-5 (no-flat) / 20 x 8-10	13"x6.5"-6"(-2 models) 13 x 6.5-6" (no-flat) / 23 x 8.5-12	13"x6.5"-6"(-2 models) 13 x 6.5-6" (no-flat) / 23 x 10.5-12
Brake	Cog Style Parking Lock / Hand Lever		
Weight (lb)	831	965	997 (52") / 1034 (61")
Length / Height	62.5" / 45"	63.75" / 45.75"	
Warranty	2 Yr - Unlimited Hours		

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



GET YOUR WALK-BEHIND AND STAND-ON ACCESSORIES

Accessory	WGC6	WG14NC-36 (-2)	WH15NC-48 (-2)	WHF19NC-52 (-2)	SZ19NC-36 / (-2) WHF14NC-36-2	SZ22NC-48 / (-2) WHF15NC-48-2	SZ26NC-52 / (-2) WHF19NC-52-2	SZ26NC-61 / (-2)
Mulch Kit	N/A	WMK36	WMK48	WMK52	SMK36	SMK48 / (-2)	SMK52 / (-2)	SMK61 / (-2)
Discharge Plate	N/A	WBP36	WBP48	WBP52	SBP36	SBP48 / (-2)	SBP52 / (-2)	SBP61 / (-2)
Weight Kit	N/A	WWK01	N/A	N/A	SWK36	SWK48		
Cold Start Kit	N/A	N/A	WCS00		N/A			
Engine Guard Kit	SC-4175821	N/A		N/A				
Grass Catcher Bracket Kit	N/A	N/A	N/A	WGC802	N/A			
Standard Grass Catcher 36"-61" (Aluminum Accelerator Type)	N/A	N/A		SGC61				
JUMBO Grass Catcher 48"-61" (Aluminum Accelerator Type)	N/A	N/A		SGCJ61				

*Anything that lists a (-2) means that accessory fits a -2 model unit.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, expressed or implied, or any liability from the use of this brochure. For complete warranty, safety, and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global website. Kubota does not provide parts, warranty, or service for any product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 | Tel 888-4-KUBOTA

Visit our web site at: www.kubotaUSA.com