

Specifications

Model	L3560				L4060				
	HST-LE (4WD, ROPS)		HSTC-LE (4WD, CAB)		HST-LE (4WD, ROPS)		HSTC-LE (4WD, CAB)		
Engine									
Type	Direct injection, vertical, water-cooled 4-cycle diesel								
Engine gross power*1	HP (kW)	37.0 (27.6)			42.0 (31.3)				
Engine net power*2	HP (kW)	35.0 (26.1)			40.0 (29.8)				
PTO power	HP (kW)	28.0 (20.9)			32.5 (24.2)				
No. of cylinders / Aspiration	3 / Natural with EGR				4 / Natural with EGR				
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)							
Total displacement	cu. in. (cc)	111.4 (1826)			148.5 (2434)				
Rated speed	rpm	2600							
Battery	12V, RC: 133 min, CCA: 582A								
Alternator		12V, 40A		12V, 60A		12V, 40A		12V, 60A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)							
PTO									
Rear PTO Revolution	1 speed: 540 rpm								
Type	Independent								
Mid PTO Revolution	1 speed: 2000 rpm								
Hydraulic									
Lift control type: Position	Standard								
Draft	Option								
Implement pump	GPM (ℓ/min.)	8.1 (30.4)			9.4 (35.6)				
Power steering pump	GPM (ℓ/min.)				4.7 (17.9)				
Total hydraulic flow	GPM (ℓ/min.)	12.8 (48.3)			14.1 (53.5)				
3-point hitch	Category I								
Lift capacity at 24 in. behind lift point	lbs. (kg)	2646 (1200)			2760 (1250)				
Travelling System									
Transmission	HST Plus (3 Ranges)								
Steering	Hydrostatic power steering								
Brake	Wet disc type								
Standard Tire Size*3									
Front	7.0-16				8.3-16				
Rear	12.4-24				14.9-24				
Travel Speeds									
HST Plus					HST Plus				
mph (km/h)	Forward	Reverse	Forward	Reverse	Forward	Reverse	Forward	Reverse	
	H-DS L: 2.1 (3.4)	L: 1.9 (3.0)	H-DS H: 3.5 (5.6)	L: 3.2 (5.1)	H-DS L: 2.1 (3.4)	L: 1.9 (3.1)	H-DS H: 3.5 (5.7)	L: 3.2 (5.2)	
	M: 4.3 (6.9)	M: 3.9 (6.2)	M: 7.1 (11.5)	M: 6.4 (10.3)	M: 4.4 (7.0)	M: 3.9 (6.3)	M: 7.3 (11.7)	M: 6.5 (10.5)	
	H: 9.9 (15.9)	H: 8.9 (14.3)	H: 16.5 (26.5)	H: 14.9 (23.9)	H: 10.1 (16.2)	H: 9.0 (14.5)	H: 16.8 (27.0)	H: 15.1 (24.3)	
Dimensions									
Overall length (w/o 3P)	in. (mm)	115.0 (2920)			121.5 (3085)				
Overall width (min. tread)	in. (mm)	59.8 (1520)			66.5 (1690)				
Overall height (w/Foldable ROPS)	in. (mm)	97.2 (2470)		90.6 (2300)		97.6 (2480)		91.1 (2315)	
Wheelbase	in. (mm)	71.1 (1805)			74.6 (1895)				
Min. ground clearance	in. (mm)	13.5 (342)			14.2 (360)				
Tread	Front (Front tire) in. (mm)	45.5 (1155)							
	Rear (Rear tire) in. (mm)	47.2 (1200), 51.2 (1300), 54.5 (1385), 58.3 (1480)			50.6 (1285), 56.5 (1435), 60.2 (1530)				
Min. Turning Radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)							
Weight (with ROPS)	lbs. (kg)	3649 (1655)		3880 (1760)		3748 (1700)		4134 (1875)	

*1 SAE J1995 *2 SAE J1349 *3 Kubota offers several tire options.

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2020 Kubota Corporation



**Kubota
Genuine Parts**
for maximum
performance,
durability and
safety

