Specifications

Model			F2510E	F2510	F3710	
			2WD	4\	VD	
Engine						
Model			Kubota D1105	Kubota D1105	Kubota V1505-CR-TE5-FM2	
Туре			Liquid-cooled of	diesel (3 cylinder)	Liquid-cooled diesel (4 cylinder)	
Engine gross horsepo	ower*	HP (kW)	23.3 (17.4)	23.3 (17.4)	36.9 (27.5)	
Total displacement		cu.in. (cm³)	68.5 (1,123)	68.5 (1,123)	91.4 (1,498)	
Air cleaner	Туре			Dual element		
	Air restriction indicator		N/A Standard			
Alternator			12.1	12 V, 60A		
Fuel tank capacity		U.S. gals.(ℓ)	12 V, 40A 12 V, 60A 12.1 (61.0)			
Transmission		0.0. ga.o. (c)		10.1 (0.10)		
Type				HST (F2/R2)		
Max. travel speed	Forward / Reverse	mph (km/h)	12 (19.4)/6.6 (10.5))/6.9 (11)	
4WD mode select			N/A		g overrunning clutch/locked 4WD	
Differential lock				Standard	g	
Cruise control				Optional		
Tire				Ориона		
Front			23×10.5-12	24×	12-12	
Rear			16×6.5-8	18×9	9.5 - 8	
Brake			10/10/0	Wet discs		
Steering				1101 0.000		
Type				Hydrostatic power		
Tilt steering			Standard			
Turn assist brake			Optional			
Dimension				op.iona.		
Tread (F/R)		in. (mm)	38.4 (975) / 34.4 (875)	41.9 (1.063)	/ 40.2 (1,020)	
Wheel base		in. (mm)		(1,300)	53.1 (1,350)	
Overall length		in. (mm)		(2,450)	99.6 (2,530)	
Overall width		in. (mm)	48.8 (1,240)		(1,370)	
Overall height		in. (mm)	77.8 (1,975)		(1,985)	
Weight (without fuel)		lbs. (kg)	1,559 (707)	1,590 (721)	1,872 (849)	
Ground clearance		in. (mm)	6.9 (175)		(185)	
Mower mounting		()	0.0 (1.70)	7.0	(100)	
Type				Independent live, Shaft drive		
PTO revolution			•		2,580	
Clutch			Wet multi discs, hydraulic			
Lift system			Hydraulic 2-point hitch			
Tilt angle		Degrees	90			
Tilt assist			Standard			
Weight transfer			Standard			
Others				Ottindara		
ROPS				Standard (ISO21299 and OSHA)		
Fuel gauge			LCD Display (Orange backlight) LCD Display (White backlight)			
Tachometer					LCD Display (White backlight)	
Toolbox			Standard			
Seat			Reclining suspension seat			
Cup holder				Standard		

Mower Specifications

Model		RCK60P-F39	RCK72P-F39	RCK60R-F36	RCK72R-F36
Discharge		Side discharge		Rear discharge	
Cutting width	in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)	72 (1,826)
Cutting height	in. (mm)	1 (25)-5 (129)			
Cutting height adjustment	in. (mm)	Each 0.25 (6.4)			
Depth	in. (mm)	6.0 (152)		5.5 (140)	
Deck pan		Welded			
Thickness	in. (mm)	Top: 0.1644 (4.2), 8Ga Side: 0.1793 (4.5), 7Ga 0.1793 (4.5), 7Ga		4.5), 7Ga	
Number of blades		3			
Front baffle kit		Standard		N.	/A
Mulch kit		Optional			

*SAEJ199

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION
1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com







For Earth, For Life

F2510E/F2510/F3710

The standard in professional front-mount mowers, the F-Series provides outstanding cutting and discharge performance. The top-of-the-line F3710 features the most powerful engine ever in a Kubota front-mount mower.





HIGH-PERFORMANCE

Maximize productivity with powerful diesel performance and high lift capacity—built to handle more work in less time.

High lifting capacity

A high lifting capacity gives the F-Series the versatility to handle an array of implements, including a snow blower, rotary sweeper and debris blower.









Diesel power that keeps you moving

Kubota diesel engines deliver the torque and responsiveness needed for tough mowing conditions—like tall or wet grass—without slowing down. With high torque rise for smooth recovery under load, and low vibration and noise, these engines offer reliable performance that's both powerful and comfortable to operate.

Diff Lock

Auto Assist 4WD features a dual-acting overrunning clutch that automatically engages four-wheel drive when wheel slip is detected. This allows the F-Series to optimize traction on uneven or soft terrain, while minimizing turf damage during tight turns. For consistent performance, full-time four-wheel drive can also be manually engaged. Additionally, a pedal-operated front differential lock enhances straight-line traction by preventing the front wheels from spinning independently.



Large fuel tank capacity

Fewer fuel stops mean more time on the job and less time refueling—especially during long tasks.

Plus, the fuel fill conveniently located just behind the ROPS for easier access.



4WD and Auto-Assist 4WD

Auto-Assist 4WD works in forward and reverse, automatically controlling the drive loads on the wheels during turns. Auto-Assist 4WD lets you turn with greater efficiency and ease with less wear and tear on the turf. Full-time 4WD can also be engaged.



Hydrostatic power steering

Hydrostatic power steering makes it easier to maneuver the unit around trees, landscaping, and other obstacles with precision and ease.

Tilt steering wheel

The tilt steering wheel can be quickly adjusted to several positions for optimum operator comfort and further driving ease.

High/Low range

A convenient Hi/ Low lever comes standard on all models, allowing you to easily adjust

mower speed to match changing terrain or job conditions.

F-Series options

"Other options and accessories available - see your local Kubota dealer for more information.

t	ioi more imormation.				
	F8255	Worklight Kit (ROPS Mounted)			
	F8281	Cruise Control			
	F8282	Turn Assist Brakes (not compatible with cab)			
	F8283	Remote Hydraulic Single Valve			
;	F8284	Remote Hydraulic Double Valve			
	F5206	Deluxe Hard Cab			

PRO-COMMERCIAL MOWER DECK

A durable, hard-working deck that's ready for a wide range of mowing jobs.

Pro-Commercial mower deck

The Pro-Commercial mower deck features an inner baffle that prevents grass from discharging forward, ensuring a cleaner cut.

A larger discharge chute enhances performance by improving airflow, allowing the mower to operate more efficiently with less power.

	Si disch	de arge	Rear discharge	
	60"	72"	60"	72"
F2510E				
F2510	•	•	•	•
F3710	•			•



6.0" deep mower deck

groomed finish.

Its deep 6.0" design lifts grass for a cleaner, more efficient cut—resulting in faster mowing and a well-

Semi pneumatic front caster wheels

Semi-pneumatic caster tires are engineered to

absorb impacts on the job without relying on air - alleviating concerns of downtime and allowing you to mow in with confidence.



PTO shaft drive

Shaft drive means no belts or pulleys – just smooth and direct power transfer from the engine to the deck and other PTO-driven attachments. Shaft drive also requires less maintenance than belt driven system and provides greater reliability.



Multi-V-belt/Steel pulleys

In addition to providing greater wear resistance, the heavy-duty cast-iron pulleys and a multi-V-belt drive system effectively distribute and reduce tension while transmitting power to the mower blades. The multi-V-belt reduces twist or slip, thus reducing the chance of damage to the mower. You get more performance and power – and fewer problems.



Swivel anti-scalp wheels

The mower deck is equipped up front with two large wheels that swivel independently through 360 degrees. The wheels ensure that the deck remains above the turf, preventing unsightly turf damage.



Fabricated deck with sturdy steel construction

Stronger and more durable than conventional pressed steel decks, the F-Series' fabricated steel decks are designed for reliable cutting performance.

Rear discharge mower

When side discharge won't do, mount a rear discharge mower deck. Two sizes—60" and 72"—are available. Both decks tilt up 90 degrees for easier cleaning and blade maintenance. They also feature sturdy steel construction for greater durability and front lift arms that attach directly over the center of gravity for better control.




Mulching kit (option)

The professional mulching kit converts the standard deck into a highprecision mulching deck that produces an even finer mulch and sends it straight back into the turf.

SIMPLE MAINTENANCE

Designed with maintenance in mind.







Dual-element air cleaner

The dual-element air cleaner helps keep the engine running smoothly and efficiently. Only the outer filter requires replacement, while the inner filter can be cleaned with compressed air—reducing maintenance costs. The F3710 model also features an airflow indicator that turns red when the filter needs cleaning or replacement, making upkeep simple and timely.



90-degree tilt mower deck The mower deck tilts a full 90 degrees, providing unobstructed

Integrated radiator screen NEW Digital panel

The easy-to-clean radiator screen is integrated into the engine cover to help maintain optimal engine temperature and performance. A built-in water temperature gauge and overheating alarm provide added protection, helping to prevent engine damage and ensure efficient operation.



The LCD display provides essential information such as fuel level, water temperature, engine RPM, and hour meter readings. Its white backlighting ensures excellent visibility in both bright sunlight and low-light conditions. On the F3710, the display also includes after-treatment data, such as DPF (Diesel Particulate Filter) status and battery level. When operating in poorly ventilated areas, regeneration can be temporarily disabled by pressing and holding the regen inhibit switch for five seconds



Conveniently located under the seat, the tool box provides fast-access storage for your tools. It's also an ideal place to store your operator manual for quick and easy reference while on the job.

DRIVING COMFORT

The all-important key to efficient, productive mower operation.

IMPLEMENTS

Heavy-duty options for specialized applications.





All-season cal

The cab has been redesigned for easy attachment and removal for all-season use.

Cab options

- Rear Worklight
- Rear View Mirror
- Heater
- Beacon Light





custom fit and optimum comfort.

Deluxe seat Operator levers

The F-Series' high level of comfort starts with a deluxe high-back seat with four separate adjustments—weight control, lumbar support, back angle, and arm rests—to provide the operator identification.

For ease of operation and operator convenience, the High/Low speed lever and deck-lifting lever are positioned beside the operator's seat quick, at-a-glance identification.



Cab shown with optional rear LED work lights that improve rear visibility. And an optional flashing LED beacon is also available.



Grass catcher

* Previous grass catcher installed on the previous model F3990.





Rotary sweeper



Front blade



Snow blower



Debris blower