



You know that feeling of accomplishment after a long day of working the land?

Whether it's turning soil, pushing dirt, making hay or mowing grass, that feeling lingers on when you're confident that you have the right equipment for the job, doing its part right along with you, day after day.

It's that confidence that leads to a whole new level of productivity, ultimately helping you achieve your vision.

At Kubota, we have a near 50-year history of providing precisely engineered machines with confidence-backed quality to ensure our customers can do more every day.

We know doing your homework is part of the job because it leads to making informed choices about your equipment and its ability to perform when you need to get the job done.



### 2021 FULL LINE TURF BROCHURE

### **MOWERS**

- 2 T Series
- 4 GR Series
- 6 New Z200 Series
- 8 Z400 Series
- 10 Z700 Series
- 12 SZ Series
- 14 W Series
- 16 ZG200 Series
- 18 ZG300 Series
- 20 ZD1000 Series
- 22 ZD1200 Series
- 24 ZD1500 Series
- 26 F Series

### **KUBOTA SERVICES**

28 Kubota Services







**T Series** 

T2090BR | T2290KW | T2290KWT

### Easy to operate, fun to drive, the ALL improved Kubota T Series is durable, and packed with premium features to keep you mowing efficiently and comfortably.

- Equipped with high power 20- and 21.5-horsepower gasoline engines
- All models are equipped with hydrostatic transmissions (HST) for precise control
- High-back seat (with suspension on T2290) provides extra cushioning and support, with dual armrests (optional on T2090) for comfort
- The thicker and higher-positioned steering wheel reduces fatigue and enhances operator comfort and control
- Convenient 12V power outlet lets you charge your phone or power accessories like an air compressor

- Short 14" turning radius allows easy maneuvering around difficult objects
- Mower height adjusts from 1" to 4" right from the operator's seat with simple dial-cam setting
- Upgraded fabricated mower deck, along with new tubularframe structure, improves strength, rigidity, and durability
- Ductile cast iron front axle is strong and durable, handling all sorts of bumps & shocks
- Compatible with a full line of performance-matched, quick-attach front implements

### T Series

i Series				
	T2090BR	T2290KW	T2290KWT	
Engine Type	OHV,	-twin		
Engine Model	Briggs & Stratton Professional 40S8			
Horsepower (gross)	20*	21.	5**	
Transmission		Hydrostatic		
Fuel Capacity (gal.)		3.6		
Speed (mph) (forward)	0-{	5.7	0-6.7	
Length	74.8"	75	.2"	
Deck Size	42	2"	48"	
Width (w/ mower)	54.8"	54.8" 60.6		
Weight (lbs.)	595	622	661	
ADDITIONAL IMPLEMENTS AND ACCESSORIE	S			
Armrest Kit	ZG1341	Stan	dard	
Grass Catcher (blower not necessary)	GCK4	2-90T	GCK48-90T	
Mulching Kit	T28	332	T2838	
Front Push Blade (48")		T2833		
Two-Stage Snowblower (46")		T2834		
MID-MOUNT MOWER SPECIFICATIONS				
	RCK42	P-90T	RCK48P-90T	
Number of Blades		2	3	
<b>Cutting Width</b>	42	48"		
Cutting Height	1–4"			
Height Adj. Increments	1/4"			

<sup>\*</sup> SAE J1940; \*\* SAE J1995



Lift System



Manual w/gas assist



**GR Series** 

GR2021G | GR2120

# With Kubota's revolutionary Glide Steer, all-wheel drive, plus tight turning, even difficult mowing conditions are now effortless.

- Your choice of a 3-cylinder, 17-horsepower Kubota diesel engine or a 2-cylinder, 20-horsepower Kohler gasoline engine
- Glide Steer provides excellent turning maneuverability with front wheels that turn up to 70 degrees while preventing turf damage
- All-Wheel Drive (AWD) characteristics provide outstanding traction needed for mowing on rolling terrain
- Versatile HST transmission is controlled by a single foot pedal for a smooth and comfortable ride
- Shaft-driven mower, transmission, and PTO offer smooth, virtually trouble-free operations

- Cruise control, full-flat operator platform and a comfortable high-back, adjustable suspension seat increase operator comfort
- > 5" deep, 48" and 54" contoured design mower decks produce professional results every time
- Equipped with Kubota's Reverse Awareness System (KRA) for additional safety when mowing in reverse
- Variety of implements available for year-round versatility, including a grass catcher, two-stage snowblower, front blade, and mulching kit

### **GR Series**

	GR2020G3 / GR2020GB3	GR2120-2 / GR2120B-2	
Engine Type	Air-cooled, gasoline, 2-cylinder	Liquid-cooled, diesel, 3-cylinder	
Engine Model	Kohler	Kubota	
Horsepower (gross)	20.5*	17**	
Transmission	Hydrostatic		
Steering System	Glide Steer, hydrostatic power steering		
Deck Size	48" 48" / 54"		
Overall Length	77.2"		
Overall Width (w/mower)	61" (w/48") 66.9" (w/54")		
Weight (lbs.) (w/mower)	871 (w/48")	970 (w/54")	

ADDITIONAL IMPLEMENTS AND ACCESSORIES	
Front Blade	48"
Grass Catcher	3-bag, 10-bushel capacity
Mulching Kit	Optional
Snowblower	2-stage 46"
Rear Weight Bracket	Optional
Suitcase Weights	Optional

### MOWER SPECIFICATIONS

	RCK48-GR	RCK54-GR
Number of Blades	(	3
Cutting Width	48"	54"
Cutting Height	1-	4"
Height Adj. Increments	1/4"	
Lift System	Hydr	aulic

<sup>\*</sup> SAE J1940; \*\* SAE J1995





**New Z200 Series** 

Z231KW | Z231BR | Z231KH | Z251BR | Z251KH

## The ultimate residential zero-turn mower — combining style, comfort, and performance.

- Zero-turn steering for superior machine control and precision mowing
- A 10-gauge steel, welded mower deck provides professional-level cutting performance for homeowners
- > Storage boxes on either side give you a place for tools, lunch, and anything else
- > Cup holders keep your drinks at hand
- LED headlights allow you to continue mowing in lowlight conditions and come standard on the KH models and is an option on the KW and BR models

- Wide-tread tires give you better traction and weight distribution to help protect your lawn
- The K-Lift (mechanical one-push deck-lift pedal) makes adjusting the cutting height simple
- > Z231KW comes with a 42-inch deck to maneuver in and out of intricate spaces smoothly and with ease
- > KH-models are equipped with full seat suspension
- The Z200 series is covered by a comprehensive four-year, 300-hour factory warranty

New Z200 Series	s				
	Z231KW-42	Z231BR-48	Z231BR-54	Z251KH-48	<b>Z251KH-5</b> 4
Engine Type		Air-coole	d, gasoline, V-Twir	1	
Engine Model	Kawasaki FR	Briggs & Stratton Professional Series  Kohler Courage Pro			urage Pro
Horsepower (gross)	21.5*	22**	25**	21**	25**
Displacement (cu. cm.)	726	72	4	74	17
Transmission	Hydro-Gear™ Commercial ZT2200 Integrated Zero-Turn Transaxle	Ćommercial Hydro-Gear™ ZT2200 Integrated Commercial ZT3100 Integrated Zero-Turn Zero-Turn Transaxle			
Fuel Tank Capacity (gal.)	3.6		4	.3	
Speed (mph) (forward/reverse)	0-6.5 / 0-4		0–8	/ 0–4	
Overall Length	74.4"				
Overall Width (w/ mower chute down)	55.1"	61.1"	67.3"	61.1"	67.3"
Overall Height	65.3"				
Wheel Base	48.5"		45	.5"	
Weight (lbs.)	621	737	7	749	771
MOWER SPECIFICATIONS					
Mower Deck Type		Pro perform	nance fabricated d	eck	
Mower Lift System		ſ	Mechanical		
Mower Height, Increment	1.5–4.25", 1/4"		1.5–4.	5", 1/4"	
Mower Deck Width	42"	48"	54"	48"	54"
IMPLEMENTS AND ACCESSORIES					
Grass Catcher			Optional		
Mulching Kit			Optional		
Seat Suspension Kit	N/A	Optio	onal	Stan	dard
LED Working Light Kit		Optional		Stan	dard
Canopy Sunshade & Deck Lift Assist Kit	N/A	N/A Optional			
Arm Rest Kit	Optional	ional N/A			
Hitch Kit	Optional	N/A			

<sup>\*</sup>These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

<sup>\*\*</sup> Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.



**Z400 Series** 

**NEW Z412KW | Z422KW | Z422KW**Z411KW | Z421KW | Z421KWT

# Designed for the prosumer who seeks professional performance and durability, as well as comfort and convenience.

### **NEW Z412 and Z422 Features**

- Premium adjustable suspension seat offers thick cushion with high back and a 4" adjustable seat slide that improves comfort and reduces fatigue
- > All deck sizes have 13"x6.5"-6" Front pneumatic tires
- > Powered by the highly acclaimed Kawasaki FS-Series Engines, the Z400 provides the torque you need to power through tall grass and rugged environments
- The Z400 is driven by the new Hydro-Gear ZT-3600 transmission, a Kubota exclusive, the most dependable and durable in the product class
- Maximum forward travel speed of 10 mph contributes to quickly completing the job at hand
- With a generous fuel tank capacity of 6.8 U.S. gallons (25.7 L), the Z400 is able to continue operations for up to six hours

- Light and smooth steering lever operation with dampers that have three adjustment positions
- Simple operation of the mower lift pedal efficiently raises the mower deck
- The operation panel is conveniently and integrally located on the right fender and features a simple, easy-to-operate design
- Convenient 12V power outlet lets you charge your phone or power accessories like an air compressor
- The seat features a thick cushion construction and slides a full 6" forward and back, allowing even prolonged operations to be undertaken in maximum comfort (Z411 & Z421)

Z400 Series			
	Z412KW-48 Z411KW-48	Z422KW-54 Z421KW-54	Z422KWT-60 Z421KWT-60
Engine Type		Air-cooled, gasoline, 2-cylinder	
Engine Model	Kawasaki FS 651V	Kawasaki	FS 730V
Horsepower (gross)*	22	2	4
Displacement (cu. cm.)		726	
Transmission		Hydro-Gear ZT-3600	
Front Tire	13" x	<b>13" x 6.5"-6" (Z412 &amp; Z422)</b> 5" x 6"	13" x 6.5" - 6"
Rear Tire	24" x 9	.5"-14"	24" x12"-14"
Fuel Capacity (gal.)		6.8	
Speed (mph) (forward/reverse)		0-10 / 0-5	
Overall Length	48	.7"	54.2"
Overall Width (w/mower chute)	61.1"	67.3"	73.6"
Overall Height (w/ROPS upright)		69.8"	
Weight (lbs.) (w/mower)	856	870	904
MOWER SPECIFICATIONS			
	RCK48P-400Z	RCK54P-400Z	RCK60P-400Z
Mower Deck Type		Kubota Side Discharge	
Mower Lift System		Mechanical / Foot pedal	
Deck Depth		5"	
Cutting Height		1.5–5"	
Cutting Width	48"	54"	60"
Blade Tip Speed (fpm) (max.)	18,880	18,700	18,300
ADDITIONAL IMPLEMENTS AND ACCESSORIES			
		<b>Z400 Series</b>	
Grass Catcher Kit		Optional	
Mulching Kit		Optional	
Chute Block Kit		Optional	
Suspension Seat Kit		Optional	
LED Work Light Kit	Optional		
Operator Controlled Discharge Chute	Optional		
Canopy Sunshade	Optional		
Maintenance Life I/I		0-4	

### \* SAE J1995

**Maintenance Lift Kit** 

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

Optional

Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.



**Z700 Series** 

Z751KWi | Z781KWi | Z781KWTi Z724XKW | Z726XKW Z723KH | Z724KH | Z725KH

Designed for the commercial landscape professional, the Z700 Series offers best in class performance, productivity, comfort and the durability that Kubota is known for.

### **Z700EFI Model Features**

- Xawaski FX EFI engines feature a fully integrated electronic governor (E-GOV) and a cutting edge ECU control unit. They deliver outstanding performance without power loss
- EFI Dial Throttle control, delivers infinite effortless engine control
- LCD Engine Meter, provides all the information you need to keep your Z700 EFI unit running at optimum efficiency
- > 24" Low Profile tires improve hill side stability
- > 12V Power outlet can charge or power many devices

### **All Model Features**

- Premium adjustable suspension seat offers a thick cushion with a 19.6" high back and a 6" adjustable seat slide that allows you to find the ideal seating position for maximum comfort
- New Deck Step indicator provides easier access
- New Water and Dust Proof safety switches elminate those failures
- 6"-deep mower deck and anti-scalp rollers provide fast, clean, superior grass-cutting performance
- With an 11.2 mph maximum speed, it's Kubota's fastest zero-turn mower
- Dual Parker® transmission with an integrated pump and motor designed for increased efficiency and simplified maintenance

### **Z700 Series**

2700 Series							
	Z751KWi-48	Z781KWi-54 Z781KWTi-60	Z724XKW-3-48 Z724XKW-3-54	Z726XKW-3-60	Z723KH-3-48	Z724KH-3-54	Z725KH-3-60
Engine Type			Air-co	oled, gasoline,	V-Twin		
Engine Model	Kawaski FX 730V EFI	Kawaski FX 850V EFI	Kawasaki FX FX 730V	Kawasaki FX FX 801V	KOHLER Command Pro® CV682	KOHLER Command Pro® CV732	KOHLER Command Pro® CV742
Horsepower (gross)	25.5*	29.5*	23.5*	25.5*	22.5**	23.5**	25**
Displacement (cu. cm.)	726	852	726	852	694	694	747
Transmission				Parker HTG14			
Fuel Capacity (gal.)				11.6			
Speed (mph) (forward/reverse)			(	0-11.2 / 0-5.6	3		
Overall Length				83.9"			
Overall Width (w/ mower)	61.3"	67.3"/ 73.8"	61.3"/ 67.3"	73.8"	61.3"	67.3"	73.8"
Overall Height (w/ROPS upright)	70.1"						
Wheel Base			ı	50.9"	I	ı	
Weight (lbs.) (w/ mower)	1,215	1,254/1,285	1,207/1,223	1,276	1,212	1,226	1,257
MOWER DECK SPECIFICATIONS							
Mower Deck Type			Comm	ercial fabricate	d deck		
Mower Deck Width, Lift System	48" Mechanical	54"/60" Mechanical	48" / 54" Mechanical	60" Mechanical	48" Mechanical	54" Mechanical	60" Mechanical
Cutting Height				1–5"			
Height Adj. Increments				1/4"			
Mower Deck Depth				6"			
IMPLEMENTS AND ACCESSORIES							
Premium Suspension Seat				Standard			
Grass Catcher	Optional - 10 bushels (48"/54"), 11 bushels (60")						
Mulching Kit				Optional			
Operator-Controlled Discharge Chute	Optional						
Towing Hitch	Optional						
LED Working Light Kit	Optional						
	T. Control of the Con						

### \* SAEJ1995

**Maintenance Lift Kit** 

Canopy Sunshade
Karu Mulching Blade

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

Optional Optional

Optional, 60" only

Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

<sup>\*\*</sup> SAE J1940



**SZ Series** 

**NEW SZ19-36-2 | SZ22-48-2 | SZ26-52-2 | SZ26-61-2** SZ19-36 | SZ22-48 | SZ26-52 | SZ26-61

The Kubota SZ series commercial stand-on is the answer to get more done, faster and more efficiently, in even the tightest spaces while delivering superior comfort and durability.

### **All Models**

- Commercial-grade Kawasaki FX & FT EFI gas engines equipped with Hydro-Gear integrated transmissions
- Adjustable front baffle on cutting decks (On -2 models: 48",52"and 61")
- > Smooth 3-position adjustable dampened controls

- > Tool-less adjustable front reference bar
- > Large operator platform (48-, 52- and 61-inch models)
- Tool-less tracking adjustment
- > Ergonomic cushion pad
- > No-flat front castors

### **SZ Series**

	SZ19-36-2 SZ19-36	SZ22-48-2 SZ22-48	SZ26-52-2 SZ26-52	SZ26-6-2 SZ26-61
Engine Type	Kawasaki FX600V	Kawasaki FX691V Kawasaki FT730V-EFI		
Horsepower (gross)*	19 HP	22 HP	26	HP
Transmission	Hydro-Gear ZT3100		Hydro-Gear ZT3600	
Speed	9 MPH		11 MPH	
Fuel Capacity (gal.)	5.1		6.5	
Deck Type			d Floating	
Deck (ga)	7 ga top and side skirts w/3 ga reinforcement			
<b>Deck Spindle &amp; Bearings</b>		1" Shaft w/ Maintenance-Free Seal Bearings		
Deck Size	36"	48"	52"	61"
<b>Cutting Height</b>		Adjustable 1.5" - 4.5"		
Front Tires (Flat-Free)	<b>11" x 6"-5" (-2 models)</b> 11" x 4.0"-5"	1	13" x 6.5"-6" (-2 models	)
Rear Tire	20" x 8"-10"	23" x 8.5"-12"	23" x 10	).5"-12"
Weight (lbs.)	831	965	997	1015
Length	62.5"		63.75"	
Height	45"		45.75"	
ATTACHMENTS				
Mulch Kit	SMK36	SMK48 / SMK48-2	SMK52 / SMK54-2	SMK61 / SMK61-2
Discharge Plate	SBP36	SBP48 / SBP48-2	SBP52 / SBP54-2	SBP61 / SBP61-2
Weight Kit	SWK36		SWK48	
Striping Kit	N/A	SSK48	SSK5	2-61

<sup>\*</sup> SAEJ1995







**W Series** 

WG6 | WGC6 | WG14 | WH15 | WHF19

## Kubota's durable Commercial Walk-Behind Mowers offer options for all commercial mowing, small and large.

### WG6/WGC6

- > Die-cast aluminum deck
- > 2.5 bushel bag capacity
- > Zone Start and Blade Brake Clutch models
- > Die-cast aluminum wheels with dual ball bearings
- > Replaceable steel deck edge guards

### WG14/WH15/WHF19

- > Electric clutch
- > Operator-adjustable control forces
- > B-Section Aramid Fiber deck belts
- > Electric-start options available
- > Precision-ground double-sealed bearings standard on all models

### **Walk-Behind Mowers**

	WG6/WGC6 21" Deck	WG14 – 36" Deck	WH15 – 48" Deck	WHF19 – 52" Deck
Engine Type	Kawasaki FJ180	Kawasaki FS481V	Kawasaki FS541V	Kawasaki FX600V
Horsepower (gross)*	5.5	14.5	15	19
Fuel Capacity (gal.)	0.5		5	
Speed (mph)	4.1	5.1	6	6.7
Transmission	3-speed Gear Drive	5-speed Peerless gear box	2-Hydro-Gear 10cc V Pumps with oil cooler a	ariable Displacement of Parker Wheel Motors
Mower Deck Type	High Vacuum, Rear Discharge	Fabricated fixed	Fabricated fixed with wear band	Fabricated float with wear band
Deck (ga)	Heavy-duty cast aluminum	7 ga deck wi	th 7 ga skirts	10 ga deck with 10 ga top, 7 ga skirts
Blade Tip Speed (fpm)	N/A	18,784	15,315	18,600
<b>Cutting Height</b>	.75–4"	1.5–4.5"	1.375–4.625"	1.5–5"
Starter	Manual	Manual	Elec	etric
Hand Controls	Zone Start / Blade Brake Clutch	Pistol Grip Dual-Lever Hydro Control		lydro Control
Deck Spindle	N/A	M	aintenance-free with 1" sha	aft
Spindle Bearings	N/A	Precision	on-ground double-sealed be	earings
Deck Drive	Direct Drive / Blade Brake Clutch	Warner Mag Stop 125 ft-lb. electric clutch		Warner Mag Stop 175 ft-lb. electric clutch
Front Tires	9 x 2.25	9 x 3.50-4 No-Flat		11 x 4.00-5 No-Flat
Rear Tires	9 x 2.25	13 x 5-6 4-ply	16 x 7.50-8 4-ply	18 x 7.50-8 4-ply
Brakes	N/A	Drum Type	Hydrostatic Dy	namic Braking
Weight (lbs.)	125 / 130	464	660	785
Length	64"	78	3"	80.7"
Height	38–43"	40.3"	43	3"

<sup>\*</sup> SAE J1995







**ZG200 Series** 

ZG222 | ZG227

The professional-quality performance, exceptional comfort, and outstanding reliability of the ZG200 Series make it the ultimate mowing machine for both professionals and homeowners.

- Powered by durable 21.1- and 26-horsepower air-cooled Kubota gasoline engines
- > Zero-turn steering for superior navigation
- Reliable, ultra-smooth, hydrostatic transmission offers superior durability and performance
- Heavy-duty Pro Commercial Mower Deck features a unique baffling system that improves airflow to discharge grass clippings and an anti-overflow system for professional-looking results
- Optional mulching system provides a beautiful finish, even in thick grass

- Foot-operated hydraulic deck-lift system for easy adjustment
- Spacious platform, comfortable and supportive seating, and an easy-to-reach cup holder for operator comfort
- Operator-friendly instrument panel puts everything within close reach
- Convenient mower, HST, and engine access for hasslefree maintenance
- > Foldable ROPS standard

### **ZG200 Series**

	ZG222-48	ZG227-54/60	
Engine Type	Kubota air-cooled, gasoline, 2-cylinder		
Engine Model	Kubota KGZ770-M3	Kubota KGZ770-M2	
Horsepower (gross)*	21.1 26		
Displacement (cu. cm.)	768		
Transmission	2-HST w/ gear reduction		
Fuel Capacity (gal.)	7.1		
Speed (mph) (forward/reverse)	0–9 / 0–5		
Overall Length	82.5"	82.5" / 83.7"	
Overall Width (w/mower chute)	61"	67.3" / 75.2"	
Overall Height (w/ROPS upright)	69.9"		
Overall Height (w/ROPS folded)	52.8"		

### MOWER SPECIFICATIONS

	ZG222-48	ZG227-54/60
Mower Deck Type	Welded, side discharge	Welded, side discharge
Mower Deck Width / Lift System	48" / Hydraulic	54 or 60" / Hydraulic
Cutting Height	1–	-5"
Height Adj. Increments	1/	′4"
Mower Deck Depth	6" (48)	6"

1,102 / 1,168

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

Weight (lbs.) (w/mower)

### **ZG200 Series**

Canopy Sunshade	Optional
Grass Catcher	Optional
Mulching Kit	Optional
Working Light Kit	Optional

\* SAE J 1940



1,190 / 1,235



**ZG300 Series** 

ZG327P ZG327RP

### Built for power, durability, and performance, the ZG300 Series features deep mower decks for exceptional cutting performance.

- ZG300 mowers are available with durable Kubota deck air-cooled gasoline engines with 26 gross horsepower
- Durable HST transmission optimizes performance to achieve maximum results
- > Pro commercial deck is a superior deep mower deck that ensures excellent cutting performance
- Anti-scalp swivel rollers can rotate a full 360 degrees preventing unsightly turf damage
- > Large-capacity dual fuel tanks on ZG300 Series models
- Foot-controlled hydraulic deck lift and PTO wet disc clutch make tough jobs easy

- Unique maintenance lift system allows easy mower access (optional on ZG300 models)
- Radiator screen is integrated into hood for better sealing performance and reduced likelihood of grass clippings finding their way into the radiator (diesel models)
- Tie-down for securing onto flatbed truck or trailer for convenient transportation
- Flat-free" front caster tires are standard with ZG300 and enable mowing operation without worrisome flat-tire downtime

### ZG300 Series

### ZG327P-60 ZG327RP-60R

Engine Type	Kubota air-cooled, gasoline, 2-cylinder
Engine Model	Kubota KGZ770
Horsepower (gross)*	26
Displacement (cu. cm.)	768
Transmission	2-HST w/ gear reduction
Fuel Capacity (gal.)	12.7
Speeds (mph) (forward/reverse)	0–10.6 / 0–5.3
Overall Length	87.8"
Overall Width (w/ mower)	75.2"
Overall Height	75.4"
Weight (lbs.)	1,565

MOWER SPECIFICATIONS	
Mower Deck Type	Welded, side, or rear discharge
Mower Deck Width / Lift System	60" / Hydraulic
Mower Height / Increment	1–5" / 1/4"
Mower Deck Depth	6.5"

Optional

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

# ZG300 Series Canopy Sunshade Optional Front Utility Blade Optional Grass Catcher\*\* Optional

Mulching Kit	Optional
Spark Arrester	Optional
Striping Kit	Optional
Working Light Kit	Optional

**Karu Mulching Blade** 



<sup>\*</sup> SAE J 1940



**ZD1000 Series** 

ZD1011 | ZD1021

Top to bottom, front to back, and inside and out, Kubota's ZD Series of zero-turn mowers is engineered for quality. Versatile and reliable, the ZD1000 compact mower can handle jobs big and small.

- ➤ The Kubota ProDeck with ACS (Aerodynamic Cutting System<sup>TM</sup>) has smoother airflow and more powerful rotation to ensure more efficient cutting, meaning you can get the job done better and faster
- Redesigned clean-cut blades have a new shape that improves overall load balance and provides a longer service life
- Discharge chute has been redesigned with a flexible yet strong material, ensuring a smoother and more uniform discharge of clippings
- > Improved fuel efficiency up to 22% better
- Low center of gravity helps improve the weight/balance and provides stability on slopes and uneven ground
- A two-pedal hydraulic deck-lift system keeps you mowing in spite of obstacles by letting you easily raise and lower the deck with your foot

### **ZD1000 Series**

	ZD1011-48 / ZD1011-54		ZD1021-60		
Engine Type	Kubota liquid-	ylinder			
Engine Model	Kubota D782-E4-ZD-3	oota D902-E4-ZD-2			
Horsepower (gross)*	19.3	21.6			
Displacement (cu. cm.)	778		898		
Transmission	2-HST	w/gear reduction			
Fuel Capacity (gal.)		6.0			
Speed (mph) (forward/reverse)		0-9 / 0-5			
Overall Length	87.8"		88.8"		
Overall Width (w/mower chute)	61.6" / 67.3"	73.8"			
Overall Height (w/ROPS upright)		74.4"			
Front Tires	13 x 5.0-6 smooth pneumatic	5-6 smooth pneumatic			
Rear Tires	24 x 9.5-14 low-profile tire	2.0-14 low-profile tire			
Brakes	Wet multi-disks, foot applied, released				
Weight (lbs.) (w/mower)	1,296 / 1,323	1,389			
MOWER DECK SPECIFICATIONS					
	RCK48P-1000Z RC	K54P-1000Z	RCK60P-1000Z		
Mower Deck Type	Kubota	ProDeck with ACS			
Mower Lift System		Hydraulic			
Deck Depth		6"			
Cutting Height		1–5"			
Cutting Width	48"	54"	60"		
Blade Tip Speed (fpm) (max.)	17100		18200		
ADDITIONAL IMPLEMENTS AND ACCESSORIES					
	ZD1011-48 / ZD1011-54		ZD1021-60		
"Catch All" 2-Bag Style Grass Catcher		Optional			
Hitch Kit		Optional			
Operator-Controlled Discharge Chute		Optional			
Work Light Kit		Optional			
Canopy Sunshade		Optional			

<sup>\*</sup> SAE J1995



**ZD1200 Series** 

ZD1211 | ZD1211R | ZD1211L | ZD1211RL

With a bigger engine and wider mower deck, the ZD1200 gets the job done with speed and efficiency. These premium mowers incorporate the best of Kubota's advanced technology in every detail and ensure both superior mowing performance and supreme operator comfort.

- The biggest LCD meter in its class shows all of the key indicators you need to maximize cutting performance and operability
- For faster operation and better ergonomics, the mower deck controls are on the right side within easy reach of your hand, letting you quickly and easily adjust the cutting height
- Low-profile tires at the rear improve the stability and traction on turns
- Redesigned HST levers not only provide more legroom but more settings to choose from, ensuring smoother operation, better zero-turn maneuverability, and greater job efficiency
- A more comfortable, fully padded and reclining bucket seat means less operator fatigue and greater productivity

   with dual adjustable armrests, higher backrest, and lumbar support
- The optional "Catch All" hopper-style grass catcher holds 11.4 bushels of clippings and can be emptied while the operator remains seated

### **ZD1200 Series**

	ZD1211-60 /	ZD1211R-60R	ZD1211L-72 / ZD1211RL-72R			
Engine Type		ed, diesel, 3-cylinder				
Engine Model		Kubota D1105-E4-ZD-2				
Horsepower (gross)*		2	4.8			
Displacement (cu. cm.)		1,	123			
Transmission		2-HST w/g	ear reduction			
Fuel Capacity (gal.)		1	3.0			
Speed (mph) (forward/reverse)		0–10.6	6 / 0-5.3			
Overall Length	8	9"	93	.7"		
Overall Width (w/ mower chute)	73.8	" / 63"	85.8"	/ 75.2"		
Overall Height (w/ROPS upright)		78	3.7"			
Front Tires		15 x 6.5-8 smoo	th semi-pneumatic			
Rear Tires		26 x 12.0-16	low-profile tire			
Brakes	Wet multi-disks, foot applied, released					
Weight (lbs.) (w/mower)	1,687	/ 1,720	1,764	/ 1,786		
MOWER DECK SPECIFICATIONS						
	RCK60P-1200Z	RCK60RP-1200Z	RCK72P-1200Z	RCK72RP-1200Z		
Mower Deck Type	Kubota ProDeck with ProDeck ACS		Kubota ProDeck with ACS	Kubota ProDeck		
Mower Lift System		Hyd	raulic			
Deck Depth	6.0"	5.5"	6.0"	5.5"		
Cutting Height		1-	-5"			
Cutting Width	6	60"	72"			
Blade Tip Speed (fpm) (max.)	18,050	16,900	18,050	18,000		
ADDITIONAL IMPLEMENTS AND ACCESSORIES						
	ZD1211-60 /	ZD1211-60R	ZD1211L-72 /	ZD1211RL-72R		
"Catch All" Hopper-Style Grass Catcher		Opt	tional			
"Catch All" 2-Bag Style Grass Catcher		Opt	tional			
Karu Mulching Blade		Optional,	60" & 72"			
Hitch Kit		Opt	tional			
Operator-Controlled Discharge Chute		Opt	tional			
Work Light Kit	Optional					
Canopy Sunshade	Optional					

<sup>\*</sup> SAE J1995



**ZD1500 Series** 

ZD1511RL | ZD1511LF | ZD1511RFL

The ZD1511 stakes its place at the top of the line of Kubota's industry-leading diesel zero-turn mowers with the electronically controlled Kubota diesel engine and the Aerodynamic Cutting System to significantly enhance cutting performance.

- The flexible discharge chute ensures superior scattering of clippings
- Wider, thicker, and more durable blades contribute to optimized air flow
- Compared to previous model ZD331, the ZD1511 features an enlarged flywheel that is responsible for an increase from 29.1 hp (21.7 kW) to 30.8 hp (23 kW)
- The hydraulic transmission, a unique Kubota feature, ideally complements the V1505 Kubota diesel engine by transmitting engine power without loss, which contributes to a quick and smooth response

- The 3.5" (88.9 mm) wide LCD Panel is the trade's largest and most comprehensive for models in this class
- > Two-pedal type hydraulic lift system enables the operator to easily and efficiently raise the mower deck when an obstacle is encountered
- Operators never need to remove hands from levers to engage the parking brake through use of the conveniently located parking brake pedal
- > Two-pin type maintenance lift makes it simple and easy to efficiently lift the front portion of the mower deck to quickly deal with any situation as it is encountered including needed maintenance

### **ZD1500 Series**

	ZD1511RL-60	R ZD1511L	F-72 / ZD1511RLF-72R			
Engine Type	Kubota liquid-cooled, diesel, 4-cylinder					
Engine Model	Kubota V1505-T-E4-ZD					
Horsepower (gross)*	30.8					
Displacement (cu. cm.)		1,498				
Transmission		2-HST w/gear reduction				
Fuel Capacity (gal.)		13.0				
Speed (mph) (forward/reverse)		0-10.6 / 0-5.3				
Overall Length		104.7"				
Overall Width (w/mower chute)	63"		85.8" / 75.2"			
Overall Height (w/ROPS upright)		78.7"				
Front Tires	1	5 x 6.5-8 smooth semi-pneumat	ic			
Rear Tires		26 x 12.0-16 low-profile tire				
Brakes	We	et multi-disks, foot applied, releas	sed			
Weight (lbs.) (w/mower)	1,984	2,006 / 2,028				
MOWER DECK SPECIFICATIONS						
	RCK60RP-1500Z	RCK72P-1500Z	RCK72RP-1500Z			
Mower Deck Type	Kubota ProDeck	Kubota ProDeck with ACS	Kubota ProDeck			
Mower Deck Type  Mower Lift System	Kubota ProDeck		Kubota ProDeck			
	Kubota ProDeck 5.5"	ACS	Kubota ProDeck 5.5"			
Mower Lift System		ACS Hydraulic				
Mower Lift System  Deck Depth		ACS Hydraulic 6.0"	5.5"			
Mower Lift System  Deck Depth  Cutting Height	5.5"	ACS Hydraulic 6.0" 1–5"	5.5"			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width	5.5" 60"	ACS Hydraulic 6.0" 1–5"	5.5"			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)	5.5" 60"	ACS Hydraulic 6.0" 1–5"	5.5"			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)	5.5" 60" 17,300	ACS Hydraulic 6.0" 1–5" 72	5.5" 2" 400			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)  ADDITIONAL IMPLEMENTS AND ACCESSORIES	5.5" 60" 17,300	ACS Hydraulic 6.0" 1–5" 72 18,4	5.5" 2" 400			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)  ADDITIONAL IMPLEMENTS AND ACCESSORIES  Mulch Kits	5.5" 60" 17,300	ACS Hydraulic 6.0" 1–5" 72 18,4  RCK72P-1500Z Optional	5.5" 2" 400			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)  ADDITIONAL IMPLEMENTS AND ACCESSORIES  Mulch Kits  Work Light Kit	5.5" 60" 17,300	ACS Hydraulic 6.0" 1–5" 72 18,  RCK72P-1500Z Optional Optional	5.5" 2" 400			
Mower Lift System  Deck Depth  Cutting Height  Cutting Width  Blade Tip Speed (fpm) (max.)  ADDITIONAL IMPLEMENTS AND ACCESSORIES  Mulch Kits  Work Light Kit  Canopy Sunshade  Operator Controlled	5.5" 60" 17,300 <b>RCK60RP-1500Z</b>	ACS Hydraulic 6.0" 1–5" 72 18,4  RCK72P-1500Z Optional Optional Optional	5.5" 2" 400 <b>RCK72RP-1500Z</b>			

<sup>\*</sup> SAE J1995



**F Series** 

F2690E | F2690 | F3990

### The F Series sets a new standard for professional frontmount mowers with cleaner emissions and greater power, precision, and efficiency.

- Kubota diesel engines provide faster, more efficient job performance with high-torque rise that allows you to power through tall or wet grass
- The F3990 offers the highest-ever horsepower among all Kubota front-mount mowers
- > 6" deep, side-discharge deck design lets tall grass stand up so it can be cut more efficiently with a cleaner appearance
- Large operator's platform, deluxe high-back seat with four separate adjustments and operator levers, for maximum driving comfort and convenience
- Hydrostatic power steering reduces operator fatigue and makes it easier to mow around trees and other obstacles
- > EPA compliance with Tier 4 emissions regulations, enhanced combustion efficiency, low vibration and noise levels, and reduced fuel costs

#### **F Series** F3990 F2690E F2690 Kubota liquid-cooled, **Engine Type** Kubota liquid-cooled, diesel, 3-cylinder diesel, 4-cylinder **Engine Model** Kubota D1105 Kubota V1505T-IDI+DPF Horsepower (gross)\* 24.8 36.9 Displacement (cu. cm.) 1,123 1,498 **Transmission** Hydrostatic, 2-range Fuel Capacity (gal.) 16.1 0-12 / 0-6.20-12.5 / 0-6.8Speed (mph) (forward/reverse) 96.5" 98.9" **Overall Length** 53.9" **Overall Width** 48.8" **Overall Height** 77.8" 78.1" Min. Ground Clearance 6.9" 7.3" Weight (lbs.) 1,594 1,606 1,716 **MOWER SPECIFICATIONS** RCK60P-F39 **RCK72P-F39** RCK60R-F36 RCK72R-F36 **Mower Deck Type** Welded, side discharge Welded, rear discharge **Cutting Width** 60" 60" **Cutting Height** 1-5" 6" **Mower Deck Depth** 5.5" ADDITIONAL IMPLEMENTS AND ACCESSORIES **F2690E** F2690 F3990 **Hard Cab Enclosure** Optional **Cab Heater** Optional **Grass Catcher** Optional 12-Bushel, Low-Dump Style **Debris Blower** Optional **60" Front Blade** Optional 60" Rotary Sweeper Optional

**Snow Blower** 

**Mulching Kit** 

Optional

Optional

<sup>\*</sup> SAE J1995

### **KUBOTA PARTS**

Kubota Tractor Corporation (KTC) Parts operations provide customer parts support, parts, and manuals through Kubota's national dealer network. We support our dealers with four large warehouses located strategically throughout the United States and two super warehouses in Japan.

KTC Parts offers a full line of O.E.M. service and maintenance parts designed and engineered to original factory specifications to keep your Kubota equipment operating at peak performance.



### **KUBOTA ORANGE PROTECTION PROGRAM®**

The Kubota Orange Protection Program gives you the opportunity to extend your coverage, without interruption, by one or two years. You can purchase your warranty extension through your Kubota dealer any time before the expiration of the regular Kubota Limited Warranty.<sup>1</sup>

### **BENEFITS AT A GLANCE**

- > Comprehensive coverage
- > Protects your investment
- > Provides peace of mind
- > Reliability of genuine Kubota parts
- > Extends both the Basic and applicable Power Train coverage
- Administered by Kubota Tractor Corporation
- > Sold and serviced by your authorized Kubota Extended Warranty dealer
- > Financing available, if purchased at the same time as your tractor
- No deductibles
- > Fully transferable



### FOR MORE INFORMATION, VISIT YOUR LOCAL KUBOTA DEALER OR CALL 888-398-9782

### **KUBOTA CREDIT CORPORATION, U.S.A.**

Since 1982, Kubota has extended a wide range of financing alternatives to customers through Kubota Credit Corporations, U.S.A. (KCC). KCC offers competitive interest rates, flexible down payments, monthly and seasonal payment terms, and a Kubota-sponsored property damage insurance program. Kubota dealers can tailor a variety of finance programs<sup>2</sup> to meet the specific requirements of their customers.

### FOR MORE INFORMATION, VISIT YOUR LOCAL KUBOTA DEALER OR WWW.KUBOTACREDITUSA.COM

- 1 Orange Protection is available in Florida for Commercial Customers only.
- 2 Subject to credit approval through Kubota Credit Corporation, U.S.A.

### KUBOTA FLEET PROGRAM

### Purchasing Kubota Turf Equipment is Now More Rewarding than Ever Before.

- > Kubota's Fleet program is designed for commercial customers of all sizes, making them eligible for a fleet discount with the purchase of just ONE unit.\*
- > Qualifications: Customer must qualify as commercial user by giving one of the following:
  - > Starter Fleet: Provide a business card and a picture of a truck & trailer
  - > Official FEIN documentation, business license OR tax documentation
  - National Hispanic Landscape Alliance (NHLA) Membership ID Card.
  - > National Association of Landscape Professionals (NALP) Starter Fleet Membership ID Card.
- Greater discounts are available with additional equipment purchases.\*\*
- > Kubota will also take into consideration your previous Kubota purchases in the last 365 days for all tier level qualification.\*\*

### THE MORE YOUR BUSINESS GROWS, THE MORE YOU SAVE!

	,									
ELIGIBLE EQUIPMENT	STARTER FLEET	STANDARD 1 Unit	PREMIUM 2-6 UNITS	ELITE 7+ UNITS						
W (21")	\$50	\$50	\$50	\$50						
W (36"-52")	\$200	\$250	\$350	\$400						
Z400 ALL	\$375	\$500	\$650	\$800						
SZ ALL	\$450	\$600	\$750	\$1,000						
Z700 ALL	\$450	\$600	\$750	\$1,000						
ZG200 / ZG300	\$450	\$600	\$750	\$1,000						
ZD1000	\$450	\$600	\$750	\$1,000						
ZD1200	\$675	\$900	\$1,200	\$1,400						
ZD1500	\$1,000	\$1,400	\$1,750	\$2,000						
F SERIES ALL	\$1,000	\$1,900	\$2,000	\$2,200						
IMPLEMENTS / ACCESSORIES***	5%	5%	10%	15%						
		(OUGTOMED DIGGOU	NE DED HAHE)	(OUGTOMER RICCOUNT REP. HAUT)						

(CUSTOMER DISCOUNT PER UNIT)

Kubota is Proud to be a Member of NALP and NHLA, which are Committed to the Success of Landscape and Lawn-Care Professionals.

All NALP & NHLA members are qualified for STANDARD Fleet status.



The National Association of Landscape Professionals (NALP) is the trade association for the landscape industry, representing the voice of more than 100,000 landscape professionals.



The National Hispanic Landscape Alliance (NHLA) represents the more than 500,000 Hispanic-Americans who work in the landscape industry across the U.S.



### "THANK YOU FOR YOUR SERVICE" PROGRAM

Kubota appreciates your service! All Veterans, Current Military, Police Officers, Firefighters and First Responders/EMT qualify for our Starter Fleet discount. You qualify for Starter Fleet Discounts because Kubota appreciates your service.

















<sup>\*</sup>Kubota Fleet Rewards will only be given to for-profit commercial mowing professionals. \*\*See your participating dealer for qualifying details. \*\*\*Only Attachments and Accessories purchased with the wholegoods qualify for these discounts. Kubota Tractor Corporation reserves the right to change the stated terms without notice.

### **KUBOTA LIMITED PRODUCT WARRANTY INFORMATION**

PRODUCT SERIES	NON-COMMERCIAL HOME & RESIDENTIAL USE	COMMERCIAL USE
T-Series	4 Year / 300 Hours	N/A
GR-Series	2 Year / 1500 Hours	1 Year / 1500 Hours
Z100 Series	4 Year / 300 Hours	N/A
Z400 Series	4 Year / 500 Hours	2 Year / Unlimited Hours
WG Series	2 Year <i>i</i>	Unlimited Hours
W Series	2 Year <i>i</i>	Unlimited Hours
SZ Series	2 Year <i>i</i>	Unlimited Hours
Z700 Series	4 Year / 750 Hours	2 Year / Unlimited Hours
<b>ZG200/300 Series</b>	2 Year <i>i</i>	Unlimited Hours
ZD Series	2 Year <i>i</i>	Unlimited Hours
F Series	2 Year /	Unlimited Hours



### EVER GO LOANER

### Benefits of EVER, GO Loaner Program:

Kubota understands that when a machine goes down, the work doesn't stop. As an extension of the Kubota Fleet Rewards Program, Kubota Dealers can now offer a loaner unit to Kubota Fleet customers.\*

### Here's How it Works:

If your commercial zero-turn mower requires a warranty repair and your local servicing dealer cannot repair it in within one business day, your dealer can provide you with a comparable loaner unit until your mower is ready to go. This ensures that you keep mowing and never miss a beat!

### **KTAC INSURANCE AGENCY**

Created specifically for Kubota owners, KTAC Insurance is a Kubota-endorsed property damage insurance program providing "all risk" protection.

### **BENEFITS AT A GLANCE**

- > Coverage against flood, wind, accidental damage, theft, fire, vandalism, and more
- > In-transit and off-property protection
- > Low \$250 deductible
- > Convenient payment options
- > Transportation reimbursement

KCC customers also receive 100% investment protection\* for the first 60 months of your loan.

### FOR MORE INFORMATION, CONTACT A KTAC REPRESENTATIVE AT 800-348-5802 OR VISIT WWW.KTACINSURANCEAGENCY.COM.

\*This is a summary of the Kubota-Endorsed Property Damage Insurance Program. This information is descriptive only and is not intended to be a solicitation or an offer to sell any insurance product or service, nor is the information a complete description of all of the terms, conditions and exclusions applicable. Actual coverage is subject to the language of the policy issued. This policy is underwritten by Ohio Indemnity Company.

### **KUBOTA LEASING**

In this credit-tight economy, leasing is critical to getting the Kubota equipment your business needs to grow. With the new Kubota Leasing program, commercial customers have access to flexible leasing that makes the full Kubota product line more affordable.

### PROGRAM HIGHLIGHTS INCLUDE:

- Affordable monthly payments
- > Fast, easy application process
- Application only required up to \$150,000
- > Same-day credit decisions with complete information
  - > Transactions starting at \$3,000 and up
  - > 24-, 36-, 48- or 60-month terms
- Flexible structures to match your cash flow and budget



Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (hp/kW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and U.S. territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured. Not all products are available at all dealerships.

ACCESSORY*	<b>Z200</b>	Z400	<b>Z700</b>	ZG200	ZG300	ZD1000	ZD1200	ZD1500	F SER	T SER	GR SER
MULCH KIT-42"	ZG1342									T2832	
MULCH KIT-48"	ZG1348	Z4048, Z4026 <sup>2</sup>	Z3448	ZD3145		ZD3145				T2838	GR2708
MULCH KIT-54"	ZG1354	Z4054, Z4027 <sup>2</sup>	Z3454	ZG3156		ZG3156					GR2709
MULCH KIT-60"		Z4060, Z4028 <sup>2</sup>	Z3460	ZG3157	ZD3165	ZG3157	ZD3166		ZG3157		
MULCH KIT-60"RD							F5266	F5266	F5266		
MULCH KIT-72"					ZD3175		ZD3167	ZD3167	F5372		
MULCH KIT-72"RD							ZD3168	ZD3168	F5276		
LIGHT KIT	ZG1302	Z3318A		ZD3116A	ZD3116A	ZD3116A	ZD3116A	ZD3116A	F8255		
GRASS BAGGER-42"	GCK42- 122Z									GCK42- 90T	
GRASS BAGGER-48"	GCK54- 100Z	GCK48- 400Z	GCK48- 700ZB	GCK54- 200Z		GCK48- ZD1011				GCK48- 90T	
GRASS BAGGER-54"1	GCK54- 100Z	GCK54- 400Z	GCK54- 700ZB	GCK54- 200Z		GCK54- ZD1011					GCK54- GR
GRASS BAGGER-60" <sup>1</sup>		GCK60- 400Z	GCK60- 700ZB	GCK54- 200Z	GCK60- 331ZA	GCK60- ZD1021	GCK60- ZD1211				
GRASS BAGGER-60" HOPPER <sup>1</sup>					GCK60H- 300Z		GCK60H- ZD1211				
GRASS BAGGER-72" <sup>1</sup>							GCK72- ZD1211				
GRASS BAGGER-72" HOPPER <sup>1</sup>					GCK72H- 300Z		GCK72H- ZD1211		GCK72- F39		
FRONT BLADE <sup>1</sup>									B2765A	T2833	GR2848
SNOWBLOWER <sup>1</sup>									F5220B	T2834	GR2846A
ROTARY BROOM <sup>1</sup>									L2163		GR2847
ARMREST KIT	ZG1341 <sup>3</sup>									ZG1341 <sup>5</sup>	
SUSPENSION SEAT	ZG1356 <sup>4</sup>	Z4051									
CANOPY	Z3366 <sup>4</sup> Z3355 <sup>4</sup>	Z3366 Z3355	Z3366 Z3365	E1123 Z3365	E1123 Z3375	E1123 Z3365	E1123 Z3375	E1123 Z3375	E1133		
OCDC 48"		Z4023	Z3348			ZD6148					
OCDC 54"		Z4024	Z3354			ZD6154					
OCDC 60"		Z4025	Z3360			ZD6160	ZD5960				
OCDC 72"							ZD5972	ZD5972			
MAINTENANCE LIFT KIT		Z4025	Z3338	ZG3127	ZG3137	Z3117					
HITCH KIT	ZG1343 <sup>3</sup>		Z3308			ZD3328	ZD3358				





### **KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive Grapevine, TX 76051 KubotaUSA.com





