



Kubota

# 2024 MOWERS BROCHURE



# COMPANY PROFILE

## HARD-WORKING KUBOTA TOOLS TO HELP YOU GET MORE DONE

For more than 50 years, Kubota has been your partner in pursuit of your property dreams.

As a do-it-yourselfer, you count on hard-working tools to help you get more done every day. And, like you, Kubota believes anything worth doing is worth doing right.

Whether you manage a two-acre yard or 2,000-acre ranch, hay field or construction site, our precision engineered orange equipment helps you conquer your goals one project at a time.

The entire Kubota product line – from utility vehicles and mowers, to tractors, hay tools and a full range of construction equipment – is quality built to keep you growing and improving your property, your business, and your community for years to come.

This brochure is a comprehensive look at our entire line and all the hard-working tools ready to help you get more done. Check out our recent innovations, new market entries, and products you likely already know well. We are constantly evolving to expand our products to better meet your needs for today and well into the future.

For more ideas to help you get more done, visit our website at [KubotaUSA.com](http://KubotaUSA.com).



**Kubota**<sup>®</sup>

---



# ***TABLE*** ***OF CONTENTS***

## **MOWERS**

|    |               |
|----|---------------|
| 2  | T Series      |
| 4  | GR Series     |
| 6  | Z200 Series   |
| 8  | Z400 Series   |
| 10 | Z700 Series   |
| 12 | SZ Series     |
| 14 | W Series      |
| 16 | ZG200 Series  |
| 18 | ZG300 Series  |
| 20 | ZD1000 Series |
| 22 | ZD1200 Series |
| 24 | ZD1611 Series |
| 26 | F Series      |



# MOWERS



## T Series

T2290KW | T2290KWT

|                           | T2290KW                                       | T2290KWT |
|---------------------------|---|----------|
| Engine Type               | OHV, air-cooled, gasoline, 2-cylinder, V-twin |          |
| Engine Model              | Kawasaki FR651V                               |          |
| Horsepower (gross)        | 21.5**  |          |
| Transmission              | Hydrostatic                                   |          |
| Fuel Capacity (gal.)      | 3.6   |          |
| Speed (mph) (forward)     | 0-5.7   | 0-6.7    |
| Overall Length            | 75.2"   |          |
| Deck Size                 | 42"   | 48"      |
| Overall Width (w/o mower) | 39.8"   |          |
| Weight (lbs.)             | 622   | 661      |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|   |           |           |
|---|-----------|-----------|
| Armrest Kit                             | Standard  |           |
| Grass Catcher<br>(blower not necessary) | GCK42-90T | GCK48-90T |
| Mulching Kit                            | T2832     | T2838     |
| Front Push Blade (48")                  | T2833     |           |
| Two-Stage Snowblower (46")              | T2834     |           |



Easy to operate, fun to drive, the Kubota T Series is durable, and packed with premium features to keep you mowing efficiently and comfortably.

- > Equipped with a high performance 21.5-horsepower Kawasaki Engine
- > All models are equipped with hydrostatic transmissions (HST) for precise control
- > High-back seat provides extra cushioning and support, with dual armrests for comfort
- > The thicker and higher-positioned steering wheel helps to reduce fatigue and enhances operator comfort and control
- > Convenient 12V power outlet lets you charge your phone or power accessories like an air compressor
- > Short 14" turning radius allows easy maneuvering around difficult objects
- > Mower height adjusts from 1" to 4" right from the operator's seat with simple dial-cam setting
- > Upgraded fabricated mower deck, along with new tubular-frame structure, improves strength, rigidity, and durability
- > Ductile cast iron front axle is strong and durable, handling all sorts of bumps & shocks
- > Compatible with a full line of performance-matched, quick-attach front implements

| MID-MOUNT MOWER SPECIFICATIONS |                      |            |
|--------------------------------|----------------------|------------|
|                                | RCK42P-90T           | RCK48P-90T |
| Number of Blades               | 2                    | 3          |
| Cutting Width                  | 42"                  | 48"        |
| Cutting Height                 | 1-4"                 |            |
| Height Adj. Increments         | 1/4"                 |            |
| Lift System                    | Manual w/ gas assist |            |



# MOWERS



## GR Series GR2020G | GR2120

**With Kubota's revolutionary Glide Steer<sup>®</sup>, all-wheel drive, plus tight turning, even difficult mowing conditions are now effortless.**

- › Your choice of a 3-cylinder, 17-horsepower Kubota diesel engine or a 2-cylinder, 20-horsepower Kohler gasoline engine
- › Glide Steer<sup>®</sup> provides excellent turning maneuverability with front wheels that turn up to 70 degrees while helping to prevent turf damage
- › All-wheel drive (AWD) characteristics provide outstanding traction needed for mowing on rolling terrain
- › Versatile HST transmission is controlled by a single foot pedal for a smooth and comfortable ride
- › Shaft-driven mower, transmission, and PTO offer smooth, virtually trouble-free operations
- › Cruise control, full-flat operator platform and a comfortable high-back, adjustable suspension seat increase operator comfort
- › 5" deep, 48" and 54" contoured design mower decks are able to produce professional results
- › Equipped with Kubota's Reverse Awareness System (KRA) for additional safety when mowing in reverse
- › Variety of implements available for year-round versatility, including a grass catcher, two-stage snowblower, front blade, and mulching kit



## GR Series

|                          | GR2020G                                 | GR2120                            |
|--------------------------|---|-----------------------------------|
| Engine Type              | Air-cooled, gasoline, 2-cylinder        | Liquid-cooled, diesel, 3-cylinder |
| Engine Model             | Kohler                                  | Kubota                            |
| Horsepower (gross)       | 20.5*                                   | 17**                              |
| Transmission             | Hydrostatic                             |                                   |
| Steering System          | Glide Steer, hydrostatic power steering |                                   |
| Deck Size                | 48"                                     | 48" / 54"                         |
| Overall Length           | 77.2"                                   |                                   |
| Overall Width (w/ mower) | 61" (w/48")                             | 66.9" (w/54")                     |
| Weight (lbs.) (w/ mower) | 871 (w/48")                             | 970 (w/54")                       |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|                     |                           |  |
|---------------------|---------------------------|--|
| Front Blade         | 48"                       |  |
| Grass Catcher       | 3-bag, 10-bushel capacity |  |
| Mulching Kit        | Optional                  |  |
| Snowblower          | 2-stage 46"               |  |
| Rear Weight Bracket | Optional                  |  |
| Suitcase Weights    | Optional                  |  |

### MOWER SPECIFICATIONS

|                        | RCK48-GR  | RCK54-GR |
|------------------------|-----------|----------|
| Number of Blades       | 3         |          |
| Cutting Width          | 48"       | 54"      |
| Cutting Height         | 1-4"      |          |
| Height Adj. Increments | 1/4"      |          |
| Lift System            | Hydraulic |          |

\* SAE J1940; \*\* SAE J1995



# MOWERS



## Z200 Series

Z232KW-42 | Z242KH-48 | Z242KW-48 | Z252KH-54 | Z252KW-54

### The ultimate residential zero-turn mower — combining style, comfort, and performance.

- › K-Ride® comfort system provides enhanced comfort (features may vary)
- › Adjustable suspension seat standard on KW 48" & 54" models, optional on KH models
- › Folding ROPS standard on KW 48" & 54" models, optional on KH models
- › A 10-gauge steel, welded mower deck provides professional-level cutting performance for homeowners
- › Push button start allows for easy one-handed starting
- › Covered storage box keeps things out of the weather and safe
- › Convenient cup holders keep your drinks at hand
- › Wide-tread tires give you better traction and weight distribution to help protect your lawn
- › The K-Lift (mechanical one-push deck-lift pedal) makes adjusting the cutting height simple
- › Z232KW comes with a 42-inch deck to maneuver in and out of intricate spaces smoothly and with ease
- › Zero-turn steering for superior machine control and precision mowing
- › The Z200 series is covered by a limited four-year, 300-hour factory warranty



## Z200 Series

|  | Z232KW-42  | Z242KH-48  | Z252KH-54 | Z242KW-48           | Z252KW-54 |
|--|--|--|-----------|---------------------|-----------|
| Engine Type                            | Air-cooled, gasoline, V-Twin   |  |           |                     |           |
| Engine Model                           | Kawasaki FR  | Kohler 7000  |           | Kawasaki FR         |           |
| Horsepower (gross)                     | 21.5*  | 22**   | 25**      | 21.5**              | 24**      |
| Displacement (cu. cm.)                 | 726  | 725  | 747       | 726                 |           |
| Transmission                           | Hydro-Gear™<br>Commercial<br>ZT2200 Integrated<br>Zero-Turn<br>Transaxle | Hydro-Gear™<br>Commercial ZT3100 Integrated<br>Zero-Turn Transaxle |           |                     |           |
| Fuel Tank Capacity (gal.)              | 3.6  | 4.3  |           |                     |           |
| Speed (mph) (forward/reverse)          | 0-6.5 / 0-4  | 0-8 / 0-4  |           |                     |           |
| Overall Length                         | 74.4"  | 79.0"  |           |                     |           |
| Overall Width<br>(w/ mower chute down) | 55.1"  | 61.1"  | 67.3"     | 61.1"               | 67.3"     |
| Overall Height                         | 66.7"  | 73.0" Fixed ROPS   |           | 68.4" Foldable ROPS |           |
| Wheel Base                             | 48.7"  | 47.0"  |           |                     |           |
| Weight (lbs.)                          | 643  | 811  | 827       | 844                 | 860       |

### MOWER SPECIFICATIONS

|                             |                                 |                |     |     |     |
|-----------------------------|---------------------------------|----------------|-----|-----|-----|
| Mower Deck Type             | Pro performance fabricated deck |                |     |     |     |
| Mower Lift System           | Mechanical                      |                |     |     |     |
| Mower Height, Increment     | 1.5-4.25", 1/4"                 | 1.5-4.5", 1/4" |     |     |     |
| Mower Deck Width            | 42"                             | 48"            | 54" | 48" | 54" |
| Blade Tip Speed (fpm)(max): | 17,700                          | 18,100         |     |     |     |

### IMPLEMENTS AND ACCESSORIES

|   |          |          |  |          |  |
|---|----------|----------|--|----------|--|
| Grass Catcher                             | Optional |          |  |          |  |
| Mulching Kit                              | Optional |          |  |          |  |
| Seat Suspension Kit                       | N/A      | Optional |  | Standard |  |
| LED Working Light Kit                     | Optional |          |  | Standard |  |
| Canopy Sunshade &<br>Deck Lift Assist Kit | N/A      | Optional |  |          |  |
| Arm Rest Kit                              | Optional | N/A      |  |          |  |
| Hitch Kit                                 | Optional | N/A      |  |          |  |

\* These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

\*\* Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

# MOWERS



## Z400 Series Z412KW | Z422KW | Z422KWT | Z411KW | Z421KW | Z421KWT

**Designed for the user who seeks professional performance and durability, as well as comfort and convenience.**

### Z412 and Z422 Features

- Premium adjustable suspension seat offers thick cushion with high back and a 4" adjustable seat slide that improves comfort and reduces fatigue
- All deck sizes have 13"x6.5"-6" front pneumatic tires
- Powered by the Kawasaki FS-Series Engines, the Z400 provides the torque you need to power through tall grass and rugged environments
- Simple operation of the mower lift pedal efficiently raises the mower deck
- The Z400 is driven by the dependable and durable Hydro-Gear ZT-3600 transmission - a Kubota exclusive
- The operation panel is conveniently and integrally located on the right fender and features a simple, easy-to-operate design
- Maximum forward travel speed of 10 mph contributes to quickly completing the job at hand
- Convenient 12V power outlet lets you charge your phone or power accessories like an air compressor
- A generous fuel tank capacity of 6.8 U.S. gallons (25.7 L)
- The seat features a thick cushion construction and slides a full 6" forward and back, allowing even prolonged operations to be undertaken in maximum comfort (Z411 & Z421)
- Light and smooth steering lever operation with dampers that have three adjustment positions



## Z400 Series

|                                 | Z412KW-48<br>Z411KW-48           | Z422KW-54<br>Z421KW-54 | Z422KWT-60<br>Z421KWT-60 |
|---------------------------------|----------------------------------|------------------------|--------------------------|
| Engine Type                     | Air-cooled, gasoline, 2-cylinder |                        |                          |
| Engine Model                    | Kawasaki FS 651V                 | Kawasaki FS 730V       |                          |
| Horsepower (gross)*             | 22                               | 24                     |                          |
| Displacement (cu. cm.)          | 726                              |                        |                          |
| Transmission                    | Hydro-Gear ZT-3600               |                        |                          |
| Front Tire                      | 13" x 5" x 6"                    |                        | 13" x 6.5" - 6"          |
| Fuel Capacity (gal.)            | 6.8                              |                        |                          |
| Speed (mph) (forward/reverse)   | 0-10 / 0-5                       |                        |                          |
| Overall Length                  | 48.7"                            |                        | 54.2"                    |
| Overall Width (w/ mower chute)  | 61.1"                            | 67.3"                  | 73.6"                    |
| Overall Height (w/ROPS upright) | 69.8"                            |                        |                          |
| Weight (lbs.) (w/ mower)        | 856                              | 870                    | 904                      |

### MOWER SPECIFICATIONS

|                              | RCK48P-400Z             | RCK54P-400Z | RCK60P-400Z |
|------------------------------|-------------------------|-------------|-------------|
| Mower Deck Type              | Kubota Side Discharge   |             |             |
| Mower Lift System            | Mechanical / Foot pedal |             |             |
| Deck Depth                   | 5"                      |             |             |
| Cutting Height               | 1.5-5", 1/4"            |             |             |
| Cutting Width                | 48"                     | 54"         | 60"         |
| Blade Tip Speed (fpm) (max.) | 18,880                  | 18,700      | 18,300      |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|                                     | Z400 Series |
|-------------------------------------|-------------|
| Grass Catcher Kit                   | Optional    |
| Mulching Kit                        | Optional    |
| Chute Block Kit                     | Optional    |
| Suspension Seat Kit                 | Optional    |
| LED Work Light Kit                  | Optional    |
| Operator Controlled Discharge Chute | Optional    |
| Canopy Sunshade                     | Optional    |
| Maintenance Lift Kit                | Optional    |

\* SAE J1995

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

# MOWERS



## Z700 Series

Z781KWiTW | Z751KWi | Z781KWi | Z781KWiTi Z724XKW |  
Z726XKW | Z723KH | Z724KH | Z725KH

Designed for the commercial landscape professional, the Z700 Series offers performance, productivity, comfort and the durability that Kubota is known for.

### Z781KWiTW

- › Airless (Tweel) tires now standard on 54" and 60" models

### Z700EFI Model Features

- › Kawasaki FX EFI engines feature a fully integrated electronic governor (E-GOV) and a cutting edge ECU control unit. They deliver outstanding performance without power loss
- › EFI dial throttle control delivers effortless engine control
- › LCD engine meter provides all the information you need to keep your Z700 EFI unit running at optimum efficiency
- › Equipped with 24" low profile tires
- › 12V Power outlet can charge or power many devices

### All Model Features

- › Premium adjustable suspension seat offers a thick cushion with a 19.6" high back and a 6" adjustable seat slide that allows you to find the ideal seating position for maximum comfort
- › New deck step indicator provides easier access
- › New water and dust proof safety switches help to reduce failures
- › 6"-deep mower deck and anti-scalp rollers help to provide fast, clean, superior grass-cutting performance
- › With an 11.2 mph maximum speed, it's Kubota's fastest zero-turn mower
- › Dual Parker® transmission with an integrated pump and motor designed for increased efficiency and simplified maintenance



## Z700 Series

|                                 | <b>Z781KWi-54</b><br><b>Z781KWTi-60</b><br><b>Z781KWiTW</b> |  |                        |  |                        |  |                        | <b>Z724XKW-3-48</b><br><b>Z724XKW-3-54</b> |                              | <b>Z726XKW-3-60</b> |                              | <b>Z723KH-3-48</b> |                              | <b>Z724KH-3-54</b> |  | <b>Z725KH-3-60</b> |  |  |
|---------------------------------|---|--|------------------------|--|------------------------|--|------------------------|--|------------------------------|---------------------|------------------------------|--------------------|------------------------------|--------------------|--|--------------------|--|--|
| Engine Type                     | Air-cooled, gasoline, V-Twin                                |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Engine Model                    | Kawaski<br>FX 730V EFI                                      |  | Kawaski<br>FX 850V EFI |  | Kawasaki FX FX<br>730V |  | Kawasaki FX FX<br>801V |  | KOHLER Command<br>Pro® CV682 |                     | KOHLER Command<br>Pro® CV732 |                    | KOHLER Command<br>Pro® CV742 |                    |  |                    |  |  |
| Horsepower (gross)              | 25.5*   |  | 29.5*                  |  | 23.5*                  |  | 25.5*                  |  | 22.5**                       |                     | 23.5**                       |                    | 25**                         |                    |  |                    |  |  |
| Displacement (cu. cm.)          | 726   |  | 852                    |  | 726                    |  | 852                    |  | 694                          |                     | 694                          |                    | 747                          |                    |  |                    |  |  |
| Transmission                    | Parker HTG14  |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Fuel Capacity (gal.)            | 11.6  |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Speed (mph) (forward/reverse)   | 0–11.2 / 0–5.6  |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Overall Length                  | 83.9"   |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Overall Width (w/ mower)        | 61.3"   |  | 67.3"/ 73.8"           |  | 61.3"/ 67.3"           |  | 73.8"                  |  | 61.3"                        |                     | 67.3"                        |                    | 73.8"                        |                    |  |                    |  |  |
| Overall Height (w/ROPS upright) | 70.1"   |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Wheel Base                      | 50.9"   |  |                        |  |                        |  |                        |  |                              |                     |                              |                    |                              |                    |  |                    |  |  |
| Weight (lbs.) (w/ mower)        | 1,215   |  | 1,254/1,285            |  | 1,207/1,223            |  | 1,276                  |  | 1,212                        |                     | 1,226                        |                    | 1,257                        |                    |  |                    |  |  |

### MOWER DECK SPECIFICATIONS

| Mower Deck Type               | Commercial fabricated deck |  |                    |  |                         |  |                   |  |                   |  |                   |  |                   |  |
|-------------------------------|----------------------------|--|--------------------|--|-------------------------|--|-------------------|--|-------------------|--|-------------------|--|-------------------|--|
| Mower Deck Width, Lift System | 48"<br>Mechanical          |  | 54"/60" Mechanical |  | 48" / 54"<br>Mechanical |  | 60"<br>Mechanical |  | 48"<br>Mechanical |  | 54"<br>Mechanical |  | 60"<br>Mechanical |  |
| Cutting Height                | 1–5"                       |  |                    |  |                         |  |                   |  |                   |  |                   |  |                   |  |
| Height Adj. Increments        | 1/4"                       |  |                    |  |                         |  |                   |  |                   |  |                   |  |                   |  |
| Mower Deck Depth              | 6"                         |  |                    |  |                         |  |                   |  |                   |  |                   |  |                   |  |
| Blade Tip Speed (fpm) (max):  | 18,600                     |  | 18,400 / 18,600    |  |                         |  |                   |  | 18,600            |  |                   |  |                   |  |

### IMPLEMENTS AND ACCESSORIES

| Premium Suspension Seat             | Standard  |  |  |  |  |  |  |
|-------------------------------------|---|--|--|--|--|--|--|
| Grass Catcher                       | Optional – 10 bushels (48" / 54"), 11 bushels (60") |  |  |  |  |  |  |
| Mulching Kit                        | Optional  |  |  |  |  |  |  |
| Operator-Controlled Discharge Chute | Optional  |  |  |  |  |  |  |
| Towing Hitch                        | Optional  |  |  |  |  |  |  |
| LED Working Light Kit               | Optional  |  |  |  |  |  |  |
| Maintenance Lift Kit                | Optional  |  |  |  |  |  |  |
| Canopy Sunshade                     | Optional  |  |  |  |  |  |  |
| Karu Mulching Blade                 | Optional, 60" only                                  |  |  |  |  |  |  |

\* SAEJ1995

These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.

\*\* SAE J1940

Power (hp) specifications for individual gasoline engine models are rated pursuant to Society of Automotive Engineers (SAE) J1940 or J2723 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Gross engine hp will be higher than actual engine power which is affected by accessories, application, engine speed, ambient operating conditions and other factors. The gross engine horsepower information is for comparison purposes only.

# MOWERS



## SZ Series

SZ19NC-36-2 | SZ22NC48-2 | S26NC-52-2 | SZ26NC-61-2

The Kubota SZ series commercial stand-on is the answer to get more done, faster and more efficiently, in even the tightest spaces while delivering superior comfort and durability.

### All Models

- › Commercial-grade Kawasaki FX & FT EFI gas engines equipped with Hydro-Gear integrated transmissions
- › Adjustable front baffle on cutting decks (on 48", 52" and 61")
- › Smooth 3-position adjustable dampened controls
- › Tool-less adjustable front reference bar
- › Large operator platform (48", 52" and 61" models)
- › Tool-less tracking adjustment
- › Ergonomic cushion pad
- › No-flat front castors



## SZ Series

|                         | SZ19NC-36-2                                    | SZ22NC-48-2  | SZ26NC-52-2         | SZ26NC-61-2 |
|-------------------------|--|--|---------------------|-------------|
| Engine Type             | Kawasaki FX600V                                | Kawasaki FX691V  | Kawasaki FT730V-EFI |             |
| Horsepower (gross)*     | 19 HP  | 22 HP  | 26 HP               |             |
| Transmission            | Hydro-Gear ZT3100                              | Hydro-Gear ZT3600  |                     |             |
| Speed                   | 9 MPH  | 11 MPH   |                     |             |
| Fuel Capacity (gal.)    | 5.1  | 6.5  |                     |             |
| Deck Type               | Fabricated Floating                            |  |                     |             |
| Deck (ga)               | 7 ga top and side skirts w/ 3 ga reinforcement | 10 ga top and 7 ga side skirts w/ 3 ga reinforcement w/ adjustable front baffle (on -2 models) |                     |             |
| Deck Spindle & Bearings | 1" Shaft w/ Maintenance-Free Seal Bearings     |  |                     |             |
| Deck Size               | 36"  | 48"  | 52"                 | 61"         |
| BladeTip Speed (fpm)    | 17,950   | 17,773   | 18,585              | 18,850      |
| Cutting Height          | Adjustable 1.5" - 4.5"                         |  |                     |             |
| Front Tires (Flat-Free) | 11" x 6"-5"                                    | 13" x 6.5"-6"  |                     |             |
| Rear Tire               | 20" x 8"-10"                                   | 23" x 8.5"-12"   | 23" x 10.5"-12"     |             |
| Weight (lbs.)           | 800  | 961  | 991                 | 1,028       |
| Length                  | 64"  |  |                     |             |
| Height                  | 45"  | 45.75"   |                     |             |

### ATTACHMENTS

|                             |       |         |          |         |
|-----------------------------|-------|---------|----------|---------|
| Mulch Kit                   | SMK36 | SMK48-2 | SMK52-2  | SMK61-2 |
| Discharge Plate             | SBP36 | SBP48-2 | SBP52-2  | SBP61-2 |
| Weight Kit                  | SWK36 | SWK48   |          |         |
| Striping Kit                | N/A   | SSK48   | SSK52-61 |         |
| Deck Lift Assist            | N/A   | SZLA01  |          |         |
| Accelerator Grass Catcher 1 | SGC61 |         |          |         |

\* SAEJ1995





## W Series

WHF14NC-36-2 | WHF15NC-48-2 | WHF19NC-52-2

**Kubota's durable Commercial Walk-Behind Mowers offer options for all commercial mowing, small and large.**

### WHF14NC-36-2 / WHF15NC-48-2 / WHF19NC-52-2

- › The ergonomic handle design and intuitive control layout keep operators mowing confidently and comfortably
- › All models use commercially proven Kawasaki FS-series engines to deliver reliable performance and superior durability
- › The durable Hydro-Gear ZT-2800 hydrostatic transaxles deliver smooth and simple operation with ground speeds of up to 6.5 mph
- › The large rear wheels provide ample ground clearance to enable smooth, easy maneuverability on all types of terrain
- › The dependable cutting decks are equipped with steel-fabricated spindle assemblies and welded baffle systems
- › Easy to maintain features include a tool-less oil drain, a handy external oil filter location and easy battery access



## Walk-Behind Mowers

|                       | WHF14NC-36-2                              | WHF15NC-48-2    | WHF19NC-52-2    |
|-----------------------|---|-----------------|-----------------|
| Engine Type           | Kawasaki FS481V                           | Kawasaki FS541V | FS600V Kawasaki |
| Horsepower (gross)*   | 14.5                                      | 15              | 18.5            |
| Fuel Capacity (gal.)  |   | 5               |                 |
| Speed (mph)           |   | 6.5             |                 |
| Transmission          | Hydro-Gear ZT-2800 transmissions          |                 |                 |
| Mower Deck Type       | Fabricated Floating Deck with Wear Band   |                 |                 |
| Deck (ga)             | 10 ga deck with 10 ga top and 7 ga skirts |                 |                 |
| Blade Tip Speed (fpm) | 18,127                                    | 16,832          | 18,645          |
| Cutting Height        | 1.5" - 4.5"                               |                 |                 |
| Starter               | Electric                                  |                 |                 |
| Hand Controls         | Ergonomic Bull Horn                       |                 |                 |
| Deck Spindle          | Maintenance-free with 1" shaft            |                 |                 |
| Spindle Bearings      | Precision-ground double-sealed bearings   |                 |                 |
| Deck Drive            | Warner Mag Stop 105 ft-lb electric clutch |                 |                 |
| Front Tires           | 11" x 6"-4" No-Flat                       |                 |                 |
| Rear Tires            | 20" x 6.5" - 8"                           | 20" x 8" - 8"   |                 |
| Brakes                | (-2) Hydrostatic Dynamic Braking          |                 |                 |
| Weight (lbs.)         | 774                                       | 789             | 832             |
| Length                | 78"                                       |                 |                 |
| Height                | 40.3"                                     | 43"             |                 |

\* SAE J1995

# MOWERS



## ZG200 Series ZG222 | ZG227

**The professional-quality performance, exceptional comfort, and outstanding reliability of the ZG200 Series make it the ultimate mowing machine for both professionals and homeowners.**

- › Powered by durable 21.1- and 26-horsepower air-cooled Kubota gasoline engines
- › Zero-turn steering for superior navigation
- › Reliable, ultra-smooth, hydrostatic transmission offers superior durability and performance
- › Heavy-duty Pro Commercial Mower Deck features a unique baffle system that discharges grass clippings for professional looking results
- › Optional mulching system provides a beautiful finish, even in thick grass
- › Foot-operated hydraulic deck-lift system for easy adjustment
- › Spacious platform, comfortable and supportive seating, and an easy-to-reach cup holder for operator comfort
- › Operator-friendly instrument panel puts everything within close reach
- › Convenient mower, HST, and engine access for hassle-free maintenance
- › Foldable ROPS standard



## ZG200 Series

|                                  | ZG222-48                                | ZG227-54/60      |
|----------------------------------|---|------------------|
| Engine Type                      | Kubota air-cooled, gasoline, 2-cylinder |                  |
| Engine Model                     | Kubota KGZ770-M3                        | Kubota KGZ770-M2 |
| Horsepower (gross)*              | 21.1                                    | 26               |
| Displacement (cu. cm.)           | 768                                     |                  |
| Transmission                     | 2-HST w/ gear reduction                 |                  |
| Fuel Capacity (gal.)             | 7.1                                     |                  |
| Speed (mph) (forward/reverse)    | 0-9 / 0-5                               |                  |
| Overall Length                   | 82.5"                                   | 82.5" / 83.7"    |
| Overall Width (w/ mower chute)   | 61"                                     | 67.3" / 75.2"    |
| Overall Height (w/ ROPS upright) | 69.9"                                   |                  |
| Overall Height (w/ ROPS folded)  | 52.8"                                   |                  |
| Weight (lbs.) (w/ mower)         | 1,168                                   | 1,190 / 1,235    |

### MOWER SPECIFICATIONS

|                                | ZG222-48               | ZG227-54/60            |
|--------------------------------|------------------------|------------------------|
| Mower Deck Type                | Welded, side discharge | Welded, side discharge |
| Mower Deck Width / Lift System | 48" / Hydraulic        | 54 or 60" / Hydraulic  |
| Cutting Height                 | 1-5"                   |                        |
| Height Adj. Increments         | 1/4"                   |                        |
| Mower Deck Depth               | 6" (48)                | 6"                     |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

#### ZG200 Series

|                   |          |
|-------------------|----------|
| Canopy Sunshade   | Optional |
| Grass Catcher     | Optional |
| Mulching Kit      | Optional |
| Working Light Kit | Optional |

\* SAE J 1940

# MOWERS



## ZG300 Series ZG327P | ZG327RP

**Built for power, durability, and performance, the ZG300 Series features deep mower decks for exceptional cutting performance.**

- › ZG300 mowers are available with durable Kubota air-cooled gasoline engines with 26 gross horsepower
- › Durable HST transmission optimizes performance to achieve maximum results
- › Pro Commercial Deck is a superior deep mower deck that helps to ensure excellent cutting performance
- › Anti-scalp swivel rollers can rotate a full 360 degrees helping to prevent unsightly turf damage
- › Large-capacity dual fuel tanks on ZG300 Series models
- › Foot-controlled hydraulic deck lift and PTO wet disc clutch
- › Unique maintenance lift system allows easy mower access (optional on ZG300 models)
- › Tie-down for securing onto flatbed truck or trailer for convenient transportation
- › “Flat-free” front caster tires are standard with ZG300 and enable mowing operation without worrisome flat-tire downtime



## ZG300 Series

### ZG327P-60 ZG327RP-60R

|                                |   |
|--------------------------------|---|
| Engine Type                    | Kubota air-cooled, gasoline, 2-cylinder |
| Engine Model                   | Kubota KGZ770                           |
| Horsepower (gross)*            | 26                                      |
| Displacement (cu. cm.)         | 768                                     |
| Transmission                   | 2-HST w/gear reduction                  |
| Fuel Capacity (gal.)           | 12.7                                    |
| Speeds (mph) (forward/reverse) | 0–10.6 / 0–5.3                          |
| Overall Length                 | 87.8"                                   |
| Overall Width (w/ mower)       | 75.2"                                   |
| Overall Height                 | 75.4"                                   |
| Weight (lbs.)                  | 1,565                                   |

### MOWER SPECIFICATIONS

|                                |                                 |
|--------------------------------|---------------------------------|
| Mower Deck Type                | Welded, side, or rear discharge |
| Mower Deck Width / Lift System | 60" / Hydraulic                 |
| Mower Height / Increment       | 1–5" / 1/4"                     |
| Mower Deck Depth               | 6.5"                            |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

### ZG300 Series

|                     |          |
|---------------------|----------|
| Canopy Sunshade     | Optional |
| Front Utility Blade | Optional |
| Grass Catcher**     | Optional |
| Mulching Kit        | Optional |
| Spark Arrester      | Optional |
| Striping Kit        | Optional |
| Working Light Kit   | Optional |
| Karu Mulching Blade | Optional |

\* SAE J 1940



Product may be shown with optional equipment

## ZD1000 Series ZD1011 | ZD1021

**Top to bottom, front to back, and inside and out, Kubota's ZD Series of zero-turn mowers is engineered for quality. Versatile and reliable, the ZD1000 compact mower can handle jobs big and small.**

- › The Kubota ProDeck with ACS (Aerodynamic Cutting System®) delivers professional looking results, meaning you can get the job done better and faster
- › Redesigned clean-cut blades have a new shape that improves overall load balance and provides a longer service life
- › Discharge chute has been redesigned with a flexible yet strong material, to help ensure a smoother and more uniform discharge of clippings
- › Improved fuel efficiency — up to 22% better
- › Low center of gravity provides stability on slopes and uneven ground
- › A two-pedal hydraulic deck-lift system lets you easily raise and lower the deck with your foot



## ZD1000 Series

|                                 | ZD1011-48 / ZD1011-54                    | ZD1021-60                     |
|---------------------------------|--|-------------------------------|
| Engine Type                     | Kubota liquid-cooled, diesel, 3-cylinder |                               |
| Engine Model                    | Kubota D782-E4-ZD-3                      | Kubota D902-E4-ZD-2           |
| Horsepower (gross)*             | 19.3                                     | 21.6                          |
| Displacement (cu. cm.)          | 778                                      | 898                           |
| Transmission                    | 2-HST w/ gear reduction                  |                               |
| Fuel Capacity (gal.)            | 6.0                                      |                               |
| Speed (mph) (forward/reverse)   | 0-9 / 0-5                                |                               |
| Overall Length                  | 87.8"                                    | 88.8"                         |
| Overall Width (w/ mower chute)  | 61.6" / 67.3"                            | 73.8"                         |
| Overall Height (w/ROPS upright) | 74.4"                                    |                               |
| Front Tires                     | 13 x 5.0-6 smooth pneumatic              | 13 x 6.5-6 smooth pneumatic   |
| Rear Tires                      | 24 x 9.5-14 low-profile tire             | 24 x 12.0-14 low-profile tire |
| Brakes                          | Wet multi-discs, foot applied, released  |                               |
| Weight (lbs.) (w/ mower)        | 1,296 / 1,323                            | 1,389                         |

## MOWER DECK SPECIFICATIONS

|                              | RCK48P-1000Z            | RCK54P-1000Z | RCK60P-1000Z |
|------------------------------|-------------------------|--------------|--------------|
| Mower Deck Type              | Kubota ProDeck with ACS |              |              |
| Mower Lift System            | Hydraulic               |              |              |
| Deck Depth                   | 6"                      |              |              |
| Cutting Height               | 1-5"                    |              |              |
| Cutting Width                | 48"                     | 54"          | 60"          |
| Blade Tip Speed (fpm) (max.) | 17100                   |              | 18200        |

## ADDITIONAL IMPLEMENTS AND ACCESSORIES

|                                       | ZD1011-48 / ZD1011-54 | ZD1021-60 |
|---------------------------------------|-----------------------|-----------|
| "Catch All" 2-Bag Style Grass Catcher | Optional              |           |
| Hitch Kit                             | Optional              |           |
| Operator-Controlled Discharge Chute   | Optional              |           |
| Work Light Kit                        | Optional              |           |
| Canopy Sunshade                       | Optional              |           |

\* SAE J1995



## ZD1200 Series

ZD1211 | ZD1211R | ZD1211L | ZD1211RL

**With a bigger engine and wider mower deck, the ZD1200 gets the job done with speed and efficiency. These premium mowers incorporate the best of Kubota's advanced technology in every detail and it helps to ensure both superior mowing performance and supreme operator comfort.**

- › The large LCD meter shows all of the key indicators you need to maximize cutting performance and operability
- › For faster operation and better ergonomics, the mower deck controls are on the right side within easy reach of your hand, letting you quickly and easily adjust the cutting height
- › Equipped with low profile tires
- › Redesigned HST levers not only provide more legroom but more settings to choose from, to help ensure smoother operation, better zero-turn maneuverability, and greater job efficiency
- › A more comfortable, fully padded and reclining bucket seat means less operator fatigue and greater productivity — with dual adjustable armrests, higher backrest, and lumbar support
- › The optional “Catch All” hopper-style grass catcher holds 11.4 bushels of clippings and can be emptied while the operator remains seated



## ZD1200 Series

|                                 | ZD1211-60 / ZD1211R-60R                  | ZD1211L-72 / ZD1211RL-72R |
|---------------------------------|--|---------------------------|
| Engine Type                     | Kubota liquid-cooled, diesel, 3-cylinder |                           |
| Engine Model                    | Kubota D1105-E4-ZD-2                     |                           |
| Horsepower (gross)*             | 24.8                                     |                           |
| Displacement (cu. cm.)          | 1,123                                    |                           |
| Transmission                    | 2-HST w/gear reduction                   |                           |
| Fuel Capacity (gal.)            | 13.0                                     |                           |
| Speed (mph) (forward/reverse)   | 0-10.6 / 0-5.3                           |                           |
| Overall Length                  | 89"                                      | 93.7"                     |
| Overall Width (w/ mower chute)  | 73.8" / 63"                              | 85.8" / 75.2"             |
| Overall Height (w/ROPS upright) | 78.7"                                    |                           |
| Front Tires                     | 15 x 6.5-8 smooth semi-pneumatic         |                           |
| Rear Tires                      | 26 x 12.0-16 low-profile tire            |                           |
| Brakes                          | Wet multi-discs, foot applied, released  |                           |
| Weight (lbs.) (w/ mower)        | 1,687 / 1,720                            | 1,764 / 1,786             |

### MOWER DECK SPECIFICATIONS

|                              | RCK60P-1200Z            | RCK60RP-1200Z  | RCK72P-1200Z            | RCK72RP-1200Z  |
|------------------------------|-------------------------|----------------|-------------------------|----------------|
| Mower Deck Type              | Kubota ProDeck with ACS | Kubota ProDeck | Kubota ProDeck with ACS | Kubota ProDeck |
| Mower Lift System            | Hydraulic               |                |                         |                |
| Deck Depth                   | 6.0"                    | 5.5"           | 6.0"                    | 5.5"           |
| Cutting Height               | 1-5"                    |                |                         |                |
| Cutting Width                | 60"                     |                | 72"                     |                |
| Blade Tip Speed (fpm) (max.) | 18,050                  | 16,900         | 18,050                  | 18,000         |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|  | ZD1211-60 / ZD1211-60R | ZD1211L-72 / ZD1211RL-72R |
|--|------------------------|---------------------------|
| "Catch All" Hopper-Style Grass Catcher |                        | Optional                  |
| "Catch All" 2-Bag Style Grass Catcher  |                        | Optional                  |
| Karu Mulching Blade                    |                        | Optional, 60" & 72"       |
| Hitch Kit                              |                        | Optional                  |
| Operator-Controlled Discharge Chute    |                        | Optional                  |
| Work Light Kit                         |                        | Optional                  |
| Canopy Sunshade                        |                        | Optional                  |

\* SAE J1995

# MOWERS



## ZD1611 Series

ZD1611RL | ZD1611LF | ZD1611RFL

The ZD1611 stakes its place at the top of the line of Kubota's diesel zero-turn mowers with the electronically controlled Kubota diesel engine and the Aerodynamic Cutting System® to significantly enhance cutting performance.

- › The flexible discharge chute helps to ensure superior scattering of clippings
- › Wider, thicker, and more durable blades contribute to optimized air flow
- › Compared to previous model the ZD1611 features an enlarged flywheel that is responsible for an increase from 29.1 hp (21.7 kW) to 30.8 hp (23 kW)
- › The hydraulic transmission, a unique Kubota feature, ideally complements the V1505 Kubota diesel engine
- › The 3.5" (88.9 mm) wide LCD Panel provides machine diagnostics and machine performance indicators
- › Two-pedal type hydraulic lift system enables the operator to easily raise the mower deck when an obstacle is encountered
- › Operators do not need to remove hands from levers to engage the parking brake through use of the conveniently located parking brake pedal
- › The simple and easy to use two-pin type maintenance lift allows for quick access to the mower deck making maintenance a breeze



## ZD1600 Series

|                                 | ZD1611RL-60R                            | ZD1611LF-72 / ZD1611RLF-72R |
|---------------------------------|---|-----------------------------|
| Engine Type                     | Diesel, liquid-cooled (4cyl.) with DPF  |                             |
| Engine Model                    | Kubota V1505-CR-TE5-ZD1                 |                             |
| Horsepower (gross)*             | 30.8                                    |                             |
| Displacement (cu. cm.)          | 1,498                                   |                             |
| Transmission                    | 2-HST w/gear reduction                  |                             |
| Fuel Capacity (gal.)            | 13.0                                    |                             |
| Speed (mph) (forward/reverse)   | 0-10.6 / 0-5.3                          |                             |
| Overall Length                  | 105.7"                                  |                             |
| Overall Width (w/ mower chute)  | 63"                                     | 85.8" / 75.2"               |
| Overall Height (w/ROPS upright) | 78.7"                                   |                             |
| Front Tires                     | 15 x 6.5-8 smooth semi-pneumatic        |                             |
| Rear Tires                      | 26 x 12.0-16 low-profile tire           |                             |
| Brakes                          | Wet multi-discs, foot applied, released |                             |
| Weight (lbs.) (w/ mower)        | 2,105                                   | 2,094 / 2,105               |

### MOWER DECK SPECIFICATIONS

|                              | RCK60RP-1500Z  | RCK72P-1500Z            | RCK72RP-1500Z  |
|------------------------------|----------------|-------------------------|----------------|
| Mower Deck Type              | Kubota ProDeck | Kubota ProDeck with ACS | Kubota ProDeck |
| Mower Lift System            | Hydraulic      |                         |                |
| Deck Depth                   | 5.5"           | 6.0"                    | 5.5"           |
| Cutting Height               | 1-5", 1/4"     |                         |                |
| Cutting Width                | 60"            | 72"                     |                |
| Blade Tip Speed (fpm) (max.) | 17,200         | 18,300                  |                |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|  | ZD1611RL      | ZD1611LF | ZD1611RFL |
|--|---------------|----------|-----------|
| Mulch Kits                                 | Optional      |          |           |
| Work Light Kit                             | Optional      |          |           |
| Canopy Sunshade                            | Optional      |          |           |
| Operator Controlled Discharge Chute (OCDC) | N/A           | Optional | N/A       |
| Karu Mulching Blade                        | Optional, 72" |          |           |

\* SAE J1995

# MOWERS



## F Series F2690E | F2690 | F3710

**The F Series sets a new standard for professional front-mount mowers with cleaner emissions and greater power, precision, and efficiency.**

- › Kubota diesel engines provide fast, and efficient job performance with high-torque rise that allows you to power through tall or wet grass
- › The F3710 offers the highest-ever horsepower among all Kubota front-mount mowers
- › 6" deep, side-discharge deck design lets tall grass stand up so it can be cut more easily with a cleaner appearance
- › Large operator's platform, deluxe high-back seat with four separate adjustments and operator levers, for maximum driving comfort and convenience
- › Hydrostatic power steering reduces operator fatigue and makes it easier to mow around trees and other obstacles



## F Series

|                               | F2690E                                   | F2690          | F3710                                    |
|-------------------------------|--|----------------|--|
| Engine Type                   | Kubota liquid-cooled, diesel, 3-cylinder |                | Kubota liquid-cooled, diesel, 4-cylinder |
| Engine Model                  | Kubota D1105                             |                | Kubota V1505-CR-TE5-FM2                  |
| Horsepower (gross)*           | 24.8                                     |                | 36.9                                     |
| Displacement (cu. cm.)        | 1,123                                    |                | 1,498                                    |
| Transmission                  | Hydrostatic, 2-range                     |                |  |
| Fuel Capacity (gal.)          | 16.1                                     |                |  |
| Speed (mph) (forward/reverse) | 0-12 / 0-6.2                             | 0-12.4 / 0-6.8 |  |
| Overall Length                | 96.5"                                    |                | 99.6"                                    |
| Overall Width                 | 48.8"                                    | 53.9"          |  |
| Overall Height                | 77.8"                                    | 78.1"          |  |
| Min. Ground Clearance         | 6.9"                                     | 7.3"           |  |
| Weight (lbs.)                 | 1,559                                    | 1,590          | 1,872                                    |

### MOWER SPECIFICATIONS

|                  | RCK60P-F39             | RCK72P-F39 | RCK60R-F36             | RCK72R-F36 |
|------------------|------------------------|------------|------------------------|------------|
| Mower Deck Type  | Welded, side discharge |            | Welded, rear discharge |            |
| Cutting Width    | 60"                    | 72"        | 60"                    | 72"        |
| Cutting Height   | 1-5", 1/4"             |            |                        |            |
| Mower Deck Depth | 6"                     |            | 5.5"                   |            |

### ADDITIONAL IMPLEMENTS AND ACCESSORIES

|  | F2690E | F2690    | F3710 |
|--|--------|----------|-------|
| Hard Cab Enclosure                         |        | Optional |       |
| Cab Heater                                 |        | Optional |       |
| Grass Catcher<br>12-Bushel, Low-Dump Style |        | Optional |       |
| Debris Blower                              |        | Optional |       |
| 60" Front Blade                            |        | Optional |       |
| 60" Rotary Sweeper                         |        | Optional |       |
| Snow Blower                                |        | Optional |       |
| Mulching Kit                               |        | Optional |       |

\* SAE J1995







**Kubota®**

**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive  
Grapevine, TX 76051  
KubotaUSA.com



This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. See dealer for details.  
77700-13569 Rev. 11-23 Turf Full Line Brochure | © 2023 Kubota Tractor Corporation