

Specifications

Model		LX2610SUHSD	LX2610HSD	LX3310HSD	LX2610HSDC	LX3310HSDC
Engine						
Type		E-TVCS, liquid cooled, 3-cylinder diesel		E-TVCS, liquid cooled, 4-cylinder diesel	E-TVCS, liquid cooled, 3-cylinder diesel	E-TVCS, liquid cooled, 4-cylinder diesel
Make, Model		D1305-E4-D36-R		V1505-CR-TE5-D36R1	D1305-E4-D26-Q	V1505-CR-TE5-D36Q1
PTO horsepower	HP (kW)	19.5 (14.5)		27.0 (20.1)	19.5 (14.5)	27.0 (20.1)
Engine gross horsepower*	HP (kW)	24.8 (18.5)		30.8 (23.0)	24.8 (18.5)	30.8 (23.0)
Rated RPM	rpm	2500				
Bore and stroke	in. (mm)	ø3.1 × 3.5 (ø78 × 88)		ø3.1 × 3.1 (ø78 × 78.4)	ø3.1 × 3.5 (ø78 × 88)	ø3.1 × 3.1 (ø78 × 78.4)
Displacement	cu. in. (cc)	77.0 (1261)		91.5 (1498)	77.0 (1261)	91.5 (1498)
Air cleaner		4.5 inch Dual paper element		6.0 inch Dual paper element	4.5 inch Dual paper element	6.0 inch Dual paper element
Lubrication		Forced lubrication				
Cooling system		Pressurized radiator				
Radiator fan		Radial air flow				
Capacities						
Fuel tank	gal (ℓ)	7.1 (27.0)			8.3 (31.5)	
Cooling system	qts. (ℓ)	4.5 (4.3)				
Engine oil	qts. (ℓ)	4.2 (4.0)		5.1 (4.8)	4.2 (4.0)	5.1 (4.8)
Transmission case	gal (ℓ)	4.0 (15)				
Drive train						
Clutch		N / A				
Transmission		HST (3 ranges)				
Differential lock		Standard				
Final drive		Spur gear				
Brake		Multi-plate wet disc				
PTO						
Type		Independent				
Rear	rpm	540				
Mid	rpm	N/A	2500			
Hydraulics						
Type		Open center				
Pump		Dual pump				
Total pump output	gpm (ℓ/min.)	8.7 (33.1)				
Hydraulic outlet		Rear outlet				
3-point hitch		Category I				
Hydraulic control system		Position control valve				
Lift capacity at lift point	lbs. (kg)	2139 (970)				
24" behind LPIbs. (kg)		1676 (760)				
Steering		Hydraulic power steering				
Standard tire size						
Front	R1	7-12				
	R4	23 × 8.50-14 / 25 × 8.50-14			23 × 8.50-14	
	R14	23 × 8.50-12 / 25 × 8.50-14			23 × 8.50-12	
Rear	R1	12.4-16				
	R4	12.4-16 / 15-19.5			12.4-16	
	R14	14-17.5 / 15-19.5			14-17.5	
Traveling speeds (at rated engine rpm)						
Forward (R1)	mph (km/h)	0-11.2 (0-18.0)		0-13.6 (0-21.9)	0-11.2 (0-18.0)	0-13.6 (0-21.9)
Reverse (R1)	mph (km/h)	0-8.4 (0-13.5)		0-10.3 (0-16.5)	0-8.4 (0-13.5)	0-10.3 (0-16.5)
Dimensions (w/ R1 tires)						
Overall length (w/o 3P)	in. (mm)	101.2 (2570)			103.9 (2640)	
Overall width (min. tread)	in. (mm)	53.7 (1365)				
Overall height	in. (mm)	88.4 (2245)			84.6 (2150)	
Wheelbase	in. (mm)	65.6 (1666)				
Ground clearance	in. (mm)	14.6 (370)				
Turning radius with brake	feet (m)	6.9 (2.1)				
Weight	lbs. (kg)	1786 (810)		1918 (870)	2293 (1040)	2469 (1120)
Other Features		ROPS (SU) models Lower link stabilizer, Drawbar, Tool box, 12V power socket				
ROPS models		Cruise control (Multi-stage notch), Tilt-steering, Deluxe seat with arm rest, Parallel link with damper seat suspension, Lower link stabilizer, Drawbar, Tool box, 12V power socket				
CAB models		4-pillar integrated cabin, Cruise control (Multi-stage notch), Tilt-steering, Deluxe seat with arm rest, Parallel link seat suspension, Telescopic lower links, Lower link stabilizer, Drawbar, Front LED work light, Tool box, Cabin Interior Light, Speakers, 12V power socket, Front & Rear wiper with washer, Rear defogger, Rear hatch half lock				

*SAE J1995

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com

©2019 Kubota Corporation

