

SPECIFICATIONS

Model		RTV-X1130 Work Site		
Body color		Kubota Orange	RealTree®* AP Camouflage	
Engine	Make	KUBOTA D1105-E4-UV-2		
	Type	3-cylinders, 4-cycle, diesel, OHV		
	Displacement	cu.in (cc)	68.5 (1123)	
	Horsepower**	HP (kW)/rpm	24.8 (18.5)@3000	
Fuel tank capacity	U.S.gals (ℓ)	7.9 (30)		
Transmission		Variable hydro transmission (VHT-X)		
Max. Traveling speed	mph (km/h)	25 (40)		
Wheels, drive system		4WD		
Front differential lock		Limited-slip differential		
Rear differential lock		Foot operated differential lock		
Gear selection		Hi-Lo range forward, Neutral, Reverse		
Brakes	Front / Rear	Wet-disk brake		
	Parking brake	Rear wheel, hand operated		
Steering		Hydrostatic power steering		
Suspension	Front / Rear	Dual A-Arms independent suspension		
Dimensions	Length	in. (mm)	153 (3883)	
	Width	in. (mm)	63 (1605)	
	Height, overall	in. (mm)	80 (2025)	
	Front tread centers	in. (mm)	50.4 (1280) (HDWS & ATV)	
	Rear tread centers	in. (mm)	50.4 (1280) (HDWS & ATV)	
	Wheelbase	in. (mm)	98.2 (2495)	
	Ground clearance front/rear	in. (mm)	11.3 (285) / 9.4 (240)	
	Turning radius	ft. (m)	17.1 (5.2)	
Towing capacity	lbs. (kg)	1300 (590)		
Payload capacity	lbs. (kg)	1629 (739)		
Curb weight	lbs. (kg)	2340 (1060)		
Cargo bed	Width	in. (mm)	54.5 (1384)	
	Length	in. (mm)	72.3 (1837)	
	Depth	in. (mm)	11.6 (294)	
	Volume	cu. ft. (m ³)	26.1 (0.74)	
	Bed height (no load)	in. (mm)	35.4 (900)	
	Load capacity	lbs. (kg)	1212 (550)	
	ProKonvert	Standard (Foldable/Removable Side Panel with Tool-less Flatbed Conversion)		
Tires	Front	25×10×12 HDWS, 6-PLY		
		25×10×12 ATV, 6-PLY		
	Rear	25×10×12 HDWS, 6-PLY		
		25×10×12 ATV, 6-PLY		
Wheels		Steel		
Front Guard		Standard Front Guard	Premium Front Guard	
Hydraulic bed lift		Standard		
Spray-on Bed Liner		Standard		

*"Realtree®" is a registered trademark of Jordan Outdoor Enterprises, Ltd.

** SAE J1995

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: KubotaUSA.com



©2023 Kubota Corporation

Cat.No.2488-01-US Printed in Japan.D.REX.'23-SEP.