



For Earth, For Life
Kubota

W

COMMERCIAL GRADE WALK BEHIND MOWERS
WG14/WH15/WHF19

Introducing Kubota grade lawn care you can get behind.



COMMERCIAL WALK BEHIND MOWERS

W Series

Kubota Precision and Power

Kubota Commercial Walk Behind Mowers are tough enough for every kind of turf. Whether you want the compact versatility of a gear drive, or the increased speed and horsepower of a hydro drive, each mower is built to put precise cutting power in your hands.

These machines are perfectly tuned to optimize power and cutting width so that mower speed and horsepower increases with each deck size option. All Kubota Walk-Behind Mowers are built to out-perform with the following cutting-edge features:

- › Never let a flat tire stop you again with puncture-proof, semi-pneumatic tires (36" / 48" only).
- › Precision-ground double-sealed bearings and heavy-duty, maintenance-free spindles are engineered to prolong cutting performance and efficiency.
- › An electric clutch and operator-adjustable control forces make these mowers easy to operate on any turf.
- › Fatigue-reducing Dual-Lever Hydro Control System (48" / 52" only) allows for easy operation.
- › Take on properties from ¼ to 3 Acres with a resilient 5-Hour Run time.
- › Mow confidently with a 1 year warranty.
- › Manufactured in the USA.



WG14 / 36" Deck | **WH15 / 48" Deck** | **WHF19 / 52" Deck**



W Series	WG14 / 36" DECK	WH15 / 48" DECK	WHF19 / 52" DECK
Engine Type	Kawasaki FS481V	Kawasaki FS541V	Kawasaki FX600V
Horsepower (SAEJ1995) *	14.5 HP	15 HP	19 HP
Speed (MPH)	5.1	6.0	6.7
Transmission	5 Speed Peerless gear box	2-Hydro-Gear 10cc Variable Displacement Pumps with oil cooler and Parker Wheel Motors	2-Hydro-Gear 10cc Variable Displacement Pumps with oil cooler and Parker Wheel Motors
Deck Type	Fabricated Fixed	Fabricated Fixed with Wear band	Fabricated Float with Wear band
Deck	7 ga deck with 7 ga skirts	7 ga deck with 7 ga skirts	10 ga deck with 10ga top and 7ga skirts
Cutting Height	Adjustable 1.5-4.5"	Adjustable 1.38-4.63"	Adjustable 1.5-5"
Starter	Manual	Electric	Electric
Hand Controls	Pistol Grip	Dual Lever Hydro Control	Dual Lever Hydro Control
Spindle	Maintenance-free with 1" shaft	Maintenance-free with 1" shaft	Maintenance-free with 1" shaft
Bearings	Precision Ground double sealed bearings	Precision Ground double sealed bearings	Precision Ground double sealed bearings
Deck Drive	Warner Mag Stop 125 ft-lb electric clutch	Warner Mag Stop 125 ft-lb electric clutch	Warner Mag Stop 175 ft-lb electric clutch
Front Tires / Rear Tires	9 x 3.50-4 (No-Flat) / 13 x 5-6 4-ply	9 x 3.50-4 (No-Flat) / 16 x 7.50-8 4-ply	11 x 4.00-5 / 18 x 7.50-8 4-ply
Brake	Band Type	Hydrostatic Dynamic Braking	Hydrostatic Dynamic Braking
Weight	464 lb	660 lb	785 lb
Length / Height	78 in. Length / 40.3 in. Height	78 in. Length / 43 in. Height	80.7 in. Length / 43 in. Height

*These Kawasaki engines have been tested in accordance with SAEJ1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power rating of these engines were determined by using measurements according to SAEJ1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified, determined by using measurements according to SAEJ1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



Get your Walk Behind accessories:

Mulch Kits

- > 36" - WMK36
- > 48" - WMK48
- > 52" - WMK52

Discharge Plates

- > 36" - WBP36
- > 48" - WBP48
- > 52" - WBP52

Cold Start Kit (Hydro)

- > WCS00

Weight Kit (36")

- > WWK01

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

Kubota®

KUBOTA TRACTOR CORPORATION

Kubota Tractor Corporation, 3401 Del Amo Boulevard, Torrance CA 90503
Western Division: 1175 S. Guild Ave., Lodi, CA 95240 Tel (209) 334-9910
Central Division: 14855 FAA Boulevard, Fort Worth, Tx 76155 Tel (817) 571-0900
Northern Division: 6300 at One Kubota Way, Groveport, OH 43125 Tel (614) 835-1100
Southeast Division: 1025 Northbrook Parkway, Suwanee, GA 30024 Tel (770) 995-8855

Visit our web site at: www.kubota.com

