

For Earth, For Life Kubata

KUBOTA ZERO-TURN MOWER **ZD326H**

Kubota's Z300 Series is a premium choice among turf care professionals and large property owners alike. Featuring an impressive balance of comfort and performance, this machine was built to handle the rigors of professional landscaping.

The new ZD326H equipped with a larger displacement 26HP engine delivers more torque – now available with powerefficient 72" mower deck.

- 26HP Kubota Diesel Engine
- 6.0"-Deep, 72"-Wide Mower Deck
- Adjustable Front Axle (oscillating/rigid)
- Semi-Pneumatic (flat-free) Front Caster Tires
- Kubota HST Transmission
- Full-flat Operator Platform

- High-Back Deluxe Suspension Seat
- Adjustable Speed Control Levers
- Hands-Free Hydraulic Deck Lift
- Hands-Free Parking Brake
- Maintenance Lift





horsepower to run the newly designed 72" mower deck.

Optimally engineered to reduce friction, the ZD326H boasts a new version of Kubota's popular 72" Pro Commercial mower deck that balances cutting preformance and power savings. Fabricated with a 6" deep deck and advance baffle design, the welded mower deck efficiently provides a precision cut, while maintaining proper

Kubota HST Transmission

The ZD326H uses Kubota's heavy-duty integral twin hydrostatic transmission (HST) with a highly durable shaft drive and wet-type PTO clutch for reliable and smooth operation.

Specifications

Model			ZD326H
			ZD326HL-72
Engine	Model		Kubota D1105
	Туре		Diesel, liquid-cooled (3 cyl.)
	Max. horsepower (Gross)*		26 HP@3000 rpm
	Total displacement		68.5 cu.in. (1123 cc)
	Starting system		Key switch - super glow
Dimensions	Overall length		91.9 in. (2335 mm)
	Overall width	(w/ mower)	87.6 in. (2224 mm)
		(w/o mower)	57.5 in. (1460 mm)
	Overall height	(w/ ROPS upright)	75.4 in. (1915 mm)
		(w/ ROPS folded)	61.2 in. (1555 mm)
Wheel base	,		59.8 in. (1520 mm)
Tread	Front		42.1 in. (1070 mm)
	Rear		45.3 in. (1150 mm)
Tire size	Front		15 x 6.0-6 Non-Flat
	Rear		26 x 12.0-12
Weight (w/ mower) (without fuel)			1706 lbs. (774 kg)
Transmission system			2-HST w/ Gear
Speed control			2-hand lever
Travel speed			0-10.6 mph (0-17.0 km/h)
range	Reverse		0-5.3 mph (0-8.5 km/h)
Brake type			Wet multi disks, foot applied, released
РТО	Type		Shaft drive
	Clutch type		Hydraulic independent PTO clutch with wet multi disks
	PTO brake		Wet single disk
Mower deck	Model		RCK72P-326HZ
	Mower lift system		Hydraulic
	Mower deck type		Pro commercial – Fabricated deck
	Deck depth		6.0 in. (152 mm)
	Belt type		Multi-Belt
	Deck steel thickness		0.17 in. (4.2 mm)
	Anti-scalp roller		Swivel
	Cutting width of mower		72 in.
	Number of blades		3 blades
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments
	Mounting system of mower		Quick joint, parallel linkage
	Blade tip speed (max.)		18100 FPM
Engine stop system			Key stop
Fuel tank capacity			12.9 gals. (49 ltrs.)
Battery			51R (12 V, 70 min., CCA: 475A)
Alternator capacity			14 Amps@14 Volts
Fuel gauge			Electric
*SAE 11005			

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

For complete operational information, the operator's manual should be consulted.

©2013 Kubota Corporation



KUBOTA TRACTOR CORPORATION

Kubota Tractor Corporation, 3401 Del Amo Boulevard, Torrance CA 90503 Western Division: 1175 S. Guild Ave., Lodi, CA 95240 Tel (209) 334-9910 Central Division: 14855 FAA Boulevard, Fort Worth, TX 76155 Tel (817) 571-0900 Northern Division: 6300 at One Kubota Way, Groveport, OH 43125 Tel (614) 835-1100 Southeast Division: 1025 Northbrook Parkway, Suwanee, GA 30024 Tel (770) 995-8855

