

PAINT COLLECTION



Paint and coatings serve two primary purposes – to provide protection and decoration. Kubota® equipment is built to perform, and hard work inevitably leads to wear and tear. To keep Kubota® equipment shining its signature orange, look towards Orange City, IA, headquarters of Diamond Vogel®.

Kubota® paints were formulated to provide the best color and coverage to Kubota® equipment after the sale. Available in aerosols, quarts, and gallons, all coatings have been designed to factory standards. For over 15 years, these Kubota® genuine coatings have been manufactured by Diamond Vogel.

Diamond Vogel is a family owned, fourth generation, paint and coatings manufacturer and retailer. Originally founded in 1926 in Orange City Iowa, Midwest roots run deep. Growing from that foundation, the company currently operates seven different manufacturing facilities, and reaches even further through retail paint stores. What started off simply, making five gallons of paint at a time, Diamond Vogel has expanded to offer liquid and powder coating solutions to meet the needs of countless industries. From aerosol to architectural coatings, Industrial OEM applications to the line-stripe paint used on the nation’s roads, the applications are as varied as the technologies behind each coating system. Diamond Vogel knows that every product serves a different purpose, and there’s a perfect coating that will keep that product looking good and working great.



Kubota® Orange
Touch-up: 70000 - 73767
Spray: 70000 - 73710
Quart: 70000 - 73709
Gallon: 70000 - 73708
Application: Pre-1989 tractors



Kubota® Orange II
Touch-up: 70000 - 73768
Spray: 70000 - 73713
Quart: 70000 - 73712
Gallon: 70000 - 73711
Application: Post-1989 tractors




Kubota® Blue Enamel
Spray: 70000 - 00197
Quart: 70000 - 00199
Gallon: 70000 - 00200
Application: Pre-1989 tractors



KH Excavator Blue
Touch-up: 70000 - 73293
Spray: 70000 - 16681
Quart: 70000 - 16684
Application: KH Excavators



KX Excavator Blue
Spray: 70000 - 73736
Quart: 70000 - 73735
Application: KX Excavators



KX-3 Dark Blue
Spray: 70000 - 00188
Quart: 70000 - 02668
Gallon: 70000 - 02669
Application: KX-3 Excavators




K008 Excavator Blue
Spray: 70000 - 70474
Application: K008 Excavators



Dark Gray Enamel
Spray: 70000 - 00210
Quart: 70000 - 73358
Gallon: 70000 - 73296
Application: Post-1989 tractors



Gray Enamel
Spray: 70000 - 00191




Light Gray
Spray: 70000 - 73878




ROPS Gray Semi-Gloss
Spray: 70000 - 73806
Application: ROPS




Dark Gray Semi-Gloss
Spray: 70000 - 73352
Quart: 70000 - 73353
Gallon: 70000 - 73354




Silver Metallic
Spray: 70000 - 73766



Beige Enamel
Spray: 70000 - 00195
Application: Frame parts



Off-White Enamel
Spray: 70000 - 00211



White Enamel
Spray: 70000 - 73758



Gray Primer
Spray: 70000 - 00371
Quart: 70000 - 00372
Gallon: 70000 - 00373



Black Enamel
Spray: 77700-06430



Ebony Chrome
Spray: 77700 - 03528
Quart: 77700 - 03581



Excavator Black
Spray: 77700 - 01865
Quart: 77700 - 01866
Gallon: 77700 - 01867



Bright Silver Metallic
Spray: 77700 - 00465



Chassis Black (40)
Spray: 77700 - 09710



Black Texture Enamel
Spray: 77700 - 08685



RTV Black S/G Enamel (25)
Spray: 77700 - 08721

NOTE: Colors shown are produced as close as modern printing techniques permit, and are only approximate representations of the actual colors.

Kubota® Genuine Parts are designed and engineered to original factory specifications. For reliable, long-lasting performance of your Kubota® equipment, look for Kubota® Genuine Parts.

Kubota® Paints for use on the machinery after sale have been designed to factory standards for color and appearance with ease of application. The paints are available in aerosol cans, and in many colors, quarts and gallons.

DIRECTIONS FOR USE

This acrylic or alkyd (depending on color) system has been developed as a fast drying, versatile, finishing enamel for use on Kubota® equipment after the sale. It offers quick dry times, high gloss with good color and gloss retention.

SURFACE PREPARATION

Service expectancy of any coating system is primarily dependent upon good surface preparation. The substrate to be coated should be free of rust, mill scale, oil and other contaminants, including salt deposits. Smooth edges of scratches, chips, etc. with fine sand paper before spraying. A primer may be required for long-term protection.

REDUCTION

This coating system can be reduced with most aromatic solvents. Use Xylene as a fast reducer in normal and cool conditions and D-100 as a reducer in warmer conditions to prevent dusting. For air spray, reduce 20% to 30% by volume, and for airless or air-assisted airless, reduce up to 15%. NO REDUCTION IS NECESSARY FOR AEROSOL PACKAGING.

APPLICATION

Spray the reduced material or aerosol can in several light coats spaced 5 to 10 minutes apart. Do not try and cover completely in heavy coats or material will run and sag. Do not attempt to cover in one coat.

DRY TIME

The system will dry to touch in 30 minutes and can be recoated up to 8 hours. After 8 hours, apply a small test patch to check evidence of lifting before proceeding with a full recoat. Wait a minimum of 24 hours before buffing. Dry time is dependent upon temperature and humidity.

Typical Properties (varies by color):

Weight Solids:	48%
Volume Solids	36%
VOC's	4.40 lbs/gal (bulk)

Coverage: 580 ft²/gal at 1 mil

Solvent Content (typical):

Xylene
Aromatic 100
VM&P Naphtha
Mineral Spirits