

## B2301 - B2601



		COMPETITIVE COMPARISON				KUBOTA COMPARISON	
MODEL		Kubota B2301	Kubota B2601	John Deere 2025R	Mahindra Max 24 HST	Kubota B2650	
Engine	Engine Manufacturer	Kubota	Kubota	Yanmar	Mahindra	Kubota	
	Type	Diesel	Diesel	Diesel	Diesel	Diesel	
	Gross Engine (*SAE J1995)	HP (kw)	22 (16.4)*	25.5 (19.0)*	23.9 (17.8)	24.4 (18.2)	26.0 (19.4)*
	PTO Power (*OECD 2)	HP (kw)	17.5 (13.0)*	19.5 (14.5)*	18.0 (13.4)	19.5 (14.4)	19.5 (14.5)*
	Rated Engine Speed	rpm	2800	2800	3200	2500	2500
	Cylinders/Displacement	cu.in. (liters)	3 / 61.1 (1.001)	3 / 68.5 (1.123)	3 / 77.0 (1.267)	3 / 80.4 (1.318)	3 / 77.0 (1.261)
	Engine Torque @ rated speed	ft./lb. (N/m)	45.6 (6.30)	53.4 (7.38)	39.09 (53)	-	60.48 (8.3)
Fuel Tank Cap	gal. (l)	6.1 (23)	6.1 (23)	6.3 (23.8)	6.1 (23)	7.1 (27.0)	
Electrical	Battery Size	(CCA)	430	430	500	46AH	430
	Alternator	(12 volt, amp)	14.5 Amp dynamo	14.5 Amp dynamo	40	50	14.5 A - dynamo 60 A
Transmission	Transmission	Hydrostatic - 3 Range	Hydrostatic - 3 Range	Hydrostatic - 2 Range	Hydrostatic - 2 Range	Hydrostatic - 3 Range	
	Brakes	Multi Wet Disc	Multi Wet Disc	Wet Disc	Wet Disc	Multi Wet Disc	
	Steering	Power	Power	Power	Power	Power	
	Axle Capacity	Front, lb. (kg)	1323 (600)	1323 (600)	1349 (612)	-	2205 (1000)
	Rear, lb. (kg)	1764 (800)	1764 (800)	2425 (1100)	-	2205 (1000)	
Hydraulics	Remote Control Valves Available	3, Optional	3, Optional	2, Optional	1, Optional	2, Optional	
	Main Pump Flow	gpm (l/m)	4.7 (17.9)	4.7 (17.9)	3.5 (13.25)	4.6 (17.4)	5 (18.9)
	Total Flow GPM	gpm (l/m)	8.3 (31.4)	8.3 (31.4)	7.0 (26.5)	7.3 (27.6)	8.7 (33.1)
	Control Type	Position	Position	Position	Position	Position	
3-point Hitch	Type	Cat. I	Cat. I	Limited Cat. I	Cat. I	Cat. I	
	Lower Link Adjustment	Check Chains	Check Chains	Check chains	Check Chains	Telescopic	
	Lift Capacity (24-in. behind link arms)	lb. (kg)	1411 (640)	1411 (640)	882 (400)	-	1676 (760)
	Lift Capacity @ lift links ends	lb. (kg)	1808 (820)	1808 (820)	N/P	1400 (635)	2139 (970)
Power Take-Off (PTO)	Standard	Rear 540 / Mid 2500	Rear 540 / Mid 2500	Rear 540 / Mid 2100	Rear 540 / Mid 2000	Rear 540 / Mid 2500	
	Control	Independent	Independent	Independent	Live	Independent	
Dimensions	Wheelbase	in. (mm)	61.4 (1560)	61.4 (1560)	63 (1600)	-	65.6 (1666)
	Height	in. (mm)	83.9 (2130)	85.0 (2160)	-	81.5 (2070)	88.4 (2245)
	Front Tread	in. (mm)	32.7 (830)	33.5 (850)	37.5 (953)	-	36.8 (935)
	Min. ground clearance	in. (mm)	12.0 (305)	12.8 (325)	12.5 (316)	-	14.6 (370)
	Min. turning radius w/ brake	ft. (m)	6.9 (2.1)	6.9 (2.1)	8.7 (2.65)	7.2 (2.2)	6.9 (2.1)
	Weight	lbs. (kg)	1566 (710)	1632 (740)	1793 (813.5)	1693 (767.9)	1786 (810)
Standard Tires	Front	6-12 ; Ag	7-12 ; Ag	23x8.50-12 ; Industrial	20x8-10 ; Industrial	7.0-12 ; Ag	
	Rear	9.5-16 ; Ag	11.2-16 ; Ag	12-16.5 ; Industrial	27x12.5-15 ; Industrial	12.4-16 ; Ag	

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.