

L4701



COMPETITIVE COMPARISON						
FEATURES		Kubota L4701	John Deere3043D	Mahindra2645	KiotiDK4510	TYMT454
Engine	Engine Manufacturer	Kubota	Yanmar	N/P	Daedong	Yanmar
	Engine	V2403-CR-E4-LB1	3TNV86CT-KJPT	N/P	3F183T	4TNV88-CR
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	47.3 (35.2)	42.2 (31)	44 (33)	45 (33.6)	46 (34.3)
	PTO HP hp (kw)	Gear: 39.3 (29.3) HST: 37.8 (28.2)	36.3 (27.1)	36 (26.8)	41.6 (31)	Gear: 36.7 (27.4)HST: 34.6 (25.8)
	Rated Engine Speeds rpm	2600	2400	2600	2600	2800
	Aspiration	Natural	Turbocharged	Natural	Natural	Natural
	Displacement cu. in. (liters)	148.5 (2.434)	95.8 (1.57)	166.7 (2.732)	111.4 (1.826)	133.6 (2.189)
	Injection Type	Direct Injection	Direct Injection	Direct Injection	Indirect Injection	Direct Injection
	Cylinders	4	3	4	3	4
	Alternator Amps	40	55	90	N/P	70
	Fuel Tank	Fuel Tank Capacity gal. (liters)	13.5 (51.0)	9.7 (36.7)	9.0 (34.0)	11.9 (45)
Transmission	Transmission	8F/8R Synchronized Shuttle HST - 3 Range	Gear Transmission (8F-8R)	12F/12R Sychro Shuttle HST - 3 Range	8F/8R Synchronized Shuttle	16F/16R HST - 3 Range
	HST Cruise Control	Standard	N/A	N/P	N/P	Standard
	Clutch Type	Gear: Dry Type Single Stage HST: N/A	N/P	Dry Single Plate	Dry Single Plate	Dry Single Plate
	Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard	Standard
	Power Steering	Power	Power	Power	Power	Power

Kubota Tractor

L4701



COMPETITIVE COMPARISON						
FEATURES		Kubota L4701	John Deere3043D	Mahindra2645	KiotiDK4510	TYMT454
PTO	Type	Live-independent	Transmission Driven With Overrunning Clutch	Independent	Independent	Independent
	Speeds @ RPM	540 @ 2600	540 @ 2400	540 @ 2600	540 @ 2600	540 @ 2600
Hydraulic System-Three Point Hitch	Engagement Method	Electric - Hydraulic	Mechanical	N/P	N/P	Electric - Hydraulic
	Main Pump Flow gpm (l/m)	7.8 (29.4)	5.9 (22.4)	8.2 (31)	N/P	9.5 (36.1)
	Power Steering Flow gpm (l/m)	4.7 (17.9)	4.4 (16.8)	4.5 (17.1)	N/P	5.0 (19.0)
	Total Flow gpm (l/m)	12.5 (47.3)	10.3 (39.2)	12.7 (48.1)	N/P	14.5 (55.1)
	Control Type	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 3 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
	Stabilizers	Telescopic Stabilizer	Check Chains	Check Chains	N/P	Telescopic Stabilizer
Dimensions Weight	Lift Cap. 24" Behind Lift Pts., SAE lbs. (kg)	2320 (1053)	1670 (757.4)	N/P	2716 (1232)	2945 (1336)
	Wheelbase in. (mm)	Gear 2WD:72.8 (1850) Gear/HST 4WD: 72.6 (1845)	62 (157.4)	67.7 (1719)	71.3 (1810)	76.2 (1935)
	Height (top of Cab) in. (mm)	91.7 (2329)	N/P	94.4 (2400)	99.2 (2520)	102.1 (2594)
	Turning Radius w/Brake ft. (m)	Gear 2WD: 8.9 (2.7) Gear/HST 4WD: 8.5 (2.6)	5.3 (1.63)	N/A	N/A	11 (3.35)
	Turning Radius w/o Brake ft. (m)	Gear 2WD: 10.2 (3.1) Gear/HST 4WD: 11.5 (3.5)	N/P	N/A	8.6 (2.6)	12.53 (3.82)
	Weight lb. (kg)	Gear Drive 2WD - 3219 (1460) Gear Drive 4WD - 3296 (1495) HST 4WD - 3307 (1500)	2840 (1288)	3285 (1490)	3373 (1530)	3814 (1730)
Tires	Front / 4WD	Ag: 8.3 - 16 Turf: 27 x 10.50 - 15 Ind: 10 - 16.5	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14	Ag: 8.3 x 16 Ind: 10 - 16.5	Ag: 8 - 16 Turf: 29 - 12.5 - 15 Ind: 10 - 16.5	Ag: 9.5 x 16 - 6 Ind: 12 x 16.5 - 6
	Rear / 4WD	Ag: 14.9 - 24 Turf: 44 x 18 - 20 Ind: 17.5 - 24	Farm: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5	Ag: 12.4 x 24 Ind: 43 x 16 - 20	Ag: 13.6 - 24 Turf: 21.5 - 16.1 Ind: 14.9 - 24	Ag: 14.9 x 24 - 6 Ind: 16.9 x 24 - 8

N/A = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.

L3301



COMPETITIVE COMPARISON								
FEATURES	Kubota L3301	John Deere 3035D	John Deere 3032E	Mahindra1635	KiotiCK3510	Massey Ferguson735E	LSMT235E	
Engine	Engine Manufacturer	Kubota	Yanmar	Yanmar	N/P	Daedong	IH Shibaura	LS
	Engine	D1803-CR-E4	3TNV88C-KJPT	3TNV88C-NJT	N/P	3H-TMAA	NB43T-F	L3C19-D2
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	33.0 (24.6)*	34.7 (25.5)	31.2 (22.9)	36.2 (27)	34.9 (26)	34.9 (26)	35.0 (26.1)
	PTO HP hp (kw)	Gear 2WD: 27.7 (20.7)* HST 4WD: 26.2 (19.5)*	30.8 (23)	25 (18.6)	Gear: 27.6 (20.6) HST: 26 (19.4)	Gear: 31.8 (23.7) HST: 30.8 (22.9)	Gear: 29.7 (21.6) HST: 27.2 (20.3)	Gear: 29.7 (22.1) HST: 28.0 (20.9)
	Rated Engine Speeds rpm	2700	2400	2500	2500	2600	2600	2600
	Aspiration	Natural	Natural	Natural	Natural	Natural	Turbocharged	Natural
	Displacement cu. in. (liters)	111.4 (1.826)	100.2 (1.64)	100.2 (1.64)	125 (2.048)	111.4 (1.826)	91.3 (1.5)	114.7 (1.88)
	Injection Type	Direct Injection	Direct Injection	Direct Injection	Direct Injection	Direct Injection	Direct Injection	Indirect Injection
	Cylinders	3	3	3	3	3	3	3
	Alternator Amps	40	55	55	90	50	N/P	70
	Fuel Tank	Fuel Tank Capacity gal. (liters)	11.1 (42)	9.7 (36.7)	7.5 (28.5)	7.7 (29)	9.0 (34)	10.0 (38)
Transmission		Gear 2WD: Synchro Shuttle, 8F/8R HST 4WD: 3 Range	Syncho Shuttle, 8F/8R	HST: 2 Range	Gear: 8F/8R HST: 3 Range	Gear: 2nd and reverse are synchronized, 9F/3R HST: 3 Range	Gear: 8x8HST: 3 Range	Gear: Synchro Shuttle, 12F/12R HST: 3 Range
Transmission	HST Cruise Control	Optional	N/A	Optional	Optional	Standard	N/P	N/P
	Clutch Type	Dry Type Single Stage	N/P	N/P	Dry Single	Dry Dual Stage	N/P	N/P
	Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Multi Disc
Axle Steering	Differential Lock	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Steering	Power	Power	Power	Power	Power	Power	Power

L3301



COMPETITIVE COMPARISON								
FEATURES	Kubota L3301	John Deere 3035D	John Deere 3032E	Mahindra1635	KiotiCK3510	Massey Ferguson735E	LSMT235E	
PTD	Type	Gear 2WD: Transmission Driven with overrunning HST 4WD: Live with overrunning clutch	Transmission Driven With Overrunning Clutch	Independent	Gear: Independent/HST: Live	Live	Transmission driven	Independent
	Speeds @ RPM	540 @ 2700	540 @ 2400	540 @ 2500	540 @ 2500	540 @ 2600	540 @ 2600	540 @ 2600
Hydraulic System Three Point Hitch	Engagement Method	Mechanical	Mechanical	Electric	N/P	Mechanical	Mechanical	N/P
	Main Pump Flow gpm (l/m)	6.3 (23.9)	5.9 (22.4)	5.3 (17.2)	7.5 (28.5)	N/P	6.7 (25.5)	8.2 (31)
	Power Steering Flow gpm (l/m)	3.8 (14.5)	4.4 (16.8)	4.0 (15.0)	3.3 (12.2)	N/P	3.8 (14.4)	4.1 (15.5)
	Total Flow gpm (l/m)	10.1 (38.4)	10.3 (39.2)	9.3 (35.2)	10.8 (40.7)	11.7 (44.4)	10.5 (39.9)	12.3 (46.6)
	Control Type	Position	Position	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 3 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional
	Three Point Hitch Type	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
	Stabilizers	Check Chains (Telescopic Optional)	Check Chains	Check Chains	Telescoping Stabilizers	Check Chains	N/P	N/P
	Lift Cap. 24" Behind Lift Pts., SAE lbs. (kg)	1433 (650)	1670 (757.4)	1356 (615.1)	N/P	1631 (740)	1600 (725)	1808 (820)
	Wheelbase in. (mm)	63.3 (1610)	62 (1574)	60 (1525)	73 (1854)	65.7 (1670)	65.9 (1675)	69 (1753)
Dimensions Weight	Height (top of Cab) in. (mm)	91.7 (2330)	82.3 (2090)	82.3 (2090)	Gear: 90.2 (2290) HST: 88 (2235)	99.2 (2520)	97.6 (2480)	88 (2235)
	Turning Radius w/Brake ft. (m)	2WD: 7.9 (2.4) 4WD: 8.2 (2.5)	5.3 (1.63)	N/P	8.5 (2.6)	8 (2.4)	N/P	N/P
	Turning Radius w/o Brake ft. (m)	2WD: 8.9 (2.7) 4WD: 10.5 (3.2)	N/P	9.4 (2.9)	N/P	N/P	N/P	N/P
Tires	Weight lb. (kg)	Gear 2WD: 2557 (1160) Gear 4WD: 2734 (1240) HST 4WD: 2778 (1260)	2811 (1275)	2222 (1008)	Gear: 3098 (1400) HST: 3076 (1395) HST Cab: 3527 (1600)	Gear: 2679 (1215) HST: 2734 (1240)	Gear: 2734 (1240) HST: 2767 (1255)	Gear: 2866 (1300) HST: 2870 (1302)
	Front / 4WD	Ag: 7.2 - 16 Turf: 25 x 8.5 - 14 Ind: 27 x 8.5 - 15 AG/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14 Ag/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 x 16 Ind: 28 x 8.5 - 15 Turf: 25 x 8.5 - 14	Ag: 7 - 16 Turf: 28 x 8.5 - 15/6 Ind: 27 x 8.5 - 15	Ag: 7 - 16 Ind: 27 x 8.5 - 15	Ag: 7 - 14 Ind: 25 x 8.5 - 14 Turf: 25 x 8.5 - 14
Rear / 4WD	Ag: 11.2 - 24 Turf: 13.6 - 16 Ind: 15 - 19.5 AG/Ind Hybrid: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5 Ag/Ind Hybrid: 43 x 16 - 20	Ag: 11.2 x 24 Ind: 43 x 16 - 20 Turf: 13.6 x 16	Ag: 11.2 - 24 Turf: 41 x 14 - 20/4 Ind: 15 - 19.5	Ag: 11.2 - 24 Ind: 15 - 19.5	Ag: 11.2 - 24 Ind: 43 x 16 - 20 Turf: 41 x 14 - 20

NA = Not Available

NP = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.

L3901



FEATURES		COMPETITIVE COMPARISON						
		Kubota L3901	John Deere3043D	John Deere3038E	Mahindra1640	KiotiCK4010	Massey Ferguson 1740E	LSMT240E
Engine	Engine Manufacturer	Kubota	Yanmar	Yanmar	N/P	Daedong	IHI Shibaura	LS
	Engine	D1803-CR-E4-LB3	3TNV86CT-KJPT	3TNV86CT-NJT	N/P	3H-TMA	NB33T-F	L3C19-T
	EPA Emission Level	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Gross Engine HP, SAE J1995 hp (kw)	37.5 (28.0)	42.2 (31)	37.2 (27.4)	38.7 (28.9)	39.6 (29.5)	38.5 (28.7)	40 (29.8)
	PTO HP hp (kw)	Gear 2WD/4WD: 32.1 (23.9) HST: 30.6 (22.8)	36.3 (27.1)	30 (22.4)	Gear: 29.9 (22.3)HST: 27.7 (20.6)	Gear: 34.8 (25.9) HST: 33.3 (24.8)	32.7 (24.4)	34 (25.4)
	Rated Engine Speeds rpm	2700	2400	2500	2400	2600	2800	2600
	Aspiration	Natural	Turbocharged	Turbocharged	Natural	Natural	Turbocharged	Turbocharged
	Displacement cu. in. (liters)	111.4 (1.83)	95.8 (1.57)	95.7 (1.57)	166.7 (2.73)	111.4 (1.83)	91.3 (1.5)	114.7 (1.88)
	Injection Type	Direct Inject	High Pressure Common Rail, Direct Inject	High Pressure Common Rail, Direct Inject	Direct Injection	Common Rail, Direct Inject	In-Line Pump System, Indirect	Common Rail, Direct Inject
	Cylinders	3	3	3	4	3	3	3
Fuel Tank	Alternator Amps	40	55	55	90	50	N/P	70
	Fuel Tank Capacity gal. (liters)	11.1 (42.0)	9.7 (36.7)	7.5 (28.5)	7.7 (29)	9.0 (34)	10 (38)	7.4 (28)
Transmission	Transmission	Gear 2WD/4WD: Synchro Shuttle 8F/8R HST 4WD: 3 Range	Gear Transmission (8F-8R)	Hydrostatic - 2 Range	Gear: 8F / 8R HST: 3 Ranges	Gear: 2nd and reverse are synchronized, 9F/3R HST: 3 Range	D. Synchro Shuttle, 8F/8R HST:	Gear: F12/R12HST: 3 Range
	HST Clutch Control	Optional	N/A	Optional	N/P	Standard (HST only)	N/P	N/P
	Clutch Type	Dry Type Single Stage	N/P	N/P	Dry Single	Dry Dual Stage	N/P	N/P
	Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Internal Wet Disc	Wet, Multi-Disc
Axles Steering	Differential Lock	Standard	N/P	Standard	Standard	Standard	N/P	N/P
	Power Steering	Power	Power	Power	Power	Power	Power	Power

L3901




FEATURES		COMPETITIVE COMPARISON						
		Kubota L3901	John Deere3043D	John Deere3038E	Mahindra1640	KiotiCK4010	Massey Ferguson 1740E	LSMT240E
PTO	Type	Gear 2WD/4WD: Live-continuous running HST 4WD: Live with overrunning clutch	Transmission Driven With Overrunning Clutch	Independent	Gear: Independent HST: Live	Gear: Live HST: Live	Gear: Independent HST: Trans. Driven	Independent
	Speeds @ RPM	540 @ 2700	540 @ 2400	540 @ 2500	540 @ 2400	540 @ 2600	540 @ 2800	540 @ 2600
	Engagement Method	Live with overrunning clutch	Mechanical	Electric	N/P	Mechanical	N/P	N/P
Hydraulic System Three Point Hitch	Main Pump Flow gpm (l/m)	6.3 (23.9)	5.9 (22.4)	5.3 (20.2)	7.7 (29)	N/P	7.2 (27.3)	8.2 (31.04)
	Power Steering Flow gpm (l/m)	3.8 (14.5)	4.4 (16.8)	4 (15)	3.7 (12.8)	N/P	4.1 (15.4)	Gear: 4.1 (15.5)HST: 5.5 (20.8)
	Total Flow gpm (l/m)	10.1 (38.4)	10.3 (39.2)	9.3 (35.2)	11.4 (41.8)	11.7 (44.4)	11.3 (42.7)	Gear: 12.3 (46.6)HST: 13.7 (51.9)
	Control Type	Position	Position	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 3 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 3 Optional
	Three Point Hitch Type	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1	Cat. 1
Dimensions Weight	Stabilizers	Check Chains (Telescoping Optional)	Check Chains	Check Chains	Telescoping Stabilizers	Check Chains	N/P	N/P
	Lift Cap, 24" Behind Lift Pts., SAE lbs. (kg)	1432 (650)	1670 (757.4)	1356 (615.1)	N/P	1631 (740)	1600 (725)	2755 (1249)
	Wheelbase in. (mm)	63.3 (1610)	62 (157.4)	62.8 (159.5)	76.9 (1953)	65.7 (1670)	65.9 (1675)	69
	Height (top of Cab) in. (mm)	91.7 (2330)	N/P	N/P	Gear: 91.5 (2324) HST: 89.4 (2270)	99.2 (2520)	97.6 (2480)	88
	Turning Radius w/Brake ft. (m)	2WD: 7.9 (2.4) 4WD: 6.2 (2.5)	5.3 (1.63)	N/P	9.2 (2.8)	8 (2.4)	N/P	N/P
Tires	Turning Radius w/o Brake ft. (m)	2WD: 8.9 (2.7) 4WD: 10.5 (3.2)	N/P	9.4 (2.9)	N/P	N/P	N/P	N/P
	Weight lb. (kg)	F: 2590 (1175) DT: 2767 (1255) HST: 2778 (1260)	2840 (1288)	2222 (1008)	Gear: 3186 (1448) HST: 3175 (1440) HST Cab: 3627 (1645)	Manual: 2679 (1215) HST: 2734 (1240)	Gear: 2756 (1250) HST: 2789 (1265)	Gear: 2881 (1307) HST: 2884 (1308)
Tires	Front / 4WD	Ag: 7 - 16 Turf: 25 x 8.5 - 14 Ind: 27 x 8.50 - 15 Ag/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14 Ag/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 x 16 Ind: 28 x 8.5 - 15 Turf: 27 x 10.5 - 15	Ag: 7 - 16 Turf: 28 x 8.5 - 15/16 Ind: 27 x 8.5 - 15	Ag: 7 - 16 Ind: 27 x 8.5 - 15	Ag: 7 - 14 Ind: 25 x 8.5 - 14 Turf: 25 x 8.5 - 14
	Rear / 4WD	Ag: 11.2 - 24 Turf: 13.6 - 16 Ind: 15 - 19.5 Ag/Ind Hybrid: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5 Ag/Ind Hybrid: 43 x 16 - 20	Ag: 11.2 x 24 Ind: 43 x 16 - 20 Turf: 41 x 14 - 20	Ag: 11.2 - 24 Turf: 41 x 14 - 20/4 Ind: 15 - 19.5	Ag: 11.2 - 24 Ind: 15 - 19.5	Ag: 11.2 - 24 Ind: 43 x 16 - 20 Turf: 41 x 14 - 20

NA = Not Available
N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.


Kubota reserves the right to change the specifications relating to its products without notice.

Kubota Tractor
L2501



COMPETITIVE COMPARISON								
FEATURES	Kubota L2501	John Deere 3025D	John Deere 3025E	Mahindra 1626	Kiotti CK2610	Massey Ferguson 1726E	LSMT225E	
Engine	Engine Manufacturer	Kubota	Yanmar	Yanmar	N/P	Daedong-Kiotti	Shibaura	Mitsubishi
	Engine	D1703-M	3TNV88F-EPJPT	3TNV88F-EPJT2	N/P	3A165LWM-U	N843T-F	S3L1
	EPA Emission Level	Tier 4	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final
	Gross Engine HP, SAE J1995 hp (kw)	24.8 (18.5)	24.4 (18.2)	24.7 (18.2)	25.9 (19.1)	24.5 (18.2)	24 (17.9)	24.4 (18.2)
	PTO HP hp (kw)	Gear 2WD/4WD: 20.5 (15.3) HST 4WD: 19.0 (14.2)	20 (14.9)	19.4 (14.4)	Gear: 21.5 (16) HST: 19 (14.2)	Gear: 21.7 (16.2) HST: 21.5 (16)	Gear: 20.4 (15.2) HST: 19.2 (14.3)	Gear: 19.5 (14.3) HST: 18.5 (12.8)
	Rated Engine Speeds rpm	2200	2400	2400	2500	2600	2600	2500
	Aspiration	Natural	Natural	Natural	Natural	Natural	Turbocharged	Natural
	Displacement cu. in. (liters)	100.47 (1.647)	100.2 (1.64)	100.2 (1.64)	80.4 (1.318)	100.5 (1.647)	N/P	80.4 (1.318)
	Injection Type	Direct Injection	Direct Injection	Direct Injection	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3	3	3
Fuel Tank	Alternator Amps	40	55	55	50	50	65	50
	Fuel Tank Capacity gal. (liters)	10.0 (38.0)	9.7 (36.7)	7.5 (28.5)	7.1 (27)	9.0 (34)	N/P	6.6 (25)
Transmission	Transmission	Gear 2WD/4WD: 8F/4R HST 4WD: 3 Range	8F/8R Synchronesh Shuttle Shift Gear Transmission	HST: 2 Range	8F/8R HST: 3 Range	9F/3R Manual Transmission HST: 3 Range	9F/3R Manual Transmission HST: 3 Range	Gear: 12F/12R HST: 3 Range
	HST Cruise Control	Gear 2WD/4WD: N/A HST 4WD: Optional	N/A	Optional	N/P	Optional (HST only)	N/P	N/P
	Clutch Type	Dry Type Single Stage	N/P	N/P	Dry Single	Dry Dual Stage	Dry Type	N/P
	Brakes	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	Steering	Power	Power	Power	Power	Power	Power	Power

Kubota Tractor
L2501



COMPETITIVE COMPARISON								
FEATURES	Kubota L2501	John Deere 3025D	John Deere 3025E	Mahindra 1626	Kiotti CK2610	Massey Ferguson 1726E	LSMT225E	
PTO	Type	Gear 2WD/4WD: Transmission driven with overrunning clutch HST 4WD: Live-continuous running	Transmission Driven With Overrunning Clutch	Independent	Live	Live	Transmission driven	Independent
	Speeds @ RPM	540 @ 2200	540 @ 2400	540 @ 2400	540 @ 2500	540 @ 2600	540 @ 2600	540 @ 2500
Hydraulic System Three Point Hitch	Engagement Method	Mechanical	Mechanical	Electronic	Mechanical	Mechanical	Mechanical	N/P
	Main Pump Flow gpm (l/m)	5.15 (19.5)	5.1 (19.2)	5.3 (20.2)	7.5 (28.5)	N/P	6.7 (25.5)	7.9 (29.9)
	Power Steering Flow gpm (l/m)	3.13 (11.8)	3.8 (14.4)	4.0 (15)	3.3 (12.2)	N/P	3.8 (14.4)	4.6 (17.4)
	Total Flow gpm (l/m)	8.26 (31.3)	8.9 (33.6)	9.3 (35.2)	10.8 (40.7)	11.7 (44.4)	10.5 (39.9)	12.5 (47.3)
	Control Type	Position	Position	Position	Position	Position	Position	Position
	Hydraulic Remote Valves	Up to 3 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional	Up to 2 Optional
	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
Dimensions Weight	Stabilizers	Check Chains (Telescopic optional)	Check Chains	Check Chains	Telescoping	Check Chains (Telescopic optional)	Check Chains	Check Chains
	Lift Cap. 24" Behind Lft Pts., SAE lbs. (kg)	1389 (630)	1670 (757.4)	1356 (615)	N/P	1631 (740)	1600 (725)	1433 (650)
	Wheelbase in. (mm)	63.3 (1610)	62 (1574)	62.8 (1595)	67.3 (1709)	65.7 (1669)	65.9 (1674)	66 (1676)
	Height (top of ROPS) in. (mm)	91.3 (2319)	82.3 (209)	82.3 (209)	81.5 (2070)	99.2 (2520)	97.6 (2470)	88 (2235)
	Turning Radius w/Brake ft. (m)	2WD: 7.9 (2.4) 4WD: 8.2 (2.5)	5.3 (1.63)	N/P	7.9 (2.4)	8.0 (2.4)	N/P	N/P
Tires	Turning Radius w/o Brake ft. (m)	2WD: 8.9 (2.7) 4WD: 10.5 (3.2)	N/P	9.4 (2.9)	N/P	N/P	N/P	N/P
	Weight lb. (kg)	Gear 2WD: 2425 (1100) Gear 4WD: 2601 (1180) HST 4WD: 2623 (1190)	2778 (1260)	2222 (1008)	Gear: 2437 (1105) HST: 2459 (1115)	Gear: 2646 (1200) HST: 2701 (1225)	2667 (1210)	Gear: 1785 (810) HST: 1609 (730)
Tires	Front / 4WD	Ag: 7.2 - 16 Turf: 25 x 8.5 - 14 Ind: 27 x 8.50 - 15 AG/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14	Ag: 7 - 14 Turf: 27 x 8.5 - 15 Ind: 25 x 8.5 - 14 Ag/Ind Hybrid: 27 x 8.5 - 15	Ag: 7 x 16 Ind: 27 x 8.5-14 Turf: 25 x 8.5-14	Ag: 7 - 16 Turf: 28 x 8.5 - 15/6 Ind: 27 x 8.5 - 15	Ag: 7 - 16 Ind: 27 x 8.50 - 15	Ag: 7 - 14 Ind: 25 x 8.5 - 14 Turf: 25 x 8.5 - 14
	Rear / 4WD	Ag: 11.2 - 24 Turf: 13.6 - 16 Ind: 15 - 19.5 AG/Ind Hybrid: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5	Ag: 11.2 - 24 Turf: 41 x 14 - 20 Ind: 15 - 19.5 Ag/Ind Hybrid: 43 x 16 - 20	Ag: 11.2 x 24 Ind: 15 x 19.5 Turf: 13.6 x 16	Ag: 11.2 - 24 Turf: 41 x 14 - 20/4 Ind: 15 - 19.5	Ag: 11.2 x 24 Ind: 15 x 19.5	Ag: 11.2 - 24 Ind: 43 x 16 - 20 Turf: 41 x 14 - 20

N/A = Not Available
 N/P = Not Published
 This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.
 Kubota reserves the right to change the specifications relating to its products without notice.