



		COMPETITIVE COMPARISON					
MODEL		Kubota L2501		John Deere 3025E	Mahindra 1526		
		Gear 2WD/4WD	HST 4WD	HST 4WD	Gear 4WD	HST	
Engine	Engine Manufacture	Kubota		Yanmar	N/P		
	Emissions	Tier 4		Tier 4	Tier 4		
	Gross Engine (*SAE J1995)	HP (kw)	24.8 (18.5)*		24.7 (18.4)	25.6 (19.0)	
	Engine Net Power (*SAE J1349)	HP (kw)	23.9 (17.8)*		N/P	N/P	
	PTO Power (*OECD 2)	HP (kw)	20.5 (15.3)*	19.0 (14.2)*	19.4 (14.4)	19.0 (14.2)	18.5 (13.8)
	No. of Cylinders	3		3	3		
	Total Displacement	cu.in. (cc)	100.47 (1647)		100.2 (1642)	80.4 (1318)	
	Rated Engine Speed	RPM	2200		2400	2500	
	Maximum Torque	lb-ft (Nm)	70.2 (95.2)		64.8 (87.8)	N/P	
	Fuel Tank Capacity	gal. (l)	10.0 (38.0)		6.2 (23.5)	7.1 (27)	
	Air Cleaner	Single Element, Dual Optional		Dual Element	N/P		
Drive train	Transmission	Synchro Shuttle, 8F/4R	HST - 3 Range	HST - 2 Range	8F/8F	HST - 3 Range	
	Brake	Wet Disc		Wet Disc	Wet Disc		
	PTO	Transmission Driven with overrunning clutch	Live continuous running	Independent	Independent		
	PTO Speed @ RPM	540 @ 1910	540 @ 2106	540 @ 2500 RPM	540 @ 2376		
	Mid PTO	N/A		N/A	Optional		
	Cruise Control	N/A	Optional	Optional	N/A		
	Front Axle Capacity	lbs. (kg)	2865 (1300)		1760 (798)	N/P	
	Rear Axle Capacity	lbs. (kg)	2865 (1300)		2640 (1197)	N/P	
	Power Steering	Integral Power Steering		Power Steering	Hydrostatic Power Steering		
Standard Tires	Front	2WD: 5-15 // 4WD: 7.2-16 ; Ag		7-14; Ag	7-16 ; Ag		
	Rear	11.2-24 ; Ag		11.2-24; Ag	11.2-24 ; Ag		
Hydraulic System	Implement Pump capacity	gpm (l/m)	5.15 (19.5)	5.3 (20.2)	7.5 (28.5)		
	Power Steering Pump	gpm (l/m)	3.11 (11.8)	4 (15)	3.3 (12.2)		
	Total Flow	gpm (l/m)	8.26 (31.3)	9.3 (35.2)	10.8 (40.9)		
	Category Hitch	Cat. I		Cat. 1	Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point	lb (kg)	1389 (630)		1356 (615.1)	2646 (1200)	
	Rear remote hydraulic valves	Up to 3 rear remotes		Up to 2 rear remotes	Up to 1 rear remote		
	Telescoping Lower Link ends	N/A		Optional	N/P		
Stabilizers	Telescopic, optional		Turnbuckle	Telescopic			
Dimensions	Wheelbase	in. (mm)	63.3 (1610)		60 (1524)	N/P	
	Tread	Front: in. (mm)	2WD: 41.3 (1060) // 4WD: 43.1 (1095)		42.9 (1089)	N/P	
		Rear: in. (mm)	43.8 (1115) - 47.1 (1195) - 50.8 (1290)		42.8 (1086)	N/P	
	Overall Length w/o 3-Point Hitch	in. (mm)	106.3 (2700)		N/P	121.3 (3080)	
	Overall Height	in. (mm)	91.3 (2319)		82.3 (2090)	81.5 (2069)	
	Overall Width (min. tread)	in. (mm)	55.1 (1400)		N/P	63.0 (1600)	
	Min. ground clearance	in. (mm)	2WD: 13.6 (345) // 4WD: 13.4 (340)		13 (330.2)	N/P	
	Min. turning radius w/ brake	ft. (m)	2WD: 7.9 (2.4) // 4WD: 8.2 (2.5)		9.2 (2.8)	7.9 (2.4)	
Weight	lbs. (kg)	F: 2425 (1100) DT: 2601 (1180)	2623 (1190)	2222 (1007.9)	2437 (1105)	2459 (1115)	

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



COMPETITIVE COMPARISON

MODEL		Kubota L3301		John Deere 3032E	Mahindra 1533		
		Gear 2WD/4WD	HST 4WD	HST 4WD	Gear 4WD	HST	
Engine	Engine manufacture	Kubota		Yanmar	Mitsubishi		
	Emissions	Tier 4		Tier 4	Tier 4		
	Gross Engine (*SAE J1995) HP (kw)	33.0 (24.6)*		31.1 (22.9)	34.5 (25.7)		
	Engine net power (*SAE J1349) HP (kw)	31.4 (23.4)*		N/P	N/P		
	PTO power (*OECD 2) HP (kw)	27.7 (20.7)*	26.2 (19.5)*	25.0 (18.6)	25.2 (18.8)	24.7 (18.4)	
	No. of cylinders	3		3	4		
	Total displacement cu.in. (cc)	111.4 (1826)		100.2 (1640)	166.7 (2732)		
	Rated revolution	2700		2500	2400		
	Fuel tank capacity gal. (l)	11.1 (42)		6.2 (23.5)	7.7 (29.1)		
	Air cleaner	Single Element, Dual Optional		Dual Element	N/P		
Drive train	Transmission	Synchro Shuttle, 8F/8R	HST - 3 Range	HST - 2 Range	Synchro Shuttle, 8F/8R	HST - 3 Range	
	Brake	Multiple Wet, Disc		Wet Disc	Wet Disc		
	PTO	Transmission Driven with overrunning	Live with overrunning clutch	Independent	Independent		
	PTO Speed @ RPM	540 @ 2430	540 @ 2580	540 @ 2500 RPM	540 @ 2376		
	Mid PTO	N/A		N/A	Optional		
	Cruise Control	N/A	Optional	Optional	Optional		
	Front Axle Capacity lb. (kg)	2865 (1300)		1760 (798)	N/P		
	Rear Axle Capacity lb. (kg)	2865 (1300)		2640 (1197)	N/P		
	Power steering	Integral Power Steering		Hydrostatic Power Steering	Hydrostatic Power Steering		
Standard Tires	Front	2WD: 5.00-15 // 4WD: 7.2-16 ; Ag		7 - 14 ; Ag	7 - 14		
	Rear	11.2-24 ; Ag		11.2 - 24 ; Ag	11.2 - 24		
Hydraulic System	Implement Pump capacity gpm (l/m)	6.78 (25.7)		5.3 (20.2)	7.7 (29.1)		
	Power steering pump gpm (l/m)	4.12 (15.6)		4.0 (15)	3.4 (12.9)		
	Total flow gpm (l/m)	10.9 (41.3)		9.3 (35.2)	11.1 (42.0)		
	Category Hitch	Cat. I		Cat. I	Cat. I		
	3-Point Hitch lift capacity @ 24" behind lift point lb (kg)	1433 (650)		1356 (615)	N/P		
	Rear remote hydraulic valves	Up to 3 rear remotes		Up to 2 rear remotes	Up to 1 rear remote		
	Telescoping Lower Link ends	N/A		Check Chains	N/A		
Stabilizers	Telescopic, optional		N/P	Telescopic			
Dimensions	Wheelbase in. (mm)	63.3 (1610)		60.0 (152.4)	N/P		
	Tread	Front in. (mm)	2WD: 41.3 (1050) // 4WD: 43.1 (1095)		42.9 (1089)	N/P	
		Rear in. (mm)	43.8 (1115) - 47.1 (1195) - 50.8 (1290)		42.8 (1086)	N/P	
	Overall Length w/o 3-Point Hitch in. (mm)	2WD: 110.6 (2810) // 4WD: 107.9 (2740)		N/P	127.8 (3246)		
	Overall Height in. (mm)	91.7 (2330)		82.3 (2090)	90.2 (2291)		
	Overall Width (min. tread) in. (mm)	55.1 (1400)		63 (1600)	63 (1600)		
	Min. ground clearance in. (mm)	2WD: 13.6 (345) // 4WD: 13.4 (340)		N/P	13.0 (330)		
	Min. turning radius w/ brake ft. (m)	2WD: 7.9 (2.4) // 4WD: 8.2 (2.5)		9.2 (2.8)	9.2 (2.8)		
Weight lbs. (kg)	F: 2557 (1160) DT: 2734 (1240)	HST: 2778 (1260)	2222 (1008)	3175 (1440)	3164 (1435)		

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/kW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



COMPETITIVE COMPARISON

MODEL	Kubota L3901		John Deere 3038E	Mahindra 1538		Mahindra 2538		
	Gear 2WD/4WD	HST 4WD	HST 4WD	Gear 4WD	HST	HST		
Engine	Engine manufacture	Kubota		Yanmar	Mitsubishi			
	Emissions	Tier 4		Tier 4	Tier 4			
	Gross Engine (*SAE J1995) HP (kw)	37.5 (28.0)*		3037.3 (27.4)	38.7 (28.8)		37.4 (27.5)	
	Engine net power (*SAE J1349) HP (kw)	36.3 (27.1)*		N/P	N/P		N/P	
	PTO power (*OECD 2) HP (kw)	32.1 (23.9)*	30.6 (22.8)*	30.0 (22.4)	29.9 (22.3)	27.7 (20.6)	31.0 (23.1)	
	No. of cylinders	3		3.0	4		4	
	Total displacement cu.in. (cc)	111.4 (1826)		95.7 (1570)	166.7 (2732)		167.0 (2732)	
	Rated revolution	2700		2500	2400		2400	
	Fuel tank capacity gal. (l)	11.1 (42.0)		6.2 (23.5)	7.7 (29.1)		9.0 (34.0)	
	Air cleaner	Single Element, Dual Optional		Dual Element	N/P		N/P	
Drive train	Transmission	Synchro Shuttle 8F/8R	HST - 3 Range	HST - 2 Range	Synchro Shuttle, 8F/8R	HST - 3 Range	HST - 3 Range	
	Brake	Wet Disc		Wet Disc	Wet Disc		Wet Disc	
	PTO	Live-continuous running	Live with overrunning clutch	Independent	Independent		Independent	
	PTO Speed @ RPM	540 @ 2425	540 @ 2580	540 @ 2500	540 @ 2376		540 @ 2400	
	Mid PTO	N/A		N/A	Optional		N/P	
	Cruise Control	N/A	Optional	Optional	Optional		Optional	
	Front Axle Capacity lb. (kg)	2865 (1300)		1760 (798)	N/P		N/P	
	Rear Axle Capacity lb. (kg)	2865 (1300)		2460 (1197)	N/P		N/P	
	Power steering	Integral Power Steering		Hydrostatic Power Steering	Hydrostatic Power Steering		Hydrostatic Power Steering	
Standard Tires	Front	2WD: 5.00-15 // 4WD: 7.2-16		7 - 14 ; Ag	7 - 14 ; Ag		7-16 ; Ag	
	Rear	11.2-24		11.2 - 24 ; Ag	11.2 - 24 ; Ag		11.2-24 ; Ag	
Hydraulic System	Implement Pump capacity gpm (l/m)	6.78 (25.7)		5.3 (20.2)	7.7 (29.1)		7.6 (28.8)	
	Power steering pump gpm (l/m)	4.12 (15.6)		4.0 (15)	3.4 (12.9)		4.1 (15.5)	
	Total flow gpm (l/m)	10.9 (41.3)		9.3 (35.2)	11.1 (42.0)		11.7 (44.3)	
	Category Hitch	Cat. I		Cat. I	Cat. I		Cat. I	
	3-Point Hitch lift capacity @ 24" behind lift point lb (kg)	1433 (650)		1356 (615)	N/P		N/P	
	Rear remote hydraulic valves	Up to 3 rear remotes		Up to 2 rear remotes	Up to 1 rear remote		Up to 1 rear remote	
	Telescoping Lower Link ends	N/A		Check Chains	N/A		Check Chains	
Stabilizers	Telescopic, optional		N/P	Telescopic		N/P		
Dimensions	Wheelbase in. (mm)	63.3 (1610)		60.0 (152.4)	N/P		N/P	
	Tread	Front in. (mm)	2WD: 41.3 (1050) // 4WD: 43.1 (1095)		42.9 (1089)	N/P		N/P
		Rear in. (mm)	43.8 (1115) - 47.1 (1195) - 50.8 (1290)		42.8 (1086)	N/P		N/P
	Overall Length w/o 3-Point Hitch in. (mm)	2WD: 110.6 (2810) // 4WD: 107.9 (2740)		N/P	127.8 (3246)		119.3 (3030)	
	Overall Height in. (mm)	91.7 (2330)		82.3 (2090)	90.2 (2291)		94.4 (2400)	
	Overall Width (min. tread) in. (mm)	55.1 (1400)		N/P	62 (1575)		59.8 (1520)	
	Min. ground clearance in. (mm)	2WD: 13.6 (345) // 4WD: 13.4 (340)		13.0 (330)	N/P		N/P	
	Min. turning radius w/ brake ft. (m)	2WD: 7.9 (2.4) // 4WD: 8.2 (2.5)		9.2 (2.8)	9.2 (2.8)		7.87 (2.4)	
Weight lbs. (kg)	F: 2590 (1175) DT: 2767 (1255)	HST: 2778 (1260)	2222 (1008)	3186 (1445)	3175 (1440)	3130 (1419.7)		

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

COMPETITIVE COMPARISON

MODEL		Kubota L4701	MAHINDRA 2545	
		Gear 4WD	Gear 4WD	
Engine	Engine Manufacturer	Kubota	MAHINDRA	
	Emissions	Tier 4	Tier 4	
	Gross Engine (*SAE J1995)	HP (kw)	47.3 (35.2)*	44 (33)
	Engine Net Power (*SAE J1349)	HP (kw)	44.8 (33.4)*	N/P
	PTO Power (*OECD 2)	HP (kw)	39.3 (29.3)*	39 (29.1)
	No. of Cylinders		4	4
	Total Displacement	cu.in. (cc)	148.5 (2434)	166.7 (2732)
	Rated revolution	RPM	2600	2600
	Fuel Tank Capacity	gal. (l)	13.5 (51.0)	9.0 (34.0)
	Air Cleaner		Single Element, Dual Optional	N/P
Drive train	Transmission	Synchro Shuttle 8F/8R	Sychro Shuttle 12F/12R	
	Brake	Wet Disc	Wet Disc	
	PTO	Live Independent	Independent	
	PTO Speed @ RPM	540 @ 2475	540 @ 2650	
	Mid PTO	N/A	N/A	
	Front Axle Capacity	lbs. (kg)	3300 (1500)	N/P
	Rear Axle Capacity	lbs. (kg)	3300 (1500)	N/P
	Power Steering		Hydrostatic Power Steering	Hydrostatic Power Steering
Standard Tires	Front	8.3-16	N/P	
	Rear	14.9-24	N/P	
Hydraulic System	Implement Pump capacity	gpm (l/m)	8.37 (31.7)	8.2 (31.0)
	Power Steering Pump	gpm (l/m)	5.07 (19.2)	4.1 (15.6)
	Total Flow	gpm (l/m)	13.44 (50.9)	12.3 (46.6)
	Category Hitch		Cat. I	Cat. 1
	3-Point Hitch lift capacity @ 24" behind lift point	lb (kg)	2320 (1053)	2646 (1200)
	Rear remote hydraulic valves		Up to 3 rear remotes	1 Optional
	Telescoping Lower Link ends		N/A	Check Chains
	Stabilizers		Telescopic	N/P
Dimensions	Wheelbase	in. (mm)	72.6 (1845)	N/P
	Tread	Front: in. (mm)	45.5 (1155)	N/P
		Rear: in. (mm)	46.5 (1180) - 47.2 (1200) - 51.2 (1300) - 57.1 (1450) - 60.8 (1545)	N/P
	Overall Length w/o 3-Point Hitch	in. (mm)	119.5 (3035)	119.3 (3030)
	Overall Height	in. (mm)	91.7 (2330)	94.4 (2400)
	Overall Width (min. tread)	in. (mm)	62.4 (1585)	63.2 (1605)
	Min. ground clearance	in. (mm)	15.2 (385)	N/P
	Min. turning radius w/ brake	ft. (m)	8.5 (2.6)	7.87 (2.4)
Weight	lbs. (kg)	3296 (1495)	3285 (1490)	

N/A = Not Available N/P = Not Published

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.