



COMPETITIVE COMPARISON			
FEATURES		Kubota LX3310	John Deere 2032R
Engine	Engine Manufacturer	Kubota	Yanmar
	Engine	ROPS: V1505-CR-TE5-D36R1 CAB: V1505-CR-TE5-D36Q1	3TNV88C-NJT
	Gross Engine HP, SAE J1995 hp (kw)	30.8 (23.0)	31.2 (23.3)
	PTO HP hp (kw)	27.0 (20.1)	24.2 (18.0)
	Rated Engine Speeds rpm	2500	2500
	Aspiration	Natural	Natural
	Displacement cu. in. (liters)	91.5 (1.498)	100.2 (1.642)
	Injection Type	Indirect	Direct
	Cylinders	4	3
Fuel Tank	Alternator Amps	ROPS: 60CAB: 75	85
	Fuel Tank Capacity gal. (liters)	ROPS: 7.1 (27.0) CAB: 8.3 (31.5)	8.5 (32.0)
Transmission	Transmission	HST: 3 Range	HST: 2 Range
	HST Cruise Control	Standard	Standard
	Brakes	Multi-Plate Wet Disc	Wet Disc
Axles Steering	Differential Lock	Standard	Mechanical
	Steering	Power	Power



COMPETITIVE COMPARISON			
FEATURES		Kubota LX3310	John Deere 2032R
PTO	Type	Independent	Independent
	Speeds @ RPM	540 @ 2500	540 @ 2500
	Clutch type	Hydraulic	Hydraulic
	Mid PTO	Standard	Standard
Hydraulic System	Hydraulic Remote Valves	2 Optional	3 Optional
	Main Pump Flow gpm (l/m)	5.0 (18.9)	5.3 (20.2)
	Power Steering Flow gpm (l/m)	3.7 (14.2)	4.0 (15.0)
	Total Flow gpm (l/m)	8.7 (33.1)	9.3 (35.2)
	Control Type	Position	Position
Three Point Hitch	Three Point Hitch Type	Cat. I	Cat. I
	Telescopic Lower Link Ends	ROPS: Optional CAB: Standard	N/A
	Stabilizers	Telescopic	Check Chains
	Lift Capacity @ the pin, SAE lbs. (kg)	2139 (970)	N/P
	Lift Capacity @ 24" Behind, SAE lbs. (kg)	1676 (760)	1356 (615)
Dimensions Weight	Wheelbase in. (mm)	65.6 (1666)	67.9 (1725)
	Height in. (mm)	ROPS: 88.4 (2245) CAB: 84.6 (2150)	N/P
	Ground Clearance in. (mm)	14.6 (370)	13 (330)
	Turning Radius w/ Brake ft.(m)	6.9 (2.1)	9 (2.75)
	Turning Radius w/o Brake ft.(m)	8.5 (2.6)	9.84 (3.0)
	Weight lb. (kg)	ROPS: 1918 (870) CAB: 2469 (1120)	2436 (1105)
Tires	Front / 4WD	Ag: 7-12 Ind: 23x8.50-14 / 25x8.50-14 (ROPS Only) Ag/Ind Hybrid: 23x8.50-12 / 25x8.50-14 (ROPS Only)	Ag: 7.00-12 Turf: 23x8.50-14 Ind: 23x8.50-14 Turf Radial: 200/60 R15
	Rear / 4WD	Ag: 12.4-16 Ind: 12.4-16 / 15-19.5 (ROPS Only) Ag/Ind Hybrid: 14-17.5 / 15-19.5 (ROPS Only)	Ag: 12.4-16 Turf: 14-17.5 Ind: 14-17.5 Turf Radial: 300/70 R20

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.

# LX2610SU



COMPETITIVE COMPARISON							
FEATURES		Kubota LX2610SU	John Deere 3025E	Kiotti CK2610	Massey Ferguson 1526	LS MT225HE	TYM T264
Engine	Engine Manufacturer	Kubota	Yanmar	Daedong-Kiotti	Iseki	Yanmar	Kukje
	Engine	D1305-E4-D36-R	3TNV88F-EPJT2	3A165LWM-U	N/P	3TNV80F-ZXKLST	A1100N2
	Gross Engine HP, SAE J1995 hp (kw)	24.8 (18.5)	24.7 (18.2)	24.5 (18.2)	24.8 (18.5)	25 (19)	24.1 (18)
	PTO HP hp (kw)	19.5 (14.5)	19.4 (14.4)	21.8 (16.3)	20.1 (15)	19.3 (14.3) / 17.1 (12.8)	18.3 (13.6)
	Rated Engine Speeds rpm	2500	2400	2600	2600	2800	2600
	Aspiration	Natural	Natural	Natural	Turbocharged	Natural	Natural
	Displacement cu. in. (liters)	77.0 (1.261)	100.2 (1.642)	100.5 (1.647)	91.4 (1.5)	80.4 (1.318)	71.7 (1.175)
	Injection Type	Indirect	Direct Injection	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3	3	3
	Alternator Amps	40	55	50	N/P	40	50
Fuel Tank	Fuel Tank Capacity gal. (liters)	7.1 (27.0)	7.5 (28.5)	9.0 (34)	10.0 (38)	6.8 (26)	6.6 (25)
Transmission	Transmission	HST - 3 Range	HST - 2 Range	HST - 3 Range	HST - 3 Range	HST - 3 Range	HST - 2 Range
	HST Cruise Control	Optional	Optional	Optional	Standard	N/P	Standard
	Brakes	Multi-Plate Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc	Wet Disc
Axles Steering	Differential Lock	Standard	Standard	Standard	Standard	Standard	Standard
	Steering	Power	Power	Power	Power	Power	Power

# LX2610SU



COMPETITIVE COMPARISON							
FEATURES		Kubota LX2610SU	John Deere 3025E	Kiotti CK2610	Massey Ferguson 1526	LS MT225HE	TYM T264
PTO	Type	Independent	Independent	Live	Transmission driven	Independent	Independent
	Speeds @ RPM	540 @ 2500	541 @ 2400	540 @ 2600	540 @ 2600	540 @ 2800	540 @ 2600
	Clutch type	Hydraulic	Wet Disk	Gear	Gear-Type	N/P	Electric/Hydro
Hydraulic System	Hydraulic Remote Valves	2 Optional	2 Optional	2 Optional	2 Optional	2 Optional	N/P
	Main Pump Flow gpm (l/m)	5.0 (18.9)	5.3 (20.1)	N/P	5.5 (20.8)	7.9 (29.9)	4.3 (16.3)
	Power Steering Flow gpm (l/m)	3.7 (14.2)	4.0 (15)	N/P	3.2 (12.1)	4.6 (17.4)	2.7 (10.4)
	Total Flow gpm (l/m)	8.7 (33.1)	9.3 (35.2)	11.7 (44.4)	8.7 (32.9)	12.5 (47.3)	7.1 (27)
	Control Type	Position	Position	Position	Position	Position	Position
Three Point Hitch	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I	Cat. I
	Telescopic Lower Link Ends	Optional	Optional	Optional	N/P	N/P	N/P
	Stabilizers	Telescopic	Check Chains	Check Chains	Check Chains	Check Chains	Check Chains
	Lift Capacity @ the pin, SAE lbs. (kg)	2139 (970)	N/P	N/P	1322 (600)	1808 (820)	1503 (700)
	Lift Capacity @ 24" Behind, SAE lbs. (kg)	1676 (760)	1356 (615)	1631 (740)	992 (450)	N/P	1102 (500)
Dimensions Weight	Wheelbase in. (mm)	65.6 (1666)	62.8 (159.5)	65.7 (1670)	65.9 (1675)	63.4 (1610)	58.3 (1480)
	Height in. (mm)	88.4 (2245)	82.3 (2090)	99.2 (2520)	97.6 (2480)	86.4 (2195)	89.8 (2281)
	Ground Clearance in. (mm)	14.6 (370)	12.7 (324)	13.4 (340.6)	11 (280)	N/P	7.71 (196)
	Turning Radius w/ Brake ft. (m)	6.9 (2.1)	N/P	8.0 (2.4)	N/P	N/P	8.2 (2.5)
	Turning Radius w/o Brake ft. (m)	8.5 (2.6)	N/P	9.4 (2.9)	N/P	N/P	8.79 (2.7)
	Weight lb. (kg)	1786 (810)	2222 (1007.9)	2701 (1225)	2600 (1180)	1764 (800)	1881 (853)
Tires	Front / 4WD	Ag: 7-12 Ind: 23x8.50-14 / 25x8.50-14 Ag/Ind Hybrid: 23x8.50-12 / 25x8.50-14	Ag: 7-14 Turf: 27x8.5-15 R4: 25x8.5-14 R4: 27x8.5-15	Ag: 7-16 Turf: 28x8.5-15/6 Ind: 27x8.5-15	Ag: 7-16 Ag Ind: 27x8.50-15	Ag: 7-14 Ind: 25x8.5-14	Ind: 23 x 8.5-12
	Rear / 4WD	Ag: 12.4-16 Ind: 12.4-16/15-19.5 Ag/Ind Hybrid: 14-17.5 / 15-19.5	Ag: 11.2-24 Turf: 41x14-20 R4: 15-19.5 R4: 43x16-20	Ag: 11.2-24 Turf: 41x14-20/4 Ind: 15-19.5	Ag: 11.2x24 Ind: 15x19.5	Ag: 11.2-24 Ind: 43x16-20	Ind: 12 x 16.5

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.

# LX2610



COMPETITIVE COMPARISON					
FEATURES		Kubota LX2610	Kiote CK2610	Massey Ferguson 1526	TYMT264
Engine	Engine Manufacturer	Kubota	Daedong-Kiote	Shibaura	Kukje
	Engine	ROPS: D1305-E4-D36-R CAB: D1305-E4-D26-Q	3A165LWM-U	N/P	A1100N2
	Gross Engine HP, SAE J1995 hp (kw)	24.8 (18.5)	24.5 (18.2)	24 (17.9)	24.1 (18)
	PTO HP hp (kw)	19.5 (14.5)	21.8 (16.3)	19.2 (14.3)	18.3 (13.6)
	Rated Engine Speeds rpm	2500	2600	2600	2600
	Aspiration	Natural	Natural	Turbocharged	Natural
	Displacement cu. in. (liters)	77.0 (1.261)	100.5 (1.647)	91.3 (1.5)	71.7 (1.175)
	Injection Type	Indirect	Indirect	Indirect	Indirect
	Cylinders	3	3	3	3
Alternator Amps	ROPS: 40CAB 60	50	N/P	50	
Fuel Tank	Fuel Tank Capacity gal. (liters)	ROPS: 7.1 (27.0) CAB: 8.3 (31.5)	9.0 (34)	10.0 (38)	6.6 (25)
	Transmission	HST - 3 Range	HST - 3 Range	HST - 3 Range	HST - 2 Range
Transmission	HST Cruise Control	Standard	Optional	Standard	Standard
	Brakes	Multi-Plate Wet Disc	Wet Disc	Wet Disc	Wet Disc
	Differential Lock	Mechanical	Mechanical	Mechanical	Mechanical
Axles Steering	Differential Lock	Mechanical	Mechanical	Mechanical	Mechanical
	Steering	Power	Power	Power	Power

# LX2610



COMPETITIVE COMPARISON					
FEATURES		Kubota LX2610	Kiote CK2610	Massey Ferguson 1526	TYMT264
PTO	Type	Independent	Live	Transmission driven	Independent
	Speeds @ RPM	ROPS: 540 @ 2500 CAB: 540 @ 2500	540 @ 2600	540 @ 2600	540 @ 2600
	Clutch type	Hydraulic	Gear-Type	Gear-Type	Electric/Hydro
	Mid PTO	Standard	Optional	Optional	Optional
Hydraulic System	Hydraulic Remote Valves	2 Optional	2 Optional	2 Optional	N/P
	Main Pump Flow gpm (l/m)	5.0 (18.9)	N/P	5.5 (30.8)	4.4 (16.6)
	Power Steering Flow gpm (l/m)	3.7 (14.2)	N/P	3.2 (12.1)	2.7 (10.4)
	Total Flow gpm (l/m)	8.7 (33.1)	11.7 (44.4)	8.7 (32.9)	7.1 (27)
	Control Type	Position	Position	Position	Position
Three Point Hitch	Three Point Hitch Type	Cat. I	Cat. I	Cat. I	Cat. I
	Telescopic Lower Link Ends	ROPS: Optional CAB: Standard	Optional	N/P	N/P
	Stabilizers	Telescopic	Check Chains	Check Chains	Check Chains
	Lift Capacity @ the pin, SAE lbs. (kg)	2139 (970)	N/P	1322 (600)	1503 (700)
	Lift Capacity @ 24" Behind, SAE lbs. (kg)	1676 (760)	1631 (740)	992 (450)	1102 (500)
Dimensions Weight	Wheelbase in. (mm)	65.6 (1666)	65.7 (1670)	65.9 (1675)	58.3 (1480)
	Height in. (mm)	ROPS: 88.4 (2245) CAB: 84.6 (2150)	99.2 (2520)	97.6 (2480)	89.8 (2281)
	Ground Clearance in. (mm)	14.6 (370)	13.4 (340.6)	11 (280)	7.71 (196)
	Turning Radius w/ Brake ft.(m)	6.9 (2.1)	8.0 (2.4)	N/P	8.2 (2.5)
	Turning Radius w/o Brake ft.(m)	8.5 (2.6)	N/P	N/P	8.79 (2.7)
	Weight lb. (kg)	ROPS: 1786 (810) CAB: 2293 (1040)	2701 (1225)	2600 (1180)	1881 (853)
Tires	Front / 4WD	Ag: 7-12 Ind: 23x8.50-14 / 25x8.50-14 (ROPS Only) Ag/Ind Hybrid: 23x8.50-12 / 25x8.50-14 (ROPS Only)	Ag: 7-16 Turf: 28x8.5-15/6 Ind: 27X8.5-15	Ag: 7-16 Ag Ind: 27x8.50-15	Ind: 23 x 8.5-12
	Rear / 4WD	Ag: 12.4-16 Ind: 12.4-16 / 15-19.5 (ROPS Only) Ag/Ind Hybrid: 14-17.5 / 15-19.5 (ROPS Only)	Ag: 11.2-24 Turf: 41x14-20/4 Ind: 15-19.5	Ag: 11.2x24 Ind: 15x19.5	Ind: 12 x 16.5

N/A = Not Available

N/P = Not Published

our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.