



COMPETITIVE COMPARISON

MODEL		Kubota RTV X1140 Worksite	Kawasaki Mule PRO-DXT	Kawasaki Mule 4010Trans 4X4 Diesel	John Deere Gator XUV 855D S4	Polaris Ranger Crew Diesel
Engine	Make	Kubota	n/a	Daihatsu	Yanmar	Kohler
	Type	4-cycle diesel	4-Cycle diesel	4-cycle diesel	4-cycle diesel	4-cycle diesel
	Cylinders	3	3	3	3	3
	Displacement (cc)	1123	993	953	854	1028
	Horsepower	24.8hp	n/a	24.7hp	22.5hp	24
	Torque (lbs/ft)	52.7	38	52	50	n/a
Fuel System	Fuel Tank Capacity	7.9 gallons	7.9 gallons	6.4 gallons	7 gallons	10 gallons
Muffler		Spark arresting	Spark arresting	Spark arresting	Spark arresting	Spark arresting
Alternator		60 amps	55 amps	40 amps	55 amps	110 amps
Transmission	Type	Variable Hydrostatic Transmission (VHT-X)	CVT with belts	CVT with belts	CVT with belts	CVT with belts
	Wheels, drive system	Rear 2WD or 4WD	Rear 2WD or 4WD	Rear 2WD or 4WD	On demand 4WD	Rear 2WD or 4WD
	Differential Lock	Standard, foot operated	Switch activated/ Rear axle only	Rear, dual-mode	Front- on/off switch Rear-hand operated	Front- on/off switch Rear-hand operated
	Gear Selection	Hi-Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse	Hi Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse, park
Steering		Power full hydraulic with manual tilt feature	Manual with tilt (EPS optional)	Power-electric	Power-electric	Manual steering with tilt



COMPETITIVE COMPARISON

MODEL		Kubota RTV X1140 Worksite	Kawasaki Mule PRO-DXT	Kawasaki Mule 4010Trans 4X4 Diesel	John Deere Gator XUV 855D S4	Polaris Ranger Crew Diesel
Brakes	Front	Sealed hydraulic discs	hydraulic disc	hydraulic drums	hydraulic disc	hydraulic disc
	Rear	Sealed hydraulic discs	hydraulic disc	hydraulic drums	hydraulic disc	hydraulic disc
	Parking	rear wheel, hand lever	rear wheel, hand lever	rear wheel, hand lever	driveline, hand lever	Park in transmission
Suspension	Front	Independent, dual A-arms	Double wishbone	Independent, McPherson struts	Dual A-arm	Dual A-arm
	Rear	Independent with coil over shock	Double wishbone	Semi-independent DeDion axle w/ leaf springs and hydraulic shocks	Dual A-arm	Dual A-arm
Front Guard		Standard	Standard	Standard	Standard	Standard
Occupant Protection System		2.0 Steel tube: meets OSHA 1928.53 & SAE J2194 ROPS	ROPS meets the performance requirements of ISO 3471	Steel tube ROPS meets SAE J1194	ROPS certified	Steel tube ROPS
Seating		Digital Multi-meter	Digital Multi-meter	Speedometer & gauges	Digital Multi-meter	Digital Multi-meter



COMPETITIVE COMPARISON

MODEL		Kubota RTV X1140 Worksite	Kawasaki Mule PRO-DXT	Kawasaki Mule 4010Trans 4X4 Diesel	John Deere Gator XUV 855D S4	Polaris Ranger Crew Diesel
Factory-installed Integrated Full Cabin		Bench Seats - Convertible 1 to 2 row seating	Bench Seats - Convertible 1 to 2 row seating	Bench Seats- Convertible 1 to 2 row seating	Bucket seats - Non-convertible, fixed 2 row seating	Bench Seats - Non-convertible, fixed 2 row seating
Factory Air Conditioner, Heater & Defroster		not available	not available	not available	not available	not available
Speaker system		--		--	--	--
Standard pre-wiring for optional stereo		--	--	--	--	--
Sound level, @ operator's ear	At max speed w/ no load	84dBA	--	--	--	--
	At 15 mph	--	--	--	--	--
Overall Dimensions (in inches)	Length	143.3	133.2	116.7	154	148.5
	Width	62.2	64	62	62	61
	Height, overall	80.1	77.6	75.8	75	76
	Front tread centers	50.4	n/a	45.7	51.2	n/a
	Rear tread centers	50.4	n/a	46.5	51.2	n/a
	Wheelbase	98.2	92.3	73.6	114	113
	Ground clearance, front axle	10.8	TBA - 10" min	6.9	11	11.3
	Ground clearance, rear axle	9.3	TBA - 10" min	8.3	11	11.3



COMPETITIVE COMPARISON

MODEL		Kubota RTV X1140 Worksite	Kawasaki Mule PRO-DXT	Kawasaki Mule 4010Trans 4X4 Diesel	John Deere Gator XUV 855D S4	Polaris Ranger Crew Diesel
Turning radius (ft)		17.7	16	12.5	28.3	17.8
Payload Capacity (lbs)		1629	1616	1632	1400	1750
Towing Capacity (lbs)		1301	2000	1200	1500	2000
Tow Hitch Availability		Standard 2" front & rear	Standard 2" rear	Standard 2" rear	Standard 2" rear	Standard 2" rear
Vehicle weight (lbs)		2370	1889.7	1738	2018	1690
Cargo Bed	Bed Load Capacity (lbs) 1 row or 2 row mode	1102lbs - 1 row 661lbs - 2 row	1000 lb - 1 row 350 lb 2 row	800 lb -1 row 400 lb - 2 row	1000	1000
	Bed Lift System	hydraulic	Strut assist (Optional Hydraulic)	manual	manual	manual
	Width x Length x Depth (in.) 1 row mode	57.7 x 51.6 x 11.2	53.7 x 42.7 x 11	47.7 x 50.4 x 11.3	--	--
	Width x Length x Depth (in.) 2 row mode	57.7 x 26 x 11.2	53.7 x 22 x 11	47.7 x 30.0 x 11.3	52 x 45 x 11	54 x 36.5 x 11.5
	Volume (cu ft) 1 or 2 row	19.1 Long 9.9 Short	14.6 / 7.5	15.6 / 9.4	16.2	13.1
Tire Selection		Heavy Duty Worksite or ATV	Duro	N/P	Ancla M-T or Maxxis Big Horn	PXT



COMPETITIVE COMPARISON

MODEL		Kubota RTV X1140 Worksite	Kawasaki Mule PRO-DXT	Kawasaki Mule 4010Trans 4X4 Diesel	John Deere Gator XUV 855D S4	Polaris Ranger Crew Diesel
Tires	Front	25x10-13	26 x 9-12	23x11-10	26x9-12 or 27 x 9-14	26 x 9-12
	Rear	25x10-13	26 x 11-12	23x11-10	26x11-12 or 27x11-14	26 x 11-12

Comparisons of specifications are based on the latest data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.

* Manual-tilt feature for steering wheel and fore/aft adjustment for driver's seat is not available on RTV-X900 General Purpose models