



# RTV X900 / RTV X1120D / RTV X1100C



## COMPETITIVE COMPARISON

MODEL	Kubota RTV X900 Worksite	Kubota RTV X1120D Worksite	Kawasaki Mule 4010 Diesel	John Deere Gator XUV 855D	Polaris Ranger 4X4 Diesel	Kubota RTV X1100C Worksite	
Occupant Protection System	2.0" steel tube; meets OSHA 1928.53 & SAE J2194 ROPS	2.0" steel tube; meets OSHA 1928.53 & SAE J2194 ROPS	Steel tube ROPS meets SAE J1194	1.75" diameter steel tube ROPS	Steel tube ROPS	2.4" x 2.4" deformed steel tube; meets OSHA 1928.53 & SAE J2194 ROPS	
Seating	Digital Multi-meter	Digital Multi-meter	Speedometer & gauges	Digital Multi-meter	Digital Multi-meter	Digital Multi-meter	
Factory-installed Integrated Full Cabin	60/40 Split-bench with underseat storage & driver's-side fore/aft adjustment*	60/40 Split-bench with underseat storage & driver's-side fore/aft adjustment	Bench	Bucket seats	Bench	60/40 Split-bench with underseat storage & driver's-side fore/aft adjustment	
Factory Air Conditioner, Heater & Defroster	not available	not available	not available	not available	not available	Standard	
Speaker system	--	--	--	--	--	Standard	
Standard pre-wiring for optional stereo	--	--	--	--	--	Standard	
Sound level, @ operator's ear	At max speed w/ no load	85 dBA	84 dBA	--	--	--	83 dBA
	At 15 mph	--	--	--	--	--	78 dBA

## COMPETITIVE COMPARISON

MODEL	Kubota RTV X900 Worksite	Kubota RTV X1120D Worksite	Kawasaki Mule 4010 Diesel	John Deere Gator XUV 855D	Polaris Ranger 4X4 Diesel	Kubota RTV X1100C Worksite	
Overall Dimensions (in inches)	Length	122.5	122.5	116.7	116	114	122.5
	Width	63.2	63.2	62	62	60	65.4
	Height, overall	79.5	79.5	75.8	75	76	82.3
	Front tread centers	48.8	48.8	45.7	51.2	--	48.8
	Rear tread centers	48.8	48.8	46.5	51.2	--	48.8
	Wheelbase	80.5	80.5	73.6	79	72	80.5
	Ground clearance, front axle	10.5	10.5	6.9	11	12	10.5
	Ground clearance, rear axle	10.4	10.4	8.3	10	12	10.4
Turning radius (ft)	13.1	13.1	11.2	12.4	12.4	13.1	
Payload Capacity (lbs)	1598	1510	1632	1400	1500	1629	
Towing Capacity (lbs)	1300	1300	1200	1500	2000 (tow hitch rating)	1300	
Tow Hitch Availability	Standard 2" front & rear	Standard 2" front & rear				Standard 2" front & rear	
Vehicle weight (lbs)	1973	2061	1598	1650	1435	2370	
Cargo Bed	Bed Load Capacity (lbs)	1102	1102	1100	1000	1000	1102
	Bed Lift System	hydraulic	hydraulic	manual	manual	manual	hydraulic
	Width x Length x Depth (in.)	57.7 x 40.5 x 11.2	57.7 x 40.5 x 11.2	46.3 x 51.6 x 11.3	52 x 45 x 11	54 x 36.5 x 11.5	57.7 x 40.5 x 11.2
	Volume (cu ft)	15.2	15.2	15.6	16.4	13	15.2
Tire Selection	Heavy Duty Worksite, ATV, or Turf	Heavy Duty Worksite, ATV, or Turf	Ancla M-T, Terrahawk AT			Heavy Duty Worksite, ATV, or Turf	
Tires	Front	25x10-12	25x10-12	23x11-10	26x9-12	25x10-12	25x10-12
	Rear	25x10-12	25x10-12	23x11-10	26x11-12	25x11-12	25x10-12

Comparisons of specifications are based on the latest data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Competitive information in this section was obtained from competitive websites and product brochures, and is correct to the best of our knowledge.

\* Manual-tilt feature for steering wheel and fore/aft adjustment for driver's seat is not available on RTV-X900 General Purpose models