

COMPETITIVE COMPARISON							
Model		Kubota SVL65-2	Bobcat T595	Bobcat T590	Deere 317G	CAT 259D	New Holland C232
Engine	Engine Brand	Kubota	Doosan	Doosan	Yanmar	CAT	FPT
	Engine Model	V2607-CR-TE4	np	np	4TNV86CHT	C3.3B DIT	F5H FL-463A
	Emission	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4	Tier 4
	Emission Solution	DPF	DOC	DOC	DPF	PMC	PMC
	Gross HP (kW) - SAE J1995	68.4 (51.0)	74 (55.2)	66 (49.2)	65 (48.65)	74.3 (55.4)	74 (55.2)
	Peak Torque - lb-ft (N-m)	166 (225)	np	np	207 (280)	np	232 (314)
	Displacement cu in(L)	159.6 (2.6)	147.4 (2.4)	np	153 (207)	203 (3.3)	207 (3.4)
	Cylinders	4	4	4	4	4	4
	Aspiration	Turbo	Turbo	Turbo	Turbo	Turbo	Turbo
Loader Specification	Geometry	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
	Tipping Load - lbs (kg)	6000 (2722)	6285 (2850)	6000 (2722)	6070 (2756)	5800 (2631)	6400 (2902)
	Rated Operating Capacity (35% of tipping) - lbs (kg)	2100 (953)	2200 (997)	2100 (953)	2125 (965)	2030 (921)	2240 (1018)
	Rated Operating Capacity (50% of tipping) - lbs (kg)	3000 (1361)	3142 (1425)	3000 (1361)	3035 (1378)	2900 (1315)	3200 (1451)
	Tip Breakout - lbs (kg)	4614 (2093)	4843 (2196)	5470 (2481)	4250 (1930)	5035 (2663)	7510 (3406)
	Lift Breakout - lbs (kg)	4266 (1935)	np	np	5000 (2270)	np	4840 (2195)
Undercarriage	Length of track on ground - in (mm)	57.9 (1470)	55.2 (1401)	54.1 (1374)	np	59 (1495)	64.5 (1639)
	Track width standard - in (mm)	12.6 (320)	12.6 (320)	12.6 (320)	12.6 (320)	12.6 (320)	17.7 (450)
	Track width optional - in (mm)	15.0 (380)	15.8 (400)	15.8 (400)	15.8 (400)	15.7 (400)	n/a
	Ground pressure (Rubber track width) - psi	4.9	5.7	5.1	4.5	4.8	4.2
	Travel Speed Low mph (km/h)	4.9 (7.8)	7.1 (11.4)	7.1 (11.4)	7 (11.3)	5.9 (9.5)	5.1 (8.2)
	Travel Speed High mph (km/h)	7.1 (11.5)	10.4 (16.7)	10.4 (16.7)	8.7 (14)	8.5 (13.7)	7.6 (12.2)
	Traction Force - lbf (kgf)	8406 (3813)	np	np	8000 (3632)	np	np
Hydraulic Systems	Pump Flow Standard - gpm (lpm)	17.4 (66)	17.1 (64.7)	17.1 (64.7)	16 (59)	20 (76)	24.2 (91.5)
	Pump Flow Optional High Flow - gpm (lpm)	27.0 (102.2)	26.7 (101.1)	26.7 (101.1)	NP	30 (112)	37.6 (142.5)
	Hydraulic Pressure - psi (bar)	3263 (229)	3500 (242)	3500 (242)	3450 (243)	3335 (230)	3046 (214)
Dimensions and Capacities	Height to Top of ROPS - in (mm)	79.9 (2029)	77.8 (1976)	77.8 (1976)	78.5 (1990)	83.1 (2111)	80.4 (2043)
	Overall Length with Standard Bucket - in (mm)	136.4 (3465)	133 (2979)	133 (3378)	127.6 (3240)	127.3 (3233)	142.9 (3631)
	Length w/o Bucket - in (mm)	107.3 (2725)	104.6 (2343)	104.6 (2657)	103 (2630)	137.3 (3486)	117.8 (2993)
	Width over Tracks -in (mm)	65.2 (1657)	67.1 (1704)	67 (1702)	65.1 (1650)	69 (1755)	76 (1930)
	Width with Standard Bucket - in (mm)	68 (1727)	68 (1523)	68 (1727)	72 (1829)	np	78 (1981)
	Dump Clearance at Full Height - in (mm)	89.6 (2275)	91.3 (2319)	91.3 (2319)	95.6 (2430)3	89.9 (2283)	102.2 (2596)
	Height to Bucket Pin - in (mm)	118.5 (3010)	119 (3023)	119 (3023)	121 (3070)	121 (3075)	131.1 (3330)
	Reach at Max Dump Height - in (mm)	34.9 (886)	34.9 (886)	34.9 (886)	31 (790)	23.9 (608)	34.2 (875)
	Bucket Rollback at Ground - degrees	30	30	30	30	np	33
	Max Dump Angle at Full Height - degrees	40	42	42	np	52	55
	Rear Angle of Departure	30	np	28.8	32.3	35	32
	Ground Clearance - in (mm)	9.1 (233)	7.3 (185.4)	7.4 (188)	8.3 (210)	8.9 (226)	9.5 (243)
	Operating Weight - lbs (kg)	8035 (3645)	8055 (3653)	7822 (3548)	8195 (3721)	8945 (4057)	9630 (4370)
	Service Capacities	Fuel Tank - gal (l)	21.7 (82)	24.75 (93.9)	36.5 (138.2)	19 (71)	27.7 (105)
Hydraulic Tank - gal (l)		5.4 (20.3)	9.5 (36)	np	np	10.3 (39)	6 (22.8)

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.