		Page: 1
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID

Relevant identified uses of the substance or mixture and uses advised against

<p>Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL</p>	<p>Emergency telephone number 1-800-VALVOLINE</p> <p>Regulatory Information Number 1-800-TEAMVAL</p> <p>Product Information 1-800-TEAMVAL</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ eye protection/ face protection.
Response:
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue

SAFETY DATA SHEET

Revision Date: 03/08/2017

Print Date: 3/10/2017

SDS Number: 000000189373

Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID

Version: 1.1

787139

rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.


SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components


Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	58.00
Distillates (Petroleum), Hydrotreated Middle	64742-46-7	Asp. Tox. 1; H304	2.97
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	2.7789
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319 Skin Sens. 1; H317	1.47
ALKYL IMIDAZOLINE		Eye Irrit. 2A; H319	1.47
PHOSPHORODITHIOIC ACID	4259-15-8	Eye Dam. 1; H318	1.47
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED CALCIUM SALTS		Eye Irrit. 2A; H319 Skin Sens. 1; H317	0.27
PHOSPHOROUS ACID, TRIPHENYL ESTER	101-02-0	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2A; H319	0.27

		Page: 3
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

		Skin Sens. 1A; H317	
--	--	---------------------	--

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

		Page: 4
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
nitrogen oxides (NO_x)
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

Revision Date: 03/08/2017

Print Date: 3/10/2017

SDS Number: 000000189373

Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID
787139

Version: 1.1

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Middle	64742-46-7	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
				NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRANS
				OSHA_TRANS
		TWA	5 mg/m3	ACGIH

SAFETY DATA SHEET

Revision Date: 03/08/2017

Print Date: 3/10/2017

SDS Number: 000000189373

Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID

Version: 1.1


787139

		STEL	Mist. 10 mg/m3 Mist.	ACGIH
				ACGIH
		TWA	0.2 mg/m3 Inhalable fraction.	ACGIHLIS_P
				ACGIHLIS_P
				ACGIHLIS_P
				ACGIHLIS_P
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS	
ALKYL IMIDAZOLINE	
PHOSPHORODITHIOIC ACID	4259-15-8
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED CALCIUM SALTS	
PHOSPHOROUS ACID, TRIPHENYL ESTER	101-02-0

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if

		Page: 7
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 128 °C Calculated Flash Point

SAFETY DATA SHEET

Revision Date: 03/08/2017

Print Date: 3/10/2017

SDS Number: 000000189373

Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID


Version: 1.1

787139

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	: 1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.842 g/cm ³
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition	

		Page: 9
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

products

carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Distillates (Petroleum), Hydrotreated Middle:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: Slightly toxic by inhalation

PHOSPHORODITHIOIC ACID:

Acute oral toxicity : LD50 (Rat): 3,100 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg
Method: OECD Test Guideline 402

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Acute oral toxicity : LD50 (Rat, male): 1.59 g/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 6.7 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.


Acute dermal toxicity : LD50 (Rabbit): > 2 - < 5 g/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

		Page: 10
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

Result: Repeated exposure may cause skin dryness or cracking.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Middle:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: No skin irritation

ALKYL IMIDAZOLINE:

Result: Slight, transient irritation

PHOSPHORODITHIOIC ACID:

Result: Slight, transient irritation

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Species: Guinea pig

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result: No eye irritation

Distillates (Petroleum), Hydrotreated Middle:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Irritating to eyes.


ALKYL IMIDAZOLINE:

Result: Irritating to eyes.

PHOSPHORODITHIOIC ACID:

Result: Corrosive

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED CALCIUM SALTS:

		Page: 11
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

Result: Irritating to eyes.

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment: May cause sensitisation by skin contact.

Result: May cause sensitization by skin contact.

PHOSPHORODITHIOIC ACID:

Result: Did not cause sensitisation on laboratory animals.

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED CALCIUM SALTS:

Assessment: May cause sensitisation by skin contact.

Result: May cause sensitization by skin contact.

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Components:

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity


Not classified based on available information.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Middle:

		Page: 12
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l


Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

PHOSPHORODITHIOIC ACID:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.4 mg/l
 Exposure time: 96 h
 Test Type: semi-static test
 Test substance: WAF
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Water flea (Daphnia magna)): 75 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): 410 mg/l
 End point: Growth inhibition
 Exposure time: 72 h

		Page: 13
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

Test Type: static test
Test substance: WAF

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

PHOSPHORODITHIOIC ACID:

Biodegradability : Result: Not biodegradable
Biodegradation: < 5 %
Exposure time: 27 d
Method: OECD Test Guideline 301D

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

No data available

Bioaccumulative potential

Components:

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Partition coefficient: n- : log Pow: 6.62
octanol/water Remarks: QSAR

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and



SAFETY DATA SHEET

Revision Date: 03/08/2017

Print Date: 3/10/2017

SDS Number: 000000189373

Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID

Version: 1.1

787139

federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

MX_DG

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TDG_INWT_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_ROAD_C


Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

		Page: 15
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

U.S. DOT - ROAD

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 313

PHOSPHORODITHIOIC ACID 4259-15-8 1.47 %


California Prop 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Not in compliance with the inventory

Inventories


		Page: 16
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 03/08/2017

NFPA: 	HMIS III: <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification


Combustible Liquid Class IIIB

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

		Page: 17
SAFETY DATA SHEET		Revision Date: 03/08/2017
		Print Date: 3/10/2017
		SDS Number: 000000189373
Kubota® SUPER UDT2 UNIVERSAL TRANS-HYDRAULIC FLUID		Version: 1.1
787139		

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System