ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033

HYDRAULIC FLUID

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet
Ashland
P.O. Box 2219
Columbus, OH 43216
United States of America

Emergency telephone number
1-800-ASHLAND (1-800-274-5263)

Regulatory Information Number
1-800-325-3751

Product Information
614-790-3333

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

Skin sensitization : Category 1

GHS Label element

Hazard pictograms



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Causes serious eye irritation.

Precautionary Statements : Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Contaminated work clothing must not be allowed out of the

workplace.

Wear eye protection/ face protection.

Wear protective gloves.

Response:

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS		Eye Irrit. 2A; H319	1.49
PHOSPHORODITHIOIC ACID	4259-15-8	Eye Dam. 1; H318	1.49
POLYMER		Skin Sens. 1; H317	0.49
PHOSPHOROUS ACID, TRIPHENYL ESTER	101-02-0	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	0.10

SECTION 4. FIRST AID MEASURES

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction.

Causes serious eye irritation.

No symptoms known or expected.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

:

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Container hazardous when empty.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

: Provide sufficient mechanical (general and/or local exhaust) **Engineering measures**

> ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Wash hands before breaks and at the end of workday. Hygiene measures

> When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

: No data available рΗ

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point $: > 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

Method: Cleveland open cup

Evaporation rate : > 1

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

Calculated Explosive Limit

Lower explosion limit : 1 %(V)

Calculated Explosive Limit

Vapour pressure : 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : 0.880 (15.6 °C)

Density : 0.8711 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 9.55 mm2/s

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

PHOSPHORODITHIOIC ACID:

Acute oral toxicity : LD50 (Rat): 3,100 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg

Method: OECD Test Guideline 402

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Acute oral toxicity : LD50 (Rat, male): 1.59 g/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 (Rat): > 6.7 mg/l

Exposure time: 1 h

Method: OECD Test Guideline 403

Remarks: Aerosol

Acute dermal toxicity : LD50 (Rabbit): > 2 - < 5 g/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Not irritating to skin

PHOSPHORODITHIOIC ACID: Result: Mildly irritating to skin

POLYMER:

Result: Not irritating to skin

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Result: Severely irritating to skin

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result: Irritating to eyes

PHOSPHORODITHIOIC ACID: Result: Corrosive to eyes

POLYMER:

Result: Not irritating to eyes

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Result: Irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

PHOSPHORODITHIOIC ACID:

Result: Did not cause sensitisation on laboratory animals.

POLYMER:

Assessment: May cause sensitization by skin contact.

PHOSPHOROUS ACID, TRIPHENYL ESTER:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1A.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

IARC

Remarks: No data available

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

PHOSPHORODITHIOIC ACID:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.4 mg/l

Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Water flea (Daphnia magna)): 75 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Desmodesmus subspicatus (Scenedesmus

subspicatus)): 410 mg/l End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

Persistence and degradability PHOSPHORODITHIOIC ACID:

Biodegradability : Result: Not biodegradable

Biodegradation: < 5 % Exposure time: 27 d

Method: OECD Test Guideline 301D

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

ASHLAND	Page: 10
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods	

U.S. DOT - RAIL

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods		

TRANSPORT CANADA - ROAD

TO THE PROPERTY OF THE PROPERT	
Not dangerous goods	

TRANSPORT CANADA - RAIL

Not dangerous goods

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s)

PHOSPHORODITHIOIC 4259-15-8 1.49 %

ACID

Pennsylvania Right To Know

LUBRICATING OILS, PETROLEUM, 64742-58-1 50.00 - 70.00 %

HYDROTREATED SPENT

HEAVY PARAFFINIC DISTILLATE 64742-54-7 30.00 - 50.00 %

New Jersey Right To Know

LUBRICATING OILS, PETROLEUM, 64742-58-1 50.00 - 70.00 %

HYDROTREATED SPENT

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

HEAVY PARAFFINIC DISTILLATE 64742-54-7 30.00 - 50.00 %

BENZENE, POLYPROPENE Not Assigned 1.00 - 5.00 %

DERIVATIVES, SULFONATED, CALCIUM

SALTS

PHOSPHORODITHIOIC ACID 4259-15-8 1.00 - 5.00 %

CONTENTS PARTIALLY UNKNOWN Not Assigned 1.00 - 5.00 %

California Prop 65 Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

ASHLAND	Page: 13
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

ASHLAND	Page: 14
SAFETY DATA SHEET	Revision Date: 05/22/2015
	Print Date: 6/9/2015
	SDS Number: R0173402
Kubota® UDT UNIVERSAL TRANS KUBOTA # 70000-20033 HYDRAULIC FLUID	Version: 1.0
KU20033	

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit

STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System