

Revision Date: 07/31/2016

Print Date: 3/27/2018

SDS Number: 000000257523 Version: 1.2

Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE

865274

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509	Regulatory Information Number 1-800-TEAMVAL
United States of America	Product Information 1-800-TEAMVAL
SDS@valvoline.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM),	64742-62-7	Not a hazardous	27.30
SOLVENT-DEWAXED		substance or mixture.	

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 00000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

SECTION 4. FIRST AID MEASURES

l

General advice	: No hazards which require special first aid measures.
If inhaled	 If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	 Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing methods	:

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

Product is com	natible with	standard	fire-fighting	agents
1 1000013 0011	pauble with	Standard	me ngnung	ayonis.

Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	:	Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	Smoking, eating and drinking should be prohibited in t application area. For personal protection see section 8.	he
Conditions for safe storage	Containers which are opened must be carefully reseal kept upright to prevent leakage. Electrical installations / working materials must comply the technological safety standards.	
Materials to avoid	No materials to be especially mentioned.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
			concentration	

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

RESIDUAL OILS (PETROLEUM), SOLVENT- DEWAXED	64742-62-7	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Engineering measures	: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,
	suspected or apparent adverse effects.

Personal protective equipment	
Respiratory protection :	No personal respiratory protective equipment normally required.
Eye protection :	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection :	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).
Hygiene measures :	General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

...

Physical state	: liquid
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup



Revision Date: 07/31/2016

Print Date: 3/27/2018

SDS Number: 000000257523 Version: 1.2

Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE

865274

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Thermal decomposition	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	No hazardous decomposition products are known.

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 00000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

SECTION 11. TOXICOLOGICAL INFORMATION

Inhalation Skin contact Eye Contact Ingestion
information. SOLVENT-DEWAXED: LD 50 (Rat): > 5,000 mg/kg
LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: No mortality observed at this dose.
LD 50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose. LD 50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information. <u>Product:</u> Result: Repeated exposure may cause skin dryness or cracking.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Species: Rabbit Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.



Revision Date: 07/31/2016

Print Date: 3/27/2018

SDS Number: 000000257523 Version: 1.2

Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE

865274

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information. **Carcinogenicity** Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Product:** No aspiration toxicity classification

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: No aspiration toxicity classification

Further information

<u>Product:</u> Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

 RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:

 Toxicity to fish
 : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l



Revision Date: 07/31/2016

SDS Number: 000000257523

Print Date: 3/27/2018

Version: 1.2

Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE

865274

	Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility		
Toxicity to daphnia and other aquatic invertebrates	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202		
Toxicity to algae	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201		
Toxicity to fish (Chronic toxicity)	NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211		
Persistence and degradability			
Components:			
RESIDUAL OILS (PETROLEUM Biodegradability), SOLVENT-DEWAXED: Result: Not readily biodegradable.		
Diodegradability	Biodegradation: 2 - 4 %		
	Exposure time: 28 d Method: OECD Test Guideline 301B		
Bioaccumulative potential			
<u>Components:</u> No data available			
Mobility in soil			
<u>Components:</u> No data available			
Other adverse effects			
No data available			
Product: Additional ecological	An environmental hazard cannot be excluded in the event of		
0 / 10			

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

information	unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.
Components:	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	: The product should not be allowed to enter drains, water courses or the soil.
	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

MX_DG

	Not departous goode
	Not dangerous goods
-	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TDG_INWT_C

Not dangerous goods

TDG_RAIL_C

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

no

SECTION 15. REGULATORY INFORMATION

SARA 311/312	Hazards :	: No SARA Hazards				
SARA 313 Component(s)		RA 313 known CAS numbers that e		tain any chemical components with exceed the threshold (De Minimis) d by SARA Title III, Section 313.		
Pennsylvania	Right To Know					
	HEAVY PARAF	FINIC DISTILLATE	64742-54-7	50.00 - 70.00 %		
	RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED		64742-62-7	20.00 - 30.00 %		
New Jersey Ri	ght To Know					
	-	FINIC DISTILLATE	64742-54-7	50.00 - 70.00 %		
	RESIDUAL OILS SOLVENT-DEW	S (PETROLEUM), /AXED	64742-62-7	20.00 - 30.00 %		

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

MINERAL OIL			Not Assigned	1.00 - 5.00 %	
	· · · · · · · · · · · · · · · · · · ·	•	PETROLEUM), SOLVENT- VY PARAFFINIC	64742-65-0	0.10 - 1.00 %
California Pro	p 65		Proposition 65 warnings are	•	nis product
The compone TSCA			on TSCA Inventory		
DSL		:	All components of this prod	uct are on the Can	adian DSL.
AUSTR		:	Not in compliance with the i	nventory	
ENCS		:	Not in compliance with the i	nventory	
KECL		:	Not in compliance with the i	nventory	
PICCS		:	Not in compliance with the i	nventory	
IECSC		:	Not in compliance with the i	nventory	


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB



Full text of H-Statements referred to under sections 2 and 3.H302Harmful if swallowed.

Further information

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent, Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 3/27/2018
	SDS Number: 000000257523
Kubota® 80W-90 GEAR LUBRICANT HD GEAR LUBE	Version: 1.2
865274	

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System