

M4 Specifications

Model	M4D-061HDC12		M4-071HDC12		M4D-071HDC12	
	4WD		4WD		4WD	
CAB	Deluxe Wide Cab		Standard Wide Cab		Deluxe Wide Cab	
Engine	V3307-CR-TE4					
Type (Make : KUBOTA)	4 cylinder in-line, Common Rail System, Direct Injection					
No. of cylinders/Aspiration	4 / turbocharged					
Engine gross power (97/68/EC) HP (kW)	65.4 (48.8)				73.2 (54.6)	
PTO power (at rated engine rpm) HP (kW)	52 (38.8)				60 (44.7)	
Total displacement cu.in. (cc)	203 (3331)					
Rated engine RPM	2400					
Fuel tank capacity gal. (ℓ)	23.8 (90)					
Alternator Amp	130					
Transmission						
No. of speeds	F12 / R12 (option: F18 / R18 with Creep)					
Main gear shift	Fully synchronized (6 speed)					
Shuttle shift	Hydraulic-shuttle					
Main clutch type	Multiple wet disc					
Brake type	Hydraulic wet disc					
Differential lock (Front / Rear)	Limited Slip Differential / Mechanical					
4WD clutch type	Electro-hydraulic on-the-go		Mechanical on-the-go		Electro-Hydraulic on-the-go	
PTO						
Type	Live-independent PTO, electro-hydraulic clutch with brake					
Speed rpm	540 / 540E		540 (540 / 540E: OPT)		540 / 540E	
Hydraulics						
Pump capacity (3-Point Hitch) gpm (ℓ/min.)	16.7 (63.3)					
3-Point Hitch	Telescopic lower link ends, Telescopic Stabilizers					
Category	I / II					
Control system	Position, draft (top link sensing) & mixed control					
Lift capacity at 24 in. behind lift point (ASAE) lbs. (kg)	3307 (1500)					
Cylinder type	Two external cylinders					
No. of standard remote valves	2 (SCD / FD), Max. 3		1 (SCD), Max. 3		2 (SCD / FD), Max. 3	
Other features						
4WD system	Bevel gear type					
Steering	Hydrostatic power steering					
Tilt steering	Standard					
Hood type / Pedal type	Full open, slanted, steel / Hanging					
Deck type (ISO-mounted w/rubber mat)	Full-flat					
Panel type	Electronic					
Standard tire size						
Front			320 / 85R20			
Rear			420 / 85R30			
Dimensions & weight						
Overall length in. (mm)			142 (3600)			
Overall height top of CAB in. (mm)			101 (2560)			
Overall width (minimum) in. (mm)			75.6 (1920)			
Wheelbase in. (mm)			84.1 (2135)			
Crop clearance (Front axle) in. (mm)			18.1 (460)			
Tread width Front in. (mm)			58.5 (1487)			
Tread width Rear in. (mm)			56.2, 68.7 (1430, 1744)			
Turning radius (w/o brake) ft. (m)			11.8 (3.6)			
Tractor weight lbs. (kg)	6008 (2725)		5952 (2700)		6008 (2725)	

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2019 Kubota Corporation



Kubota
Genuine Parts
for maximum performance, durability and safety

KUBOTA GENUINE PARTS