

TRACTOR			M8-181	M8-201
ENGINE	Engine		B6.7 Tier 4 Final / Stage V	
	Manufacturer		Cummins	
	Displacement	ℓ	6.7	
	No. of Cylinders		6	
	Aftertreatment		DOC+SCR+DPF	
	Fuel Tank Capacity	gal. (ℓ)	99 (375)	
	Def. Tank Capacity	gal. (ℓ)	9 (35)	
PERFORMANCE	Rated Engine Horsepower* @ 2100 Engine RPM	HP	180	200
	Responsive Power Delivery		Additional 25 HP	
	Rated PTO Horsepower* @ 2000 Engine RPM	HP	145	159
PTO	Type		Electro-Hydraulically Operated	
	Rear PTO Types		540 - 6 Spline & 1000 - 21 Spline (Optional 1000 - 20 Spline)	
	Rear PTO Speeds		540/540E/1000/1000E	
	Front PTO Type - Optional		Electro-Hydraulically Operated	
	Front PTO		1000 - 21 Spline, Clockwise	
TRANSMISSION	Semi-Powershift		30F x 15R - 6 Powershifts x 5 Ranges	
	KVT		CVT	
	Max. Traveling Speed	MPH (km/h)	24.8 (40) (Optional 31 (50))	
HYDRAULICS	Hydraulic System		Closed-Center, Load Sensing (CCLS)	
	Steering/Operating Flow	gpm (ℓ/min)	11.1 (42)	
	Standard Implement Pump Flow	gpm (ℓ/min)	31.7 (120)	
	Optional Implement Pump Flow	gpm (ℓ/min)	42.2 (160)	
	Max Flow at One EHR Remote	gpm (ℓ/min)	31.7 (120)	
	No. of Rear Remote Valves (Electronic)		3 Valves (Optional 5 Valves)	
	Power Beyond		Optional	
	Trailer Brake (Hydraulic)		Optional	
Drawbar	Category		CAT III (Optional CAT IIIHD)	
Rear 3-Pt Hitch	Category		CAT III/IIIN	
	Lift Cap., 24" Behind Lift Points (OECD)*	lbs. (kg)	11200 (5080)	
	Optional: Lift Capacity (OECD)*	lbs. (kg)	13600 (6170)	
	Ball Ends		Standard	
	Hook Ends		Optional	
Front 3-Pt Hitch	Factory Installed		Optional	
	Lift Capacity at Hooks (OECD)*	lbs. (kg)	8818 (4000)	
Front Axle	Rigid Limited Slip Differential		Standard	
	Suspended Full Locking Differential		Optional	
	Rigid Full-Locking Differential		Optional	
	Turning Angle		55°	
Rear Axle	Bar Axle 4.13"x 98" (105mm x 2489mm) Overall Length		Standard	
	Bar Axle 4.13" x 118" (105mm x 2997mm) Overall Length		Optional	
Cabin	7" K-Monitor		Standard	
	12" K-Monitor Pro		Optional	
	High Visibility Roof Panel		Standard	
	Seat Fabric - Air Suspension		Standard	
	Seat Fabric - Semi-Active		Optional	
	Seat Leather - Semi-Active Heat and Air Conditioned		Optional	
	Radio Ready		Standard	
	Cab Suspension		Optional Semi-Active Electro - Hydraulic	
	Exterior Lighting		Standard 8 Halogen (Optional 12 Halogen)	
	LED Lighting		Optional 12 LED	
Measurement	Wheel base	in. (mm)	114 (2895)	
	Avg Shipping Weight	lbs. (kg)	19510 (8850)	
	Height	in. (mm)	128 (3250)	