

Model		RTV-XG850 SIDEKICK			
Type		General purpose	Worksite		Special
Body color		Orange	Orange, Green	RealTree® AP Camouflage	Black
Engine	Type	2-cylinders, 4-cycle, Gas, DOHC			
	Displacement cc	851			
	Horsepower HP (kW) /rpm	48.3 (36) / 5,750			
	Cooling system	Liquid			
	Battery Ah, CCA	56, 650			
Transmission		CVT PLUS (CVT with centrifugal clutch)			
Gear selection		Hi-Lo range forward, neutral, reverse			
Max. Traveling speed mph (km/h)		0-40 (0-64.4)			
4WD system	Front differential	Limited-slip differential			
	Rear differential	Foot operated differential lock			
Steering		Speed sensitive Electric Power Steering			
Brakes	Front / Rear	4-wheel hydraulic disc brake			
	Parking brake	Rear wheel, hand operated			
Suspension	Front suspension	Independent, Dual A-arms with adjustable spring preload			
	Front suspension travel in. (mm)	9 (229)			
	Rear suspension	Independent with coil over shock			
	Rear suspension travel in. (mm)	8.5 (216)			
Ground clearance	Front in. (mm)	9.8 (249)			
	Rear in. (mm)	9.9 (249)			
Headlights		LED (High-Low) with 2 reflectors			
Occupant Protective System (OPS)	Tubular overhead structure in. (mm)	2.0 (50.8)			
	Seat belts	3-point			
	Certification	SAE J2194 and OSHA ROPS standards			
Seating		2			
Dimensions	Length in. (mm)	117 (2,973) *without bumper	119.6 (3,093) *include bumper		
	Width in. (mm)	63.2 (1,605)			
	Height, overall in. (mm)	79.5 (2,020) *include ROPS			
	Front tread centers in. (mm)	52 (1,320)			
	Rear tread centers in. (mm)	52 (1,320)			
	Wheelbase in. (mm)	80.5 (2,045)			
	Turning radius ft. (m)	13.1 (4.0)			
Weight lbs. (kg)		1,761 (799) *dry			
Towing capacity lbs. (kg)		Flat : 2,000 (907.2) / Slope : 1,550 (703)			
Payload capacity lbs. (kg)		1,435 (651)			
Cargo bed	Material	Steel			
	Width x Length x Depth in. (mm)	40.5 x 57.5 x 11.4 (1,030 x 1,465 x 290)			
	Volume cu. F. (m3)	15.2 (0.43)			
	Cargo bed load lbs. (kg)	1,000 (454) / 600 (272) *California model			
	Dumping system	Manual			
	Power Lift	Optional electric hydraulic power lift			
Fuel tank capacity US gal (L)		8.64 (32.7)			
Sound rating at operator's ear at max rpm db. (A)		89.8			
Tires	Front and rear ATV	25 x 10-12, 6-ply		Optional	25 x 10-12, 6-ply
		HDWS			
Front guard		Optional	Standard front guard		
Alloy wheel			Optional		Standard
Steering tilt		Not available	Standard		
Spray-on bed liner		Not available	Optional	Standard	