

Specifications

L3560HSTC Limited Edition			
4WD, CAB			
Engine			
Type		Direct injection, vertical, water-cooled 4-cycle diesel	
Engine gross power (SAE J1995)	HP (kW)	37.0 (27.6)	
Engine net power (SAE J1349)	HP (kW)	35.0 (26.1)	
PTO power (OECD/CODE2)	HP (kW)	28.0 (20.9)	
No. of cylinders / Aspiration		3 / Natural with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)	
Total displacement	cu. in. (cc)	111.4 (1826)	
Rated speed	rpm	2600	
Battery		12V, RC: 133 min, CCA: 582A	
Alternator		12V, 60A	
Fuel tank capacity	US gal. (ℓ)	13.5 (51)	
PTO			
Rear PTO			
Revolution		1 speed: 540 rpm	
Type		Independent	
Mid PTO		Option	
Revolution		1 speed: 2000 rpm	
Hydraulic			
Lift control type: Position		Standard	
Draft		Option	
Implement pump	GPM (ℓ/min.)	8.1 (30.4)	
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)	
Total hydraulic flow	GPM (ℓ/min.)	12.8 (48.3)	
3-point hitch		Category I	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2646 (1200)	
Traveling system			
Transmission		HST Plus (3 ranges)	
Steering		Hydrostatic power steering	
Brake		Wet disc type	
Clutch		-	
Standard tire size*			
Front		7.0-16	
Rear		12.4-24	
Travell speed			
No. of speeds (at rated engine speed)	mph (km/h)	Forward	Reverse
		H-DS L L: 2.1 (3.4) M: 4.3 (6.9) H: 9.9 (15.9)	L: 1.9 (3.0) M: 3.9 (6.2) H: 8.9 (14.3)
		H-DS H L: 3.5 (5.6) M: 7.1 (11.5) H: 16.5 (26.5)	L: 3.2 (5.1) M: 6.4 (10.3) H: 14.9 (23.9)
Dimensions			
Overall length (w/o 3P)	in. (mm)	115.0 (2920)	
Overall width (min. tread)	in. (mm)	59.8 (1520)	
Overall height (top of CAB)	in. (mm)	90.6 (2300)	
Wheelbase	in. (mm)	71.1 (1805)	
Min. ground clearance	in. (mm)	13.5 (342)	
Tread	Front (front tire)	in. (mm)	45.5 (1155)
	Rear (rear tire)	in. (mm)	47.2 (1200) / 51.2 (1300) 54.5 (1385) / 58.3 (1480)
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)	
Weight	lbs. (kg)	3880 (1760)	

* Kubota offers several tire options.

Front loader specifications

Model		LA555	LA805
Maximum Lift Height (Pivot pin)	in. (mm)	96.4 (2448)	104.7 (2659)
Clearance with Attachment Dump	in. (mm)	75.9 (1928)	80.0 (2033)
Reach @ Maximum Height	in. (mm)	28.4 (721)	23.3 (591)
Maximum Dump Angle	deg.	40	42
Reach with Attachment on Ground	in. (mm)	66.6 (1691)	72.4 (1840)
Maximum Rollback Angle	deg.	30	41
Digging Depth (When Bucket is level)	in. (mm)	4.9 (124)	4.7 (120)
Overall Height in Carry Position	in. (mm)	52.7 (1338)	54.6 (1386)
Square Bucket Width / Struck Capacity	in. (mm)/cu.ft (m³)	66 (1675) / 8.1 (0.23)	72 (1830) / 10.9 (0.31)
Lift Capacity (Pivot pin)	lbs. (kg)	1190 (540)	1715 (778)
Lift Capacity (500mm forward)	lbs. (kg)	899 (408)	1290 (585)
Breakout Force (500mm forward)	lbs. (N)	2030 (9029)	2549 (11341)
Raising Time to Full Height without Load	sec.	2.7	3.2
Lowering Time without Load (powerdown)	sec.	2.2	2.0
Attachment Rollback Time	sec.	1.6	1.9
Attachment Dumping Time	sec.	1.3	1.3
Rated Flow	l/m (GPM)	31.5 (8.3)	37.0 (9.8)
Relief Valve PSI	psi (kg/cm²)	2560 (180)	2630 (185)
Specs taken from		L3560	L4060

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: www.kubotausa.com

©2018 Kubota Corporation



Kubota
Genuine Parts
for maximum performance, durability and safety