

## SPECIFICATIONS

MODEL	LX2620HSD	LX2620HSDC	LX2620SUHSD	LX3520DTN	LX3520HSD	LX4020HSD	LX3520HSDC	LX4020HSDC	LX3520SUHSDC
<b>ENGINE</b>									
<b>Type</b>	Indirect injection, vertical, water-cooled, 4 - cycle diesel			Direct injection, vertical, water-cooled, 4 - cycle diesel with turbo chager					
<b>Make, Model</b>	D1305-E4-D36R	D1305-E4-D36Q	D1305-E4-D36R	V1505-CR-TE5-D40R6	V1505-CR-TE5-D40R5	V1505-CR-TE5-D40R4	V1505-CR-TE5-D40Q4	V1505-CR-TE5-D40Q3	V1505-CR-TE5-D40Q4
<b>PTO Horsepower</b>	<i>HP (kW)</i> 19.5 (14.5)			29.6 (22.1)	28.7 (21.4)	32.6 (24.3)	28.7 (21.4)	31.2 (23.3)	28.7 (21.4)
<b>Engine Gross Horsepower*</b>	<i>HP (kW)</i> 24.8 (18.5)			34.9 (26.0)		39.8 (29.7)	34.9 (26.0)	39.8 (29.7)	34.9 (26.0)
<b>Rated RPM</b>	<i>RPM</i> 2500			2600	2700				
<b>Bore &amp; Stroke</b>	<i>in. (mm)</i> 3.1 x 3.5 (78 x 88)			3.1 x 3.1 (78 x 78.4)					
<b>Displacement</b>	<i>cu. in. (cc)</i> 77.0 (1261)			91.4 (1498)					
<b>Air Cleaner</b>	4.5 inch paper filter (with dual filter)			6 inch paper filter (with dual element)					
<b>Lubrication</b>	Forced lubrication								
<b>Cooling System</b>	Pressurized radiator								
<b>Radiator Fan</b>	Radial air flow								
<b>CAPACITIES</b>									
<b>Fuel Tank</b>	<i>gal (ℓ)</i> 7.1 (27)	8.5 (32)	7.1 (27)	8.5 (32.0)					
<b>Cooling System</b>	<i>qts. (ℓ)</i> 4.5 (4.3)	5.7 (5.4)	4.5 (4.3)			5.7 (5.4)			
<b>Engine Oil</b>	<i>qts. (ℓ)</i>	4.2 (4.0)		5.0 (4.7)					
<b>Transmission Case</b>	<i>gal (ℓ)</i>	4.0 (15)		5.5 (21.0)					
<b>DRIVE TRAIN</b>									
<b>Clutch</b>	N / A			Dry type single stage	N / A				
<b>Transmission</b>	HST (3 ranges)			Gear	HST (3 ranges)				
<b>Differential Lock</b>	Standard								
<b>Final Drive</b>	Spur gear								
<b>Brake</b>	Multi-plate wet disk								
<b>PTO</b>									
<b>Type</b>	Independent								
<b>Rear</b>	<i>RPM</i>	540							
<b>Mid</b>	<i>RPM</i>	2500	OPT	N / A	2460			OPT	



\* SAE J1995

Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

## SPECIFICATIONS

MODEL	LX2620HSD	LX2620HSDC	LX2620SUHSD	LX3520DTN	LX3520HSD	LX4020HSD	LX3520HSDC	LX4020HSDC	LX3520SUHSDC
<b>HYDRAULICS</b>									
<b>Type</b>	Open center								
<b>Pump</b>	Dual pump								
<b>Total Pump Output</b>	<i>gpm (ℓ/min.)</i>	8.7 (33.1)		9.1 (34.5)	9.5 (35.8)				
<b>Hydraulic Outlet</b>	Rear outlet								
<b>3-point Hitch</b>	Category I								
<b>Hydraulic Control System</b>	Position control valve								
<b>Lift Capacity at Lift Point</b>	<i>lbs. (kg)</i>	2139 (970)		2348 (1065)	2535 (1150)				
<b>24" Behind Lift Point</b>	<i>lbs. (kg)</i>	1676 (760)		1819 (825)	1962 (890)				
<b>Steering</b>	Hydrostatic power steering								
<b>STANDARD TIRE SIZE</b>									
<b>Front</b>	R1	7-12		6-14		7-12			
	R4	23 x 8.50-14		N / A		23 x 8.50-14			
	R14	23 x 8.50-12		N / A		23 x 8.50-12			
<b>Rear</b>	R1	12.4-16		8.3-24		12.4-16			
	R4	12.4-16		N / A		12.4-16			
	R14	14-17.5		N / A		14-17.5			
<b>TRAVELING SPEEDS (AT RATED ENGINE RPM)</b>									
<b>Forward (R1)</b>	<i>mph (km/h)</i>	11.2 (18.0)		14.7 (23.6)	17.0 (0-27.4)				
<b>Reverse (R1)</b>	<i>mph (km/h)</i>	8.4 (13.5)		14.6 (23.3)	13.0 (0-20.8)				
<b>DIMENSIONS (W/ R1 TIRES)</b>									
<b>Overall Length (w/o 3P)</b>	<i>in. (mm)</i>	101.8 (2586)	103.9 (2639)	101.8 (2586)	98.2 (2494)	101.6 (2580)			
<b>Overall Width (min. tread)</b>	<i>in. (mm)</i>	53.7 (1365)			39.4 (1000)	53.7 (1365)			
<b>Overall Height</b>	<i>in. (mm)</i>	88.4 (2245)	84.6 (2150)	88.4 (2245)	84.0 (2134)	88.4 (2240)	88.2 (2240)	85.6 (2175)	
<b>Wheelbase</b>	<i>in. (mm)</i>	65.6 (1666)			61.0 (1550)	66.7 (1695)			
<b>Ground Clearance</b>	<i>in. (mm)</i>	14.6 (370)		12.8 (325)	8.9 (225)			12.8 (325)	
<b>Turning Radius with Brake</b>	<i>feet (m)</i>	6.9 (2.1) Front drive disengaged			7.5 (2.1) Front drive disengaged	7.5 (2.3) Front drive disengaged			
<b>Weight</b>	<i>lbs. (kg)</i>	1775 (805)	2249 (1020)	1775 (805)	2154 (977)	2191 (994)		2624 (1190)	2590 (1175)