

# RA Series

# Specifications

## RA1035 / RA1042T



| Kubota Models                  | RA1035    | RA1042T     |
|--------------------------------|-----------|-------------|
| FarmLine                       | •         | •           |
| ProLine                        | -         | -           |
| <b>Dimensions and Weight</b>   |           |             |
| Working width (ft)             | 11'6"     | 13'9"       |
| Transport width (ft)           | 5'9"      | 6'7"        |
| Transport length (ft)          | 11'       | 13'2"       |
| Parking height (ft)            | 5'7"      | 7'7"        |
| Weight (lbs)                   | 926       | 1257        |
| Swath width (m)                |           |             |
| Capacity theo. (acres/h)       | 9.6       | 11.4        |
| <b>Hitching system</b>         |           |             |
| Pivoting 3-pt headstock (cat.) | 1/2       | -           |
| Lower links (2-pt.)            | -         | -           |
| Linkage drawbar                | -         | •           |
| Gauge wheel 16°                | 0         | 0           |
| <b>Rotors/Tine arms/Tines</b>  |           |             |
| Rotor diameter (ft)            | 9'2"      | 11'         |
| Swath delivery                 | left      | left        |
| Number of rotors               | 1         | 1           |
| Number of arms per rotor       | 10        | 11          |
| Number of double tines/arm     | 4         | 4           |
| Tine diameter (in)             | 0.35"     | 0.35"       |
| Continuous cam track           | -         | -           |
| Detachable tine arms           | •         | •           |
| Height adjustment              | mech.     | mech.       |
| <b>Wheels and axles</b>        |           |             |
| Tires (rotors)                 | 16x6.50-8 | 18.5x8.50-8 |
| Fixed tandem axle              | 0         | •           |
| Pivoting tandem axle           | -         | -           |
| Stand. Tires (carrying frame)  | -         | -           |
| <b>Optional equipment</b>      |           |             |
| Carrier arm compensating       | 0         | -           |
| Locking catch for slopes       | 0         | -           |
| <b>Safety accessories</b>      |           |             |
| Warning panels                 | 0         | 0           |
| Road lights                    | 0         | 0           |

• = standard 0 = optional - = not available

\* = double swath \*\* = with detached tine arms and lowered headstock

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.