

SPECIFICATIONS

SZ Series	SZ19 / 36" DECK	SZ22 / 48" DECK	SZ26 / 52" DECK / 61" DECK
Engine Type	Kawasaki FX600V	Kawasaki FX691V	Kawasaki FT730V-EFI
Horsepower (gross)*	19	22	26
Fuel Capacity (gal)	5.1	6.5	
Speed (MPH)	9	10.5	11
Transmission	Hydro-Gear ZT3100	Hydro-Gear ZT3600	
Deck Type	Floating Fabricated Steel with Wear band		
Deck	7 ga deck with 7 ga skirts	10 ga deck with 10 ga top and 7 ga skirts	
Cutting Height	1.5-4.5"		
Starter	Electric		
Spindle Bearings	1" shaft with maintenance-free precision ground double-sealed bearings		
Deck Drive	Warner Mag Stop 125 ft-lb electric clutch	Warner Mag Stop 200 ft-lb electric clutch	
Front Tires / Rear Tires	11 x 4-5 (no-flat) / 20 x 8-10	13 x 6.5-6" (no-flat) / 23 x 8.5-12	13 x 6.5-6" (no-flat) / 23 x 10.5-12
Brake	Cog Style Parking Lock / Hand Lever		
Weight (lb)	831	965	997 (52") / 1034 (61")
Length / Height	62.5" / 45"	63.75" / 45.75"	
Warranty	2 Yr - Unlimited Hours		

*These Kawasaki engines have been tested in accordance with SAE J1995, verified by TÜV Rheinland Group, and certified by SAE International. The gross power ratings of these engines were determined by using measurements according to SAE J1995 which were witnessed by SAE-approved witnesses from TÜV Rheinland Group. Torque ratings of these engines were not certified by SAE. Actual power and torque output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.