

# WR Series

# Specifications

## WR1400



Kubota Models	WR1400
<b>Weight and Dimensions</b>	
Transport Length (in)	170"
Transport Width (in)	99"
Transport Height (in)	76"
Weight (lbs)	2249
<b>Bale</b>	
Max Bale Size (L x D) (in)	47" x 50"
Max Bale Weight (lbs)	2650
<b>Wrapping Table</b>	
Mounted Wrapper	-
Pull-Type Wrapper	•
Support Rollers/Belts (number)	2/4
Automatic Film Cutter	•
Max. Wrapping Speed (rpm)	30
<b>Pre-stretcher</b>	
1 pre-stretcher 750 mm	•
Pre-Stretcher 29.5" (750mm)	•
Max. wrapping speed (rpm)	30
<b>Operations</b>	
Manual Cable Control (M)	•
Electro Hydraulic Joystick (J)	•
Programmable Computer (C )	-
Remote Control (C )	-
Oil Consumption (l/min)	28
<b>Wheels and Axles</b>	
10.0/80-12	•
<b>Wheels and Axles</b>	
Fill Roll Magazine	o
Adapter Kit for 20" (500mm) Film Spool	o
Bale And Wrap Counter	•
Auto-Stop at End of Wrapping Cycle	•
Film End/Tear Sensor (C )	-
Road Lights	o

• = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.