

Specifications

Model		ZG222		ZG227		ZG327		
		ZG222A-48		ZG227A-54	ZG227LA-60	ZG327PA-60	ZG327RPA-60	
Engine	Model	Kubota KGZ770-E2-MA3		Kubota KGZ770-E2-MA2		Kubota KGZ770-E2-MA1		
	Type	Gasoline, air-cooled V-Twin with heavy-duty canister air filter						
	Max. horsepower* (Gross) HP	21.1 @3600 rpm		26.0 @3600 rpm				
	Total displacement cu.in. (cc)	46.9 (768)						
	Starting system	Key switch						
Dimensions	Overall length in. (mm)	82.5 (2096)		83.7 (2126)		87.8(2230)		
	Overall width in. (mm)	(w/ mower)	61.1 (1552)	67.3 (1710)	75.2 (1911)	75.2 (1911)	63.1 (1604)	
		(w/o mower)	47.7 (1210)				57.5 (1460)	
	Overall height in. (mm)	(w/ ROPS upright)	69.9 (1775)				75.4 (1915)	
		(w/ ROPS folded)	52.8 (1340)				61.2 (1555)	
Wheel base	in. (mm)	51.0 (1295)		52.2 (1325)		55.5 (1410)		
Tread	Front in. (mm)	34.3 (870)		35.6 (905)		38.4 (975)		
	Rear in. (mm)	36.6 (930)				45.3 (1150)		
Tire size	Front	13 x 5.0-6 Pneumatic				15 x 6.0-6 Not-flat		
	Rear	23 x 10.5-12				26 x 12.0-12		
Weight (w/ mower) (without fuel)	lbs. (kg)	1168 (530)		1190 (540)	1235 (560)	1565 (710)		
Transmission system		2-HST w/ Gear reduction						
Speed control		2-hand lever						
Travel speed range	Forward mph (km/h)	0-9.0 (0-14.5)				0-10.6 (0-17.0)		
	Reverse mph (km/h)	0-5.0 (0-8.0)				0-5.3 (0-8.5)		
Brake type		Wet multi disks, foot applied, released						
PTO	Type	Shaft drive						
	Clutch type	Hydraulic independent PTO clutch with wet multi disks						
	PTO brake	Wet single disk						
Mower deck	Model	RCK48P-222Z	RCK54P-227Z	RCK60P-227Z	RCK60P-327Z	RCK60R-331Z		
	Mower lift system	Hydraulic						
	Mower deck type	Pro commercial — Fabricated deck						
	Deck depth in. (mm)	6.0 (152)				6.5 (165)	5.5 (140)	
	Belt type	Multi-Belt						
	Deck steel thickness in. (mm)	0.15 (3.8)				0.17 (4.2)		
	Anti-scalp roller			Rigid		Swivel		
	Cutting width of mower	48 in.		54 in.		60 in.		
	Number of blades	3 blades						
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments						
	Mounting system of mower	Quick joint, parallel linkage						
Blade tip speed (max.) FPM	17000				18100	16700		
Engine stop system		Key stop						
Fuel tank capacity	gals. (ℓ)	7.1 (27)				12.7 (48)		
Battery		U1L-10 (12 V, RC: 22 min., CCA: 300, CA: 365)						
Alternator capacity	Amps	13.4 A at 12 Volts						
Hour meter		Standard						
Fuel gauge		Electric						

* Power(HP) specifications for individual gasoline engine models are rated pursuant to Society of Automobile Engineers(SAE) J1940 based on gross output testing performed in accordance with SAE J1995 without the air cleaner and muffler. Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: kubotaUSA.com

©2019 Kubota Corporation

